AD-A061 443 LOCKHEED MISSILES AND SPACE CO INC PALO ALTO CALIF PA--ETC F/G 19/4
THE UNDERWATER SHOCK ANALYSIS (USA) CODE, A REFERENCE MANUAL.(U)
FEB 78 J A DERUNTZ, T L GEERS, C A FELIPPA DNA001-76-C-0285
UNCLASSIFIED LMSC/D624328 DNA-4524F NL

1 OF 2
AD
A061443

AD-E300 369

(12) LEVEL II

DNA 4524F

AD A061443

DDC FILE COPY

(6)

THE UNDERWATER SHOCK ANALYSIS (USA) CODE, A REFERENCE MANUAL

(10) J. A. /DeRuntz, T. L. /Geers, C. A. /Felippa

Lockheed Palo Alto Research Laboratory
3251 Hanover Street
Palo Alto, California 94304

(14) LMSC/D624328

(11) 28 Febr~~uary~~ 1978

(12) 142p.

(9) Final ~~Report~~ for ~~Period~~ 26 Apr~~il 1~~976–28 Febr~~uary 1~~978

(15) CONTRACT ~~No.~~ DNA 001-76-C-0285

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

(18) DNA, SBIE

(17) X978

THIS WORK SPONSORED BY THE DEFENSE NUCLEAR AGENCY
UNDER RDT&E RMSS CODE B344076462 L62BAXYX97801 H2590D.

(16)

(19) 4524F, AD-E300 369

Prepared for
Director
DEFENSE NUCLEAR AGENCY
Washington, D. C. 20305

78 10 05 047

210 118

JOB

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER DNA 4524F	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) THE UNDERWATER SHOCK ANALYSIS (USA) CODE, A REFERENCE MANUAL		5. TYPE OF REPORT & PERIOD COVERED Final Report for Period 26 Apr 76—28 Feb 78 6. PERFORMING ORG. REPORT NUMBER LMSC-D624328
7. AUTHOR(s) J. A. DeRuntz T. L. Geers C. A. Felippa		8. CONTRACT OR GRANT NUMBER(s) DNA 001-76-C-0285
9. PERFORMING ORGANIZATION NAME AND ADDRESS Lockheed Palo Alto Research Laboratory 3251 Hanover Street Palo Alto, California 94304		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Subtask L02BAXYX978-01
11. CONTROLLING OFFICE NAME AND ADDRESS Director Defense Nuclear Agency Washington, D.C. 20305		12. REPORT DATE 28 February 1978 13. NUMBER OF PAGES 146
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		15. SECURITY CLASS (of this report) UNCLASSIFIED 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

This work sponsored by the Defense Nuclear Agency under RDT&E RMSS Code B344076462 L02BAXYX97801 H2590D.

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Fluid Structure Interaction
Underwater Shock
Doubly Asymptotic Approximation
Discrete Analysis Compter Code
Staggered Solution Procedure

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

This report constitutes a reference manual for the Underwater Shock Analysis (USA) Code, a computer program for calculation of the transient response of a submerged structure to a spherical shock wave of arbitrary pressure profile and source location. The code considers the structure to be linear-elastic and treats the surrounding fluid as an infinite acoustic medium. A discrete-element (finite-element, finite-difference) computational model is used for the structure, while the computational model for the fluid is based upon the Doubly Asymptotic Approximation.

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

78 10 03 047

SUMMARY

This report constitutes a reference manual for the Underwater Shock Analysis (USA) Code, a computer program for calculation of the transient response of a submerged structure to a spherical shock wave of arbitrary pressure profile and source location. The code considers the structure to be linear-elastic and treats the surrounding fluid as an infinite acoustic medium. A discrete-element (finite-element, finite-difference) computational model is used for the structure, while the computational model for the fluid is based upon the Doubly Asymptotic Approximation.

PREFACE

The authors express their appreciation to Dr. K. C. Park for his consultation and to Dr. C. L. Yen for providing the modal results for the infinite-cylinder problem and constructing the finite-element structural models used in the examples.

TABLE OF CONTENTS

LIST OF ILLUSTRATIONS

SECTION I

INTRODUCTION

This report documents a computer program, the Underwater Shock Analysis (USA) Code, that calculates the transient response of a submerged structure to a spherical shock wave of arbitrary pressure-profile and source location. The structure is considered to be linear-elastic and the surrounding fluid is treated as an infinite acoustic medium. The computational model for the structure is constructed through the use of an auxiliary discrete-element (finite-element, finite-difference) code of choice [1, 2], while that for the fluid is constructed through the use of the Doubly Asymptotic Approximation (DAA) [3, 4].

1.1 DOUBLY ASYMPTOTIC APPROXIMATION

The principal advantage of the DAA is that it models the infinite acoustic medium surrounding the structure as a membrane covering the wet surface of the structure. Hence fluid motion is described merely in terms of wet-surface response variables, which are then linked by compatibility relations to the structural response variables. Furthermore, this description is a simple matrix ordinary differential equation with desirable computational properties.

The principal disadvantage of the DAA is that it constitutes an approximation to the "exact" boundary-element representation of the surrounding medium [5, 6]. The DAA does approach exactness for both high-frequency (early-time) and low-frequency (late-time) structural motions, however, and effects a smooth transition between the two asymptotes. In addition, it has exhibited satisfactory accuracy in a variety of check calculations [4, 5, 7]. Hence, in view of its desirable computational properties, the DAA is considered suitable for engineering analysis.

1.2 STAGGERED SOLUTION PROCEDURE

The governing matrix equation for structural response is a second-order ordinary differential equation in time, while that for fluid response is a first-order ordinary differential equation. Simultaneous solution of these equations by direct step-by-step numerical integration, however, is unacceptably expensive. Hence the USA Code utilizes a staggered solution procedure [8] for step-by-step solution of the equations in time.

Now a staggered solution procedure involves a response extrapolation at each time step, which usually leads to numerical instability for time increments exceeding a critical value. Because this critical value may be unacceptably small for many computations, the governing equations for fluid response have been modified in such a way that unconditional stability is achieved. Thus, through avoidance of both direct simultaneous solution and conditional stabity constraints, highly efficient computation is possible for the greatest variety of cases.

As an illustration of the capabilities of USA, a transient response calculation has been performed for a 2490 degree-of-freedom (DOF) structural model with a stiffness-matrix average half-bandwidth of 85 DOF. The central-processing-unit (CPU) time on a Univac 1108 required for the 280 time-step calculation (with a single change in time increment during the calculation) was 28 minutes. The corresponding time on a CDC 6600, on which the code also operates, would be about 10 minutes.

1.3 INPUT/OUTPUT

The USA Code requires three types of input data in order to perform its function. First, structural mesh-geometry, mass-matrix and stiffness-matrix data must be provided by the structural analysis code used by the analyst. Second, fluid mesh-geometry and boundary-element data must be furnished. Finally, charge standoff and incident pressure-profile, as well as time integration specifications must be provided.

The code, in its turn, outputs structural displacement and velocity histories and fluid pressure histories for the wet surface. Response data post-processors furnish pseudo-velocity shock spectra, and response-history and shock-spectrum plots. In addition, post-processors embedded in the structural analysis code may be used to obtain, for example, stress and strain response histories, as well as response-history and stress-contour plots. As currently configured, the USA Code can routinely handle problems with up to 2500 structural and 145 fluid DOF within a core allocation of 65000 decimal words. If primary core size is increased to 100000 decimal words, approximately 200 fluid DOF may be processed with a corresponding increase in the structural DOF.

1.4 SPECIAL FEATURES

A number of special features are incorporated in the code. First, a capability has been provided to handle a fluid mesh on the wet surface that is not coincident with the surface mesh for the structural model. This permits, for example, the use of a refined structural mesh in a region of high stress gradients, even though a relatively coarse mesh is retained for the fluid.

Second, options for variable-step time integration and computation restart are furnished. The former allows the use of small time increments during periods where the response is expected to be varying rapidly in time, and the use of large time increments for periods characterized by a slowly varying response. The latter permits the division of a response computation into segments, so that the analyst may examine the results at selected points along the way. Such examination is facilitated by the use of the "printer-plot" routine that augments the usual printout data with response plots "drawn" by the printer.

Finally, the code incorporates fluid wet-surface elements for both general and beam-like motions of the structure (see Appendix A). This feature is especially useful for compartment-by-compartment analysis of a submarine. Such an analysis utilizes a general-structure discrete-element model of a particular compartment of interest, with the remainder of the submarine modeled as a beam. Hence a detailed analysis of an entire submarine may be performed with several discrete-element models of moderate size, avoiding the use of a single gigantic model.

1.5 SPECIAL NON-FEATURES

Several features of modest complexity have yet to be incorporated into the USA Code. First, an option for automatic time-step integration would free the analyst from having to select integration time increments in accordance with his expectations regarding response behavior. Second, fluid wet-surface elements for bar-like motions of a structure would allow proper treatment of the longitudinal vibrations of a submarine analyzed on a compartment-by-compartment basis. Finally, a capability to handle very large problems would be useful in those cases where structural segmentation is not possible.

Two important features of greater complexity have yet to be incorporated into the code. The first is a treatment of hull cavitation, which may substantially affect structural response for incident shock waves of short duration. The second is the inclusion of free-surface (bulk cavitation) effects, especially as they influence the form of the incident-wave excitation. The introduction of these two features requires the treatment of highly non-linear phenomena, which presents a stiff challenge for future work.

SECTION II

THEORY

This section describes the theoretical foundation of the USA Code. It is constructed as an overview, with coverage of details left to referenced papers and reports, and to appendices.

2.1 STRUCTURAL RESPONSE EQUATION

The matrix ordinary differential equation for the dynamic response of a linear-elastic structure is [1]

$$\underset{\sim}{M}_s \, \ddot{\underline{x}} + \underset{\sim}{C}_s \, \dot{\underline{x}} + \underset{\sim}{K}_s \, \underline{x} = \underline{f} \tag{2.1}$$

where $\underline{x}$ is the structural displacement vector, $\underset{\sim}{M}_s$, $\underset{\sim}{C}_s$ and $\underset{\sim}{K}_s$ are the structural mass, damping and stiffness matrices, respectively, $\underline{f}$ is the external force vector, and a dot denotes a temporal derivative. Generally, $\underset{\sim}{M}_s$, $\underset{\sim}{C}_s$ and $\underset{\sim}{K}_s$ are highly banded, symmetric matrices of large order; at present, the USA Code considers $\underset{\sim}{M}_s$ to be diagonal and $\underset{\sim}{C}_s$ to be zero.

For excitation of a submerged structure by an acoustic wave, $\underline{f}$ is given by

$$\underline{f} = -\underset{\sim}{G} \, \underset{\sim}{A}_f \, (\underline{p}_I + \underline{p}_S) \tag{2.2}$$

where $\underline{p}_I$ and $\underline{p}_S$ are nodal pressure vectors for the wet-surface fluid mesh pertaining to the (known) incident wave and the (unknown) scattered wave, respectively, $\underset{\sim}{A}_f$ is the diagonal area matrix associated with elements in the fluid mesh, and $\underset{\sim}{G}$ is the transformation matrix that relates the structural and fluid nodal surface forces. More will be said about $\underset{\sim}{G}$ in the next subsection.

2.2 DAA EQUATION

The Doubly Asymptotic Approximation may be written [3,4]

$$\underset{\sim}{M}_f \, \dot{\underline{p}}_S + \rho c \, \underset{\sim}{A}_f \, \underline{p}_S = \rho c \, \underset{\sim}{M}_f \, \dot{\underline{u}}_S \tag{2.3}$$

where $\underline{u}_S$ is the vector of scattered-wave fluid-particle velocities normal to the structure's wet surface, ρ and c are the density and sound velocity of the fluid, respectively, and $\underset{\sim}{M}_f$ is the symmetric fluid mass matrix for the wet-surface fluid mesh (see Appendix A). This matrix is produced by a boundary-element treatment of Laplace's equation for the irrotational flow generated in an infinite, inviscid, <u>incompressible</u> fluid

by motions of the structure's wet surface; it is fully populated with non-zero matrix elements. When transformed into structural coordinates, the fluid mass matrix yields the added mass matrix, which, when combined with the structural mass matrix, yields the virtual mass matrix for motions of a structure submerged in an incompressible fluid [9].

As mentioned in Section I, the approximate relation (2.3) is called "doubly asymptotic" because it approaches exactness in both the high-frequency (early-time) and low-frequency (late-time) limits. For high-frequency motions, $|\dot{\underline{p}}_S| >> |\underline{p}_S|$, so that (3) approaches the relation $\underline{p}_S = \rho c \underline{u}_S$, which is the correct limit for short acoustic wavelengths. For low-frequency motions, $|\dot{\underline{p}}_S| << |\underline{p}_S|$, so that (2.3) approaches the incompressible-flow relation $\underset{\sim}{A}_f \underline{p}_S = \underset{\sim}{M}_f \dot{\underline{u}}_S$, which is the correct limit for long acoustic wavelengths.

For excitation by an incident acoustic wave, $\underline{u}_S$ is related to structural response by the kinematic compatibility relation

$$\underset{\sim}{G}^T \dot{\underline{x}} = \underline{u}_I + \underline{u}_S \tag{2.4}$$

where the superscript "T" denotes matrix transposition. Equation 2.4 expresses the constraint that normal fluid-particle velocity match normal structural velocity on the wet surface of the structure. The fact that the transformation matrix relating those velocities is $\underset{\sim}{G}^T$ follows from the invariance of virtual work with respect to either of the wet surface coordinate systems. Generally, $\underset{\sim}{G}$ is a rectangular matrix whose height greatly exceeds its width, inasmuch as the number of structural DOF usually exceeds considerably the number of fluid DOF.

2.3 INTERACTION EQUATIONS

The introduction of (2.2) into (2.1) and (2.4) into (2.3) yields the interaction equations

$$\begin{aligned} \underset{\sim}{M}_s \ddot{\underline{x}} + \underset{\sim}{C}_s \dot{\underline{x}} + \underset{\sim}{K}_s \underline{x} &= - \underset{\sim}{G} \underset{\sim}{A}_f (\underline{p}_I + \underline{p}_S) \\ \underset{\sim}{M}_f \dot{\underline{p}}_S + \rho c \underset{\sim}{A}_f \underline{p}_S &= \rho c \underset{\sim}{M}_f (\underset{\sim}{G}^T \ddot{\underline{x}} - \dot{\underline{u}}_I) \end{aligned} \tag{2.5}$$

These equations may be solved simultaneously at each time step by the transfer of $- \underset{\sim}{G} \underset{\sim}{A}_f \underline{p}_S$ and $\rho c \underset{\sim}{M}_f \underset{\sim}{G}^T \ddot{\underline{x}}$ to the left sides of their respective equations. Such a procedure is exceedingly expensive, however, because of the large connectivity of the coefficient matrix involved. As mentioned in Section I, efficient computation is possible through the application of a staggered solution procedure that is unconditionally stable with respect to the choice of time increment.

The simplest implementation of the staggered solution procedure recommended in [8] may be effected as follows. $\underset{\sim}{M}_s$ is taken to be diagonal and, to allow for the possibility that $\underset{\sim}{M}_s$ may have zero entries for rotational DOF, $\underset{\sim}{G}$ is constructed such that only the transla-

tional DOF for the structure couple with the fluid DOF [see (2.4)]; then the first of (2.5) may be partitioned to obtain $\underset{\sim}{G}^T \ddot{x}$, which may then be introduced into the second of (2.5). Premultiplication of the resulting equation by $\frac{1}{\rho c} \underset{\sim}{A}_f \underset{\sim}{M}_f^{-1}$ then yields

$$\frac{1}{\rho c} \underset{\sim}{A}_f \dot{\underline{p}}_S + (\underset{\sim}{D}_f + \underset{\sim}{D}_s) \underline{p}_S = -\underset{\sim}{A}_f \underset{\sim}{G}^T \underset{\sim}{M}_s^{-1} (\underset{\sim}{C}_s \dot{\underline{x}} + \underset{\sim}{K}_s \underline{x}) - (\underset{\sim}{D}_s \underline{p}_I + \underset{\sim}{A}_f \dot{\underline{u}}_I) \tag{2.6}$$

where $\underset{\sim}{D}_f = \underset{\sim}{A}_f \underset{\sim}{M}_f^{-1} \underset{\sim}{A}_f$ and $\underset{\sim}{D}_s = \underset{\sim}{A}_f \underset{\sim}{G}^T \underset{\sim}{M}_s^{-1} \underset{\sim}{G} \underset{\sim}{A}_f$ are symmetric, and where $\underset{\sim}{M}_s^{-1}$ is a diagonal matrix with each nonzero element given as the reciprocal of the corresponding nonzero element of $\underset{\sim}{M}_s$ and each zero element mirroring the corresponding zero element of $\underset{\sim}{M}_s$. The first of (2.5) and (2.6) are herein termed "the augmented interaction equations".

2.4 SPHERICAL INCIDENT WAVE

Each element of the vectors $\underline{p}_I$ and $\dot{\underline{u}}_I$ for a spherical incident wave are given by

$$\begin{aligned} p_{Ii}(t) &= \frac{S}{R_i} \, p_I \left(t - \frac{R_i - S}{c} \right) \\ \dot{u}_{Ii}(t) &= \left[\frac{1}{\rho c} \dot{p}_{Ii}(t) + \frac{1}{\rho R_i} p_{Ii}(t) \right] \gamma_i \end{aligned} \tag{2.7}$$

where S is the "charge standoff", i.e., the distance between the origin of the incident spherical wave and the nearest point on the structure's wet surface, R_i is the distance from the origin of the incident spherical wave to the $i\underline{th}$ fluid node on the wet surface. γ_i is the cosine of the angle between the vector corresponding to R_i and the wet-surface normal at the $i\underline{th}$ fluid node, and $p_I(t)$ is the incident-wave pressure-profile defined at $R_i = S$. For a shock wave, $p_I(t)$ is discontinuous at $t = 0$ and the $\dot{u}_{Ii}(t)$ contain singularities.

In order to remove shock-wave singularities from $\dot{\underline{u}}_I$ in (2.6), a modified pressure vector is defined as

$$\underline{p}_M = \underset{\sim}{\Gamma} \underline{p}_I + \underline{p}_S \tag{2.8}$$

where $\underset{\sim}{\Gamma}$ is a diagonal matrix with direction-cosine elements γ_i. The introduction of (2.8) into (2.6) and the first of (2.5), followed by utilization of the second of (2.7) then yields the modified, augmented, interaction equations

$$\underset{\sim}{M}_s \ddot{\underline{x}} + \underset{\sim}{C}_s \dot{\underline{x}} + \underset{\sim}{K}_s \underline{x} = - \underset{\sim}{G} \underset{\sim}{A}_f \left[\underline{p}_M + (\underset{\sim}{I} - \underset{\sim}{\Gamma}) \underline{p}_I \right] \tag{2.9}$$

$$\frac{1}{\rho c} \underset{\sim}{A}_f \dot{\underline{p}}_M + (\underset{\sim}{D}_f + \underset{\sim}{D}_s) \underline{p}_M = - \underset{\sim}{A}_f \underset{\sim}{G}^T \underset{\sim}{M}_s^{-1} (\underset{\sim}{C}_s \dot{\underline{x}} + \underset{\sim}{K}_s \underline{x}) - \underset{\sim}{H} \underline{p}_I$$

in which $\underset{\sim}{I}$ is the identity matrix, and

$$\underset{\sim}{H} = \underset{\sim}{D}_s - (\underset{\sim}{D}_s + \underset{\sim}{D}_f - \frac{1}{\rho} \underset{\sim}{A}_f \underset{\sim}{R}^{-1}) \underset{\sim}{\Gamma} \tag{2.10}$$

where $\underset{\sim}{R}$ is the diagonal matrix formed by the distances R_i. Equations (2.9) (with $\underset{\sim}{C}_s = 0$) are the equations solved by the USA Code to determine the structural responses $\underline{x}$ and $\dot{\underline{x}}$, and the wet-surface pressures $\underline{p} = (\underset{\sim}{I} - \underset{\sim}{\Gamma}) \underline{p}_I + \underline{p}_M$.

SECTION III

ORGANIZATION

The USA Code has been written in standard FORTRAN IV for use on both Univac and CDC computers. Machine dependency has been isolated in one utility program described below. Program modularity has been strictly enforced, with communication between computational modules controlled by means of a data management system.

The basic structure of the code is shown in Fig. 3-1. The structural preprocessor is a separate code selected by the user to provide the computational model for the structure. The skyline utility merely reformats $\underset{\sim}{M}_s$ and $\underset{\sim}{K}_s$ as provided by the structural preprocessor for processing by the USA Code (recall that $\underset{\sim}{C}_s$ is taken as zero). The fluid mass preprocessor forms $\underset{\sim}{A}_f$, $\underset{\sim}{M}_f$, and $\underset{\sim}{G}$, while the matrix augmentation preprocessor forms $\underset{\sim}{D}_f$, $\underset{\sim}{D}_s$, and $\underset{\sim}{A}_f \underset{\sim}{G}^T \underset{\sim}{M}_s^{-1}$ [see (2.9)]. The main processor is the time integrator, which forms $\underset{\sim}{\Gamma}$ and $\underset{\sim}{H}$ and then solves (2.9) in step-by-step fashion using the staggered solution procedure. The response postprocessor provides tabular and graphic output for the computed kinematic responses as well as pseudo-velocity shock spectra. Finally, the data manager controls the flow of data between processors. More detailed descriptions of the various program components follow, while information required for utilization of the code is contained in Appendices B through E.

3.1 THE DATA MANAGER DMGASP

DMGASP is a self-contained utility module that functions as a manager of auxiliary storage and as the focal point for all block input/output activities [10]. Constituting the lowest level of the NOSTRA Data Management System [11], it carries out the direct transfer of data blocks between core and peripheral storage. (The terminology "direct transfer" is used here to denote unformatted and unbuffered data transmission.) The basic auxiliary storage management operations embodied in DMGASP are

- Activate storage device
- Position device
- Read data block from device
- Write data block on device
- Deactivate device

In the USA Code, DMGASP is operated as a stand-alone I/O package that receives directives directly from the master processors. Assembly language versions of DMGASP currently exist for UNIVAC 1100 EXEC-8, CDC SCOPE 3.4, and CDC NOS operating systems; hence the USA Code may be used only on these systems at this time.



Figure 3-1. Organization of USA Code

3.2 THE STRUCTURAL PREPROCESSOR

This is a user-provided code that assembles the structural mass and stiffness matrices and generates information that relates the internal and external descriptions of the structural DOF. Input typically includes

- Mesh geometry
  - Coordinate systems
  - Node locations
- Element definitions
  - Type
  - Connectivity
- Material properties
  - Mass density
  - Moduli
- Constraints
  - Symmetry conditions
  - Element external constraints
  - Element internal constraints

Fluid internal to the submerged structure must be included in the structural model. At this time, USA treats only diagonal mass matrices associated with a lumped mass representation of the structure, and only single precision matrices can be processed.

3.3 THE SKYLINE UTILITY

This preprocessor converts the structural mass and stiffness matrices generated by the structural preprocessor into the internal "skyline" format required by the USA time integration processor [12,13]. As there are a variety of ways to store large, sparse, symmetric matrices, virtually any structural preprocessor that is to be used with the USA Code will require a utility package to change the storage format. At this time, conversion utilities have been written for SPAR [14] and NASTRAN [15]. User instructions for constructing the skyline utility for other structural codes are given in Appendix F.

Figure 3.1 shows 2 paths to mass storage from the skyline utility. The SPAR converter uses DMGASP for both input and output, whereas the NASTRAN converter uses unformatted buffered FORTRAN commands for input and DMGASP for output.

Constraints are also handled differently in these two utilities. NASTRAN provides a reduced stiffness matrix which already incorporates any prescribed constraints. SPAR does not; however, USA has the ability to apply constraints due to symmetry or attachment to ground during the time integration. Structural DOF that must be set to zero are flagged by the skyline utility [13].

3.4 THE FLUID MASS PREPROCESSOR FLUMAS

This code constructs the fluid mass matrix for a structure submerged in an infinite, inviscid, incompressible fluid by the boundary element technique [9]. In addition, it generates fluid mesh data and a set of transformation coefficients relating the structural and fluid DOF. The computation of these coefficients is based upon the use of centroidal node for the fluid elements and the assumption of a bilinear variation of displacement over the surface of each structural element. This assures that the description of the fluid pressure forces in the two mesh systems is statically equivalent without inducing moments at the structural nodes.

FLUMAS contains a refined formulation for the fluid mass matrix, which includes the primary effects of element curvature. In addition, it has the capability to treat structures containing both surface-of-revolution and general-geometry components, as described in Appendix A. The code can also efficiently construct the fluid mass matrix for a body with two planes of symmetry by using a mesh which covers 1/4 of the surface. Symmetric or anti-symmetric fluid motions can then be imposed in the quadrants not covered by the mesh. Two-dimensional "plane-strain" behavior of long cylinders can also be simulated by another branch in the code. Finally, a useful diagnostic tool contained within the code is the capability to solve the fluid-boundary-mode problem $\underset{\sim}{M}_f \underline{u} = \lambda \underset{\sim}{A}_f \underline{u}$ [9].

Typical input data for this processor includes

- Mesh geometry
  - Fluid Wet-Surface Mesh
  - Structure Wet-Surface Mesh
- Element definitions
  - General curved surface
  - Surface of revolution
- Material property
  - Mass density
- Constraints
  - Quarter model
  - Long cylinder

A detailed description of the required input data is given in Appendix B.

3.5 THE AUGMENTED MATRIX PREPROCESSOR AUGMAT

This preprocessor accepts data from the structural and fluid analyzers to construct the specific matrices required for solution of the augmented Eqs. (2.9). The output of this code includes not only the required matrices in skyline form, but also a distillation of the output from both the structural and fluid processors. This has been done so that only one

permanent file need be referenced as input to the time integrator; this results in improved data handling and core usage. Input to this code involves the following information

- Mass matrices
  - Fluid
  - Structure
- Structural DOF correspondence table
  - External and internal node descriptions
  - Factorization order
  - DOF reduction due to constraints
- Fluid mesh geometry
  - Global coordinates of fluid nodes
  - Direction cosines for nodal surface normals
  - Areas of fluid elements
- Fluid/structure DOF transformation coefficients
- Fluid material properties
  - Mass density
  - Speed of sound

Although this constitutes a substantial amount of information, almost all of it is retrieved from permanent data files. A detailed discussion of the required input data is contained in Appendix C.

3.6 THE TIME INTEGRATION PROCESSOR TIMINT

This main processor constitutes an implementation of the unconditionally stable staggered solution technique developed in [8]. The primary output is a permanent data file that contains nodal values for structural displacement, structural velocity and wet-surface pressure at every time step. In addition, a parallel file is created that retains restart information at time intervals dictated by the user. The code has a variable time step capability and can treat a spherical incident wave of arbitrary pressure profile and charge location. Finally, selected response histories can be listed and then displayed for immediate examination using a "printer-plot" graphics package embedded both in TIMINT and in POSTPR (see Sect. 3.7).

The computational strategy for the staggered solution procedure is embodied in the following eight steps, assuming the solution is known at time t:

(1) Estimate the unknown structural restoring force $\underset{\sim}{K}_s \underline{x}$ at $t + \Delta t$ from the extrapolation of current and past values

(2) Transform this extrapolation into fluid node values and form the right-hand side of the fluid equation, which also involves the known incident pressure at $t + \Delta t$

(3) Solve the fluid equation and obtain a preliminary estimate of the total pressure vector at $t + \Delta t$

(4) Transform fluid pressures into structural nodal forces

(5) Solve the structural equation for the displacement and velocity vectors at $t + \Delta t$

(6) Transform the computed structural restoring forces at $t + \Delta t$ into fluid node values and reform the right hand side of the fluid equation

(7) Re-solve the fluid equation and obtain refined values for the total pressures at $t + \Delta t$

(8) Save system responses

Steps 1, 3, and 5 constitute the basic staggered solution technique, while Steps 2 and 4 are required because of the difference between the fluid and structural surface meshes. The iteration on the fluid solution reflected in Steps 6 and 7 has been added to enhance accuracy. Inasmuch as the computation time is overwhelmed by the structural solution requirements, this requires only a small increase in total run time. The use of a three-point extrapolation method in Step 1 also improves accuracy, as discussed in [8].

Implicit integration algorithms have been used for both the fluid and structural equations. The former is treated with the 3-step Park method [16] while the latter is treated with the "JO" implementation of the trapezoidal rule [17].

Typical input to this processor includes

- Charge characteristics
  - Location
  - Pressure profile
- Time step information
  - Start and finish times
  - Time increment values
- Restart data
- Display directives
  - Displacements
  - Velocities
  - Pressures
  - Pseudo-velocity shock spectra

Detailed user information concerning TIMINT is given in Appendix C.

3.7 THE RESPONSE POSTPROCESSOR POSTPR

This utility is responsible for the listing and "printer-plot" graphic display of selected system responses and pseudo-velocity shock spectra. Some of the same capabilities are also embedded in the TIMINT processor for immediate selective scanning of the output. POSTPR, however, is used for more detailed examination of the results at a later time. As a complete display of all structural and fluid DOF histories for even a moderate size problem could run into thousands of pages of output care must be exercised in the selection of data to be displayed. Usage of this code is discussed in Appendix E.

SECTION IV

EXAMPLE PROBLEMS

This section presents results generated by the USA Code for two idealized underwater shock problems. The structure studied in the first problem is a hollow circular beam of finite length, while that involved in the second problem is an infinite, circular cylindrical shell. In both problems, the structure is excited by a transverse, plane step-wave of unit incident pressure and material properties are used that correspond to a steel shell immersed in water. The input data are normalized so that the density and speed of sound for the fluid both equal unity; hence, the density, Young's modulus, and Poisson's ratio for the structural material are taken as 7.85, 98.125 and 0.3, respectively. The radius and wall thickness of the beam and the cylinder are 1 and 0.01, respectively, while the length of the beam is 9. In order to assess the accuracy of the computational results, selected response histories are compared with those obtained by other methods.

4.1 CIRCULAR BEAM

The response variable of primary interest in this problem is the late-time asymptotic translational velocity V_∞ of the structure. An analytical expression for this quantity may be obtained from (2.5) by taking $\dot{\underline{x}} = \underline{\gamma}_{Ps}\, v(t)$, where $\underline{\gamma}_{Ps}$ is the vector of direction cosines relating the translational motions of the structural nodes and the direction of propagation of the plane incident wave. (The elements of $\underline{\gamma}_{Ps}$ that pertain to the rotational DOF are, of course, zero.) The introduction of this relation into the first of 2.5, followed by premultiplication of the resulting equation by $\underline{\gamma}_{Ps}^T$, then yields

$$m_s \dot{v} = -\underline{\gamma}_S^T \underset{\sim}{G} \underset{\sim}{A}_f (\underline{p}_I + \underline{p}_S) \tag{4.1}$$

where $m_s = \underline{\gamma}_{Ps}^T \underset{\sim}{M}_f \underline{\gamma}_{Ps}$; this follows from the fact that $\underset{\sim}{C}_s \underline{\gamma}_{Ps} = \underset{\sim}{K}_s \underline{\gamma}_{Ps} = \underline{0}$.

After the wave front of the plane step-wave has enveloped the structure, i.e., for $t > t_e$,

$$\underline{p}_I = \rho\, c\, U_I\, \underline{1}$$
$$\overset{*}{\underline{p}}_I = \rho\, c\, U_I (t\underline{1} - \underline{t}_A)$$
$$\underline{u}_I = U_I \underline{\gamma}_P$$

where U_I is the fluid particle velocity characterizing the step-wave, $\underline{1}$ is the unity vector, the asterisk denotes the temporal integral of the quantity beneath it, $\underline{t}_A$ is the vector of incident-wave arrival times for the fluid surface elements, and $\underline{\gamma}_P$ is the vector of direction cosines relating the normals of the fluid elements to propagation vector of

the plane incident wave. In addition, $|\dot{p}_S| << |p_S|$ for late-time motions (see Section 2.2), so that the second of (2.5) becomes

$$p_S = A_f^{-1} M_f (G^T \gamma_{Ps} \dot{v} - \dot{u}_I), \; t >> t_e \tag{4.3}$$

The introduction of this relation into (4.1) then yields

$$(m_s + m_a)\, \dot{v} = - \gamma_{Ps}^T G\, A_f p_I + \gamma_{Ps}^T G\, M_f \dot{u}_I, \; t >> t_e \tag{4.4}$$

where the added mass $m_a = \gamma_{Ps}^T G\, M_f G^T \gamma_{Ps}$. But, from (4.4), $G^T \gamma_{Ps} = \gamma_P$, so that m_a is also given as $m_a = \gamma_P^T M_f \gamma_P$.

With $G^T \gamma_{Ps} = \gamma_P$, the first of (4.2) yields $\gamma_{Ps}^T G\, A_f p_I = \rho\, c\, U_I \gamma_P^T A_f 1 = 0$, inasmuch as the wet surface of the structure is closed. Hence, the right side of (4.4) vanishes for $t > t_e$, which gives the expected result $\dot{v} = 0$. This prompts the use of integrated forms of (4.1) and (4.3) (with quiescent initial conditions), which yields, instead of (4.4),

$$(m_s + m_a)\, v = - \gamma_P^T A_f \overset{*}{p}_I + \gamma_P^T M_f u_I, \; t >> t_e \tag{4.5}$$

The introduction of the second and third of (4.2) into this equation then provides the desired expression for late-time asymptotic translational velocity

$$V_\infty = \frac{m_d + m_a}{m_s + m_a} U_I \tag{4.6}$$

where the structure's displaced mass m_d may be shown to be expressible as $m_d = \rho\, c\, \gamma_P^T A_f (t1 - t_A)$. Note that (4.6) is a general result, applicable to any wet-surface geometry.

Two different uniform mesh geometries were used to study the circular beam. Ten- and twenty-node models were constructed with beam elements provided by the structural analyzer SPAR [18]. The corresponding fluid models contained 9 and 19 elements of equal size, with 12 and 24 circumferential integration points (see Appendix A). For the beam considered, $m_s = 4.439$ and $m_d = 28.274$; with m_a determined as $m_a = \gamma^T M_f \gamma$, mesh geometry has a small effect on the value calculated for V_∞. It was found that $m_a = 23.824$ for the coarse mesh and $m_a = 24.332$ for the fine mesh, which yield $V_\infty = 1.843$ and $V_\infty = 1.828$, respectively.

In the response calculations, a constant time step of 0.1 (20 steps per envelopment period) was used for both models; the results are shown in Figures 4-1 and 4-2. Velocities at the ends of the beam are higher than those at the center because the three-dimensional flow field at the ends offers less resistance to the plane wave excitation than the two-dimensional flow field at the center. It is noted that the responses of both models are similar although those for the finer mesh appear to tend to the rigid body asymptotic velocity more precisely.

4.2 INFINITE CYLINDRICAL SHELL

For this problem, a 72-node, 36-element SPAR model with a uniform circumferential mesh was constructed. The length of the cylindrical shell equalled the circumferential dimension of the square plate elements used for the model; hence the shell was one element long. Kinematic constraints of zero axial displacement and no end rotation were enforced through the skyline utility, as described in Section 3.3. The fluid model consists of 36 equally-spaced elements around the circumference; the two-dimensional nature of the infinite shell geometry was simulated by exercising an option in the fluid preprocessor FLUMAS that adds fictitious elements in the axial direction.

Two dimensional n=0, 1, and 2 modal response results were generated by USA using appropriate Fourier components of the incident-wave force vectors in (2.9). For comparison, DAA analytical solutions were generated by the method described in [7] and [19]. The primary response variables of interest were radial displacement for n=0, radial and tangential velocity for n=1, and radial and tangential displacement for n=2. A time step of 0.025 was used up to t=1; for t between 1 and 2 this was increased 0.05, and for t greater than 2 a time step of 0.1 was used.

The USA and corresponding analytical results are shown harmonic by harmonic in Figures 4-3 through 4-7. In all cases the maximum errors made by USA fall into the range of 1 to 2%.



Figure 4-1. Transverse Velocity of Finite Beam, Coarse Mesh



Figure 4-2. Transverse Velocity of Finite Beam, Halved Mesh



Figure 4-3. n=0 Radial Displacement of Infinite Cylinder



Figure 4-4. n=1 Radial Velocity of Infinite Cylinder



Figure 4-5. n=1 Tangential Velocity of Infinite Cylinder



Figure 4-6. n=2 Radial Displacement of Infinite Cylinder



Figure 4-7. n=2 Tangential Displacement of Infinite Cylinder

REFERENCES

[1] W. Pilkey, K. Saczalski and H. Schaeffer, eds., Structural Mechanics Computer Programs, The University Press of Virginia, Charlottesville, Va., 1974

[2] N. Perrone and W. Pilkey, eds. Structural Mechanics Software Series, Vol. 1, The University Press of Virginia, Charlottesville, Va., 1977

[3] T. L. Geers, "Residual Potential and Approximate Methods for Three-Dimensional Fluid-Structure Interaction Problems," J. Acoust. Soc. Am., Vol. 49, No. 5 (Part 2), May 1971, pp. 1505-1510

[4] T. L. Geers, "Doubly Asymptot c Approximations for Transient Motions of Submerged Structures," to appear in J. Acoust. Soc. Am.

[5] T. L. Geers, "Transient Response Analysis of Submerged Structures," pp. 59-85 of Finite Element Analysis of Transient Nonlinear Structural Behavior, AMD-Vol. 14, ASME, New York, 1975

[6] H. Huang, G. C. Everstine, and Y. F. Wang, "Retarded Potential Techniques for the Analysis of Subjerged Structures Impinged by Weak Shock Waves," pp. 83-93 of Computational Methods for Fluid-Structure Interaction Problems, AMD-Vol. 26, ASME, New York, 1977

[7] T. L. Geers, "Shock Response Analysis of Submerged Structures," Shock and Vibration Bulletin, Vol. 44, Supp. 3, August 1974, pp. 17-32

[8] K. C. Park, C. A. Felippa, and J. A. DeRuntz, "Stabilization of Staggered Solution Procedures for Fluid-Structure Interaction Analysis," pp. 95-124 of Computational Methods for Fluid-Structure Interaction Problems, AMD-Vol. 26, ASME, N.Y., 1977

[9] J. A. DeRuntz and T. L. Geers, "Added Mass Computation by the Boundary Integral Method," Int. J. Num. Meth. Eng., Vol. 12, 1978, pp. 531-550

[10] C. A. Felippa, "The Input-Output Manager of the NOSTRA Data Management System, Univac 1100 - Series Version Reference Manual," LMSC-D556430, Lockheed Palo Alto Research Laboratory, Palo Alto, California, January 1977

[11] C. A. Felippa, "The Resource Pool Manager of the NOSTRA Data Management System," LMSC-D556245, Lockheed Palo Alto Research Laboratory, Palo Alto, California, September 1977

[12] P. S. Jensen, "EASY - An Engineering Analysis System of Utility Programs," LMSC-D556249, Lockheed Palo Alto Research Laboratory, Palo Alto, California, Sept. 1977

[13] C. A. Felippa, "Skymatrix Processing Utility Library (SKYPUL) Users Manual," LMSC-D623146, Lockheed Palo Alto Research Laboratory, Palo Alto, Calif., January 1978

[14] J. A. DeRuntz, "SPARKY - A Utility for the Conversion of SPAR Matrices from Block to Skyline Format," LMSC report in preparation, Lockheed Palo Alto Research Laboratory, Palo Alto, California

[15] G. C. Everstine and D. R. Wallace, "A Guide to the Interfacing of NASTRAN with a Lockheed Integrator," NSRDC-TM-184-77-07, October 1977

[16] K. C. Park, "An Improved Stiffly Stable Method for Direct Integration of Nonlinear Structural Dynamics," J. Appl. Mech., Vol. 42, 1975, pp. 464-470

[17] C. A. Felippa and K. C. Park, "Computational Aspects of Time Integration Procedures in Structural Dynamics," LMSC-D556247, Lockheed Palo Alto Research Laboratory, Palo Alto, California, January 1977

[18] W. D.Whetstone, SPAR Reference Manual, LMSC-D403168, Lockheed Palo Alto Research Laboratory, Palo Alto, California, June 1974

[19] T. L. Geers, "Scattering of a Transient Acoustic Wave by an Elastic Cylindrical Shell," J. Acoust. Soc. Am., Vol. 51, No. 5 (Part 2), May 1972, pp. 1640-1651

[20] C. R. Rao and S. K. Mitra, Generalized Inverse of Matrices and Its Applications, John Wiley and Sons, New York, 1971

[21] R. W. Hamming, Numerical Methods for Scientists and Engineers, McGraw-Hill Inc., New York, Second Ed., 1973

APPENDIX A

FLUID MASS COMPUTATION FOR A SUBMERGED STRUCTURE WITH BOTH ROTATIONALLY SYMMETRIC AND GENERAL-GEOMETRY COMPONENTS

Computer calculation of the fluid mass matrix for a submerged structure which is composed of both rotationally symmetric surfaces and general nonsymmetric surfaces may be accomplished using the fully three-dimensional boundary integral approach of Ref. [9]. In such a case, however, the use of general-surface elements for each rotationally symmetric surface is not efficient when it is known a priori that only certain circumferential harmonics of the fluid motion are of importance. This may occur, for example, when part of the structure consists of a beam of circular cross section for which only the $n = 1$ harmonic is required. Then, the order of the fluid mass matrix may be reduced from that for the fully three-dimensional structure by a redefinition of the fluid degrees-of-freedom.

For a general-surface element with a single centroidal control point, the associated degree-of-freedom has a direct physical interpretation, namely, the fluid velocity normal to the plane of the element. For rotationally symmetric surfaces, the elemental degrees-of-freedom become Fourier coefficients for the circumferential harmonics of the surface velocity at prescribed axial locations. This gives rise to the concept of the "surface of revolution" (SOR) element as opposed to the "general-surface" (GEN) element. In this appendix, we describe a technique for the inclusion of both SOR and GEN elements in the same fluid mass matrix.

A direct way to couple both SOR and GEN elements in a single matrix is first to construct the fluid mass matrix for the fully three-dimensional structure. Then, a transformation can be applied which is associated with a hybrid surface velocity vector representing both physical and generalized coordinates. To implement this two-stage procedure, we cover the entire surface of the structure with GEN elements and, in particular, require equal spacing of such elements around the circumference of the surfaces-of-revolution. The number of such elements in this latter category is taken to be the same at all axial stations and is denoted by N. A set of N circumferential GEN elements at any axial station is then regarded as a single SOR element having as many degrees-of-freedom as the number of Fourier coefficients which are chosen to describe the global fluid motion. The set of control points associated with the circumferential GEN elements will be referred to as integration points for their associated SOR elements.

We now assume that the fluid velocity vector for the full three-dimensional surface discretization $\underline{v}$ can be approximated in the mean by the hybrid fluid velocity vector $\underline{v}^*$ by the transformation

$$\underline{v} \approx \underset{\sim}{D}\, \underline{v}^* \tag{A.1}$$

in which

$$\underline{v} = \begin{bmatrix} \underline{v}^G \\ \underline{v}^S \end{bmatrix} , \quad \underline{v}^* = \begin{bmatrix} \underline{v}^G \\ \underline{v}^F \end{bmatrix} \tag{A.2}$$

$$D = \begin{bmatrix} \underset{\sim}{I} & \underset{\sim}{O} \\ \underset{\sim}{O} & \underset{\sim}{F} \end{bmatrix} \tag{A.3}$$

where the superscript G refers to the GEN elements located on the general geometry portions of the structure and the subscript S refers to the sets of GEN elements which make up the individual SOR elements; the vector $\underline{v}^F$ contains the Fourier velocity coefficients for these SOR elements. For convenience, we have partitioned the above arrays so that the entries pertaining to GEN elements appear first and will continue this convention in the following. The matrix $\underset{\sim}{F}$ is rectangular and has the form

$$\underset{\sim}{F} = \begin{bmatrix} \underline{C}_0^1 & \underline{C}_1^1 & \underline{S}_1^1 & \cdots & \underline{C}_M^1 & \underline{S}_M^1 & & & & & \underline{O} \\ & & & & & & \underline{C}_0^2 & \underline{C}_1^2 & \underline{S}_1^2 & \cdots & \underline{C}_M^2 \quad \underline{S}_M^2 \\ & \ddots & \underline{O} & \ddots & \underline{O} & \ddots & & \underline{O} & & \ddots & \underline{O} \quad \ddots \\ \underline{O} & & & & & & \underline{C}_0^L & \underline{C}_1^L & \underline{S}_1^L & \cdots & \underline{C}_M^L \quad \underline{S}_M^L \end{bmatrix} \tag{A.4}$$

Here, M is the maximum number of circumferential harmonics and L is the total number of SOR elements while the vectors $\underline{C}_m^\ell$ and $\underline{S}_m^\ell$ for the ℓ^{th} SOR element and the m^{th} circumferential harmonic are given by

$$\underline{C}_m^\ell = \begin{bmatrix} 1 \\ \cos \frac{2\pi m}{N} \\ \vdots \\ \cos \frac{2\pi m i}{N} \\ \vdots \\ \cos \frac{2\pi m (N-1)}{N} \end{bmatrix} , \quad \underline{S}_m^\ell = \begin{bmatrix} 0 \\ \sin \frac{2\pi m}{N} \\ \\ \sin \frac{2\pi m i}{N} \\ \\ \sin \frac{2\pi m (N-1)}{N} \end{bmatrix} \tag{A.5}$$

where i is the circumferential integration point index. If the transformation (A.1) is now applied to the fluid velocity vector, then invariance of the total kinetic energy of the fluid provides the direct means for reduction of the mass matrix as

$$\underset{\sim}{M}^* = \underset{\sim}{D}^T \underset{\sim}{M} \underset{\sim}{D} \tag{A.6}$$

where the transcipt T denotes matrix transposition and $\underset{\sim}{M}$ is the previously computed fluid mass matrix for the fully three-dimensional structure.

Application of the preceding procedure can involve a large expenditure of computational effort, particularly if the number of SOR elements and circumferential integration points is large. In such a case, matrix partitioning and out-of-core operations may be required. Even when large matrices can be handled by such core management techniques, the computations include the factorization of a large, full, unsymmetric matrix and subsequent solution operations just to form the mass matrix before reduction. These considerations have prompted the development of an alternate but approximate approach that uses intermediately formed matrices of the same order as the final reduced mass matrix with a corresponding saving of computation time.

Calculation of the fluid mass matrix based upon the simple source formulation involves three state variables, the source strength $\underline{\sigma}$, the velocity potential $\underline{\phi}$ and the normal derivative of the velocity potential $\underline{\phi}_n$, which are related by the matrix equations [9]

$$\begin{aligned} \underline{\phi} &= \underset{\sim}{B}\,\underline{\sigma} \\ \underline{\phi}_n &= -\underset{\sim}{C}\,\underline{\sigma} \end{aligned} \tag{A.7}$$

Here, $\underset{\sim}{B}$ and $\underset{\sim}{C}$ are full, unsymmetric, square matrices while $\underline{\phi}$, $\underline{\phi}_n$, and $\underline{\sigma}$ are column vectors. We take the order of this system to be the number of discrete fluid degrees-of-freedom for the full three-dimensional surface discretization. The actual coefficients of $\underset{\sim}{B}$ and $\underset{\sim}{C}$ and the precise manner in which they are combined to form the fluid mass matrix are unimportant to the development here and the interested reader is referred to [9] for this exposition. However, we will use certain aspects of the connectivity of $\underset{\sim}{B}$ and $\underset{\sim}{C}$ later.

A fundamental assumption made in [9] is that the source strength $\underline{\sigma}$ is constant over each element. Here, we make the same assumption for all elements, and further stipulate that the variation of $\underline{\sigma}$ and $\underline{\phi}$ as well as $\underline{\phi}_n$ (the negative of the fluid velocity vector) around the circumference of each SOR element can be expressed by the same finite Fourier series embedded in the transformation in (A.1). If there are only SOR elements in the structure, it can be shown that this relationship is exact, harmonic by harmonic, however, the presence of general-geometry structure components in the flow field perturbs this exactness. We then have

$$\underline{\sigma} \approx D\,\underline{\sigma}^*$$
$$\underline{\phi} \approx D\,\underline{\phi}^* \qquad (A.8)$$
$$\underline{\phi}_n \approx D\,\underline{\phi}_n^*$$

so that Eq. (A.8) can be substituted into Eq. (A.7) to obtain

$$\begin{aligned} \underset{\sim}{D}\,\underline{\phi}^* &\approx \underset{\sim}{B}\,\underset{\sim}{D}\,\underline{\sigma}^* \\ \underset{\sim}{D}\,\underline{\phi}_n^* &\approx -\underset{\sim}{C}\,\underset{\sim}{D}\,\underline{\sigma}^* \end{aligned} \qquad (A.9)$$

We are now able to construct a set of equations in the reduced system similar to Eq. (A.7) by multiplying Eq. (A.9) by the left inverse of D, which is defined as [19].

$$\underset{\sim}{D}_L^{-1} = (\underset{\sim}{D}^T\,\underset{\sim}{D})^{-1}\,\underset{\sim}{D}^T \qquad (A.10)$$

It then follows that the counterparts of $\underset{\sim}{B}$ and $\underset{\sim}{C}$ in the reduced system are

$$\begin{aligned} \underset{\sim}{B}^* &\approx \underset{\sim}{D}_L^{-1}\,\underset{\sim}{B}\,\underset{\sim}{D} \\ \underset{\sim}{C}^* &\approx \underset{\sim}{D}_L^{-1}\,\underset{\sim}{C}\,\underset{\sim}{D} \end{aligned} \qquad (A.11)$$

$\underset{\sim}{D}_L^{-1}$ is easily obtained from the orthogonality and normalization conditions for the finite Fourier series, i.e., [20]

$$\sum_{i=1}^{N} \sin\frac{2\pi m(i-1)}{N}\cos\frac{2\pi n(i-1)}{N} = O$$

$$\sum_{i=1}^{N} \sin\frac{2\pi m(i-1)}{N}\sin\frac{2\pi n(i-1)}{N} = \begin{cases} O & m \neq n \\ N/2 & m = n \end{cases} \qquad (A.12)$$

$$\sum_{i=1}^{N} \cos\frac{2\pi m(i-1)}{N}\cos\frac{2\pi n(i-1)}{N} = \begin{cases} O & m \neq n \\ N/2 & m = n \neq o \\ N & m = n = o \end{cases}$$

Using Eqs. (A.3), (A.4), (A.5), and (A.12), we find that

$$\left(\underset{\sim}{D}^T\,\underset{\sim}{D}\right)^{-1} = \begin{bmatrix} \underset{\sim}{I} & \underset{\sim}{O} \\ \underset{\sim}{O} & \underset{\sim}{G} \end{bmatrix} \qquad (A.13)$$

where $\underset{\sim}{G}$ is a diagonal matrix given by

$$\underset{\sim}{G} = \frac{1}{N} \begin{bmatrix} 1 & & & & & \\ & 2 & & & O & \\ & & 2 & & & \\ & & & 2 & & \\ & & & & \ddots & \\ & O & & & & \\ & & & & & 2 \end{bmatrix} \qquad (A.14)$$

We now show that the formation of $\underset{\sim}{B}$ and $\underset{\sim}{C}$ and the transformation indicated in Eq. (A.1) can be carried out simultaneously to give the matrices $\underset{\sim}{B}^*$ and $\underset{\sim}{C}^*$ directly. Consistent with the partitioning of Eqs. (A.2) and (A.3), $\underset{\sim}{B}$ may be expressed as

$$\underset{\sim}{B} = \begin{bmatrix} \underset{\sim}{B}^{GG} & \underset{\sim}{B}^{GS} \\ \underset{\sim}{B}^{SG} & \underset{\sim}{B}^{SS} \end{bmatrix} \qquad (A.15)$$

where the first superscript refers to the element type (GEN or SOR) for which the potential is being evaluated and the second superscript indicates the element type whose source strength contributes to that potential [see the first of Eq. (A.7)]. Now, using Eqs. (A.3), (A.10), (A.11), (A.13), and (A.15), we obtain

$$\underset{\sim}{B}^* = \begin{bmatrix} \underset{\sim}{B}^{GG} & \underset{\sim}{B}^{GS}\,\underset{\sim}{F} \\ \underset{\sim}{G}\,\underset{\sim}{F}^T\,\underset{\sim}{B}^{SG} & \underset{\sim}{G}\,\underset{\sim}{F}^T\,\underset{\sim}{B}^{SS}\,\underset{\sim}{F} \end{bmatrix} \qquad (A.16)$$

A similar result can be written for $\underset{\sim}{C}^*$; however, as the development to follow is the same for both $\underset{\sim}{B}^*$ and $\underset{\sim}{C}^*$, only that for $\underset{\sim}{B}^*$ is presented.

Equation (A.16) shows that the relationship between GEN elements is unaltered by the transformation, but that the matrices coupling GEN and SOR elements require matrix multiplication. For the matrix $\underset{\sim}{B}^{GS}\,\underset{\sim}{F}$, we have

$$b^*_{ij} = \sum_{j'=1}^{N} b^{j'}_{ij} \begin{smallmatrix}\cos\\ \sin\end{smallmatrix} \left[\frac{2\pi m\,(j'-1)}{N}\right] \qquad (A.17)$$

where the subscript i identifies a particular GEN element, the subscript j identifies a particular SOR element, and the index j' identifies one of the N integration points around the circumference of the j^{th} SOR element. Hence, the $b^{j'}_{ij}$ can be computed sequentially over the index j' and the summation performed conjunctively. The same technique, of course, can be applied to the matrix $\underset{\sim}{G}\,\underset{\sim}{F}^T\,\underset{\sim}{B}^{SG}$ as

$$b_{ji}^{*} = \frac{\epsilon_m}{N} \sum_{j'=1}^{N} b_{ji}^{j'} \begin{matrix} \cos \\ \sin \end{matrix} \left[\frac{2\pi m (j' - 1)}{N} \right] \tag{A.18}$$

where

$$\epsilon_m = \begin{cases} 1 & m = 0 \\ 2 & m > 0 \end{cases} \tag{A.19}$$

Construction of the matrix relating SOR elements is complicated by the fact that double summations are involved. From Eq. (A.16), we have

$$b_{ij}^{*} = \frac{\epsilon_m}{N} \sum_{j'=1}^{N} \sum_{j'=1}^{N} b_{ij}^{i'j'} \begin{matrix} \cos \\ \sin \end{matrix} \left[\frac{2\pi m (i' - 1)}{N} \right] \begin{matrix} \cos \\ \sin \end{matrix} \left[\frac{2\pi n (j' - 1)}{N} \right] \tag{A.20}$$

where the subscripts i and j identify SOR elements and the indices i' and j' identify integration points on the i^{th} and j^{th} SOR elements, respectively. It will now be shown that Eq. (A.20) can be simplified to an equation involving a single summation by examination of the connectivity of B^{SS}.

As discussed in [9], the matrix elements of $\underset{\sim}{B}$ and $\underset{\sim}{C}$ are, except for a multiplicative constant, functions only of the geometry of the finite element mesh. Now, it is clear from Figure A-1 that the relative geometry of points A/D is identical to that of points B/E, that the relative geometry of points A/E is identical to that of B/F, etc. Hence, the $N \times N$ submatrix that relates the source strengths at the integration points on segment j to the values of the potential at the integration points on segment i must have identical terms along every diagonal. Moreoever, the variation in any row (or column) is that of an even function because of the rotationally symmetric geometry, i.e., the relationship of C/D is identical to that of C/F, etc. On the basis of these facts, Eq. (A.20) may be considerably simplified.

Consider, for example, the expansion

$$S = \frac{\epsilon_m}{N} \sum_{k=1}^{N} \sum_{\ell=1}^{N} U_{k\ell} \cos \frac{2\pi m (k - 1)}{N} \cos \frac{2\pi n (\ell - 1)}{N} \tag{A.21}$$

with the condition that

$$U_{k+1,\ell+1} = U_{k\ell} \tag{A.22}$$

and the understanding that if a subscript on the left becomes greater than N it is replaced by k + 1 - N, etc. Now, the double summation in Eq. (A.21) is ordered by rows and columns; however, we can rearrange it into N terms, each of which represents summation along either the main

diagonal or an extended diagonal[†]. Then, taking advantage of Eq. (A.22), we obtain

$$
\begin{aligned}
N S/\epsilon_m = {} & U_{11} \sum_{k=1}^{N} \cos \frac{2\pi m (k-1)}{N} \cos \frac{2\pi n (k-1)}{N} + \\
& U_{12} \sum_{k=1}^{N} \cos \frac{2\pi m k}{N} \cos \frac{2\pi n (k-1)}{N} + \\
& U_{13} \sum_{k=1}^{N} \cos \frac{2\pi m (k+1)}{N} \cos \frac{2\pi n (k-1)}{N} + \dots \\
& \dots + U_{1N} \sum_{k=1}^{N} \cos \frac{2\pi m (k+N-2)}{N} \cos \frac{2\pi n (k-1)}{N}
\end{aligned}
\tag{A.23}
$$

Next, we reorganize the general term that appears in Eq. (A.23) as

$$
\begin{aligned}
U_{1,\ell+1} \sum_{k=1}^{N} \cos \frac{2\pi m (k-1+\ell)}{N} \cos \frac{2\pi n (k-1)}{N} = {} & \\
U_{1,\ell+1} \cos \frac{2\pi m \ell}{N} \sum_{k=1}^{N} \cos \frac{2\pi m (k-1)}{N} \cos \frac{2\pi n (k-1)}{N} & - \\
U_{1,\ell+1} \sin \frac{2\pi m \ell}{N} \sum_{k=1}^{N} \sin \frac{2\pi m (k-1)}{N} \cos \frac{2\pi n (k-1)}{N} &
\end{aligned}
\tag{A.24}
$$

If $m \neq n$, it follows from Eq. (A.12) that the general term is zero and, hence, the sum S is equal to zero. If $m = n$, then Eqs. (A.12) and (A.24) reduce Eq. (A.23) to

$$S = \sum_{k=1}^{N} U_{1k} \cos \frac{2\pi m (k-1)}{N} \tag{A.25}$$

In a similar manner, the other possible combinations of trigonometric functions in Eq. (A.20) may be simplified; such simplification yields, for $m \neq n$,

$$b^*_{ij} = O \tag{A.26}$$

[†] The latter consists of a diagonal in the upper triangle plus its complement in the lower triangle.

while for $m = n$ in the cos/cos and sin/sin combinations in Eq. (A.20),

$$b^*_{ij} = \sum_{j'=1}^{N} b^{1j'}_{ij} \cos \frac{2\pi m(j'-1)}{N} \tag{A.27}$$

and, for $m = n$ in the sin/cos and cos/sin combinations in Eq. (A.20),

$$b^*_{ij} = \sum_{j'=1}^{N} b^{1j'}_{ij} \sin \frac{2\pi m(j'-1)}{N} \tag{A.28}$$

Finally, as it has been demonstrated that the $b^{i'j'}_{ij}$ must be even functions around the circumference of any SOR segment, the contribution of Eq. (A.28) to the final results must vanish, leaving only Eq. (A.27). This, of course, also means that the computation required to form Eq. (A.27) can essentially be halved.

The results of the preceding development may be summarized as follows:

- The coupling that occurs between SOR segments occurs, harmonic by harmonic, without coupling of different harmonics
- The coupling is the same for both the sine and cosine functions, and is given by Eq. (A.27)
- The sine and cosine functions of a particular harmonic do not couple

Thus far, we have substantially reduce the computations required to form the $\underset{\sim}{B}^*$ and $\underset{\sim}{C}^*$ matrices. A few steps remain, however, in order to reach the final objective, viz., efficient formation of the fluid mass matrix for the coupled structure.

As discussed in [9] , $\underset{\sim}{B}^*$ and $\underset{\sim}{C}^*$ are used to form the fluid kinetic energy expression, which is derivable from an appropriate surface integral. In the discretized, fully three-dimensional system, this requires a diagnonal matrix $\underset{\sim}{dA}$ whose elements are simply the incremental areas of each surface element. The kinetic energy T is then

$$T = -\frac{1}{2}\rho \int_S \underline{\phi}_n^T \, \underset{\sim}{dA} \, \underline{\phi} \tag{A.29}$$

where ρ is the fluid density and the integration extends over the fully three-dimensional surface S. We may write this expression in the reduced system by simply substituting from Eq. (A.8), with the result that

$$\underset{\sim}{dA}^* = \underset{\sim}{D}^T \, \underset{\sim}{dA} \, \underset{\sim}{D} \tag{A.30}$$

Carrying out the matrix multiplications, we obtain

$$\underset{\sim}{dA}^* = \begin{bmatrix} \underset{\sim}{dA}^G & \underset{\sim}{O} \\ \underset{\sim}{O} & \underset{\sim}{F}^T \, \underset{\sim}{dA}^S \, \underset{\sim}{F} \end{bmatrix} \tag{A.31}$$

For each submatrix appropriate to a particular SOR element and harmonic that appears in $\underset{\sim}{F}^T \, d\underset{\sim}{A}^S \, \underset{\sim}{F}$, the expansion gives

$$d\,a^*_{ii} = \frac{N}{\epsilon_m} \, d\,a^{11}_{ii} \tag{A.32}$$

where $d\,a^{11}_{ii}$ is the incremental area for a single integration element around the circumference of the segment in the full three dimensional discretization.

The preceding results can now be applied to any of the computational schemes described in [9] . As is noted there, however, one particular scheme, labeled "I2," has been found to be surprisingly accurate in relation to its computational demands and hence has been chosen here as the "baseline" method. In this case, the incremental areas appearing in Eqs. (A.29) through (A.32) may be replaced by the total area of the element, as the "I2" scheme essentially assumes that $\underline{\phi}$ and $\underline{\phi}_n$, as well as $\underline{\sigma}$, are constant over each surface element.

A modest study has been performed on a simple model in which the reduced mass matrix has been obtained directly from Eq. (A.6) and by the approximate method outlined above. This model consists of two cylindrical shell segments with a radial "fin" joined to one segment on the lateral surface as shown in Figure A-2; only the n=1 beam modes were kept in the reduced matrix. Comparisons have been made of the eigenvalues of the "fluid boundary mode" problem defined by

$$\underset{\sim}{M}^* \, \underline{x} = \lambda \, \underset{\sim}{A}^* \, x \tag{A.33}$$

(In [9] the λ are identified with modal kinetic energy components.)

Typical results from the study are shown in the following table:

λ-Direct	λ-Approximate	Mode
0.59671	0.56960	S
0.47838	0.47826	A
0.29624	0.25955	S
0.27412	0.27108	A
0.21624	0.21622	A
0.19634	0.17554	S

where S denotes a symmetric or breathing mode relative to the two sides of the "fin" and A denotes an antisymmetric or rigid-body "fin" mode. We see that the eigenvalues for the rigid modes are in good agreement; however, the eigenvalues for the symmetric modes exhibit discrepancies of 5 to 14 percent. These discrepancies may be due to the retention of only the n = 1 modes in the reduced matrix; only further evaluation under more general conditions can clarify this point. At this time, however, it appears that the technique introduced here is a viable one, particularly for very large problems whose size precludes application of the direct method.



Figure A-1. Schematic of SOR and GEN Element Model



Figure A-2. Geometry of Study Problem for SOR and GEN Element Coupling

APPENDIX B

USER INFORMATION FOR THE FLUID PREPROCESSOR FLUMAS

The following includes modifications which were made under separate contract to the Naval Surface Weapons Center, Contract Number N60921-77-C-0112.

This appendix includes a copy of the users manual, and a sample input deck and subsequent output for the infinite cylindrical shell problem presented in Section 4.

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                    F  L  U  M  A  S

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

   THIS FUNCTIONAL COMPONENT OF THE UNDERWATER SHOCK ANALYSIS CODE
   CONSTRUCTS THE FLUID MASS MATRIX FOR A STRUCTURE SUBMERGED IN AN
   INFINITE, INVISCID, INCOMPRESSIBLE FLUID BY THE BOUNDARY ELEMENT
   TECHNIQUE. IT ALSO GENERATES FLUID MESH DATA AND A SET OF
   TRANSFORMATION COEFFICIENTS THAT RELATE THE STRUCTURAL AND FLUID
   DEGREES OF FREEDOM ON THE WET SURFACE. THE CODE HAS THE CAPABILITY
   TO TREAT STRUCTURES CONTAINING BOTH SURFACE-OF-REVOLUTION (SOR)
   AND GENERAL-GEOMETRY (GEN) COMPONENTS. THE CODE CAN ALSO CONSTRUCT
   THE FLUID MASS MATRIX FOR A QUARTER-MODEL WITH ARBITRARILY
   ASSIGNED SYMMETRY OR ANTISYMMETRY CONDITIONS, AND CAN SIMULATE THE
   TWO-DIMENSIONAL PLANE STRAIN BEHAVIOR OF LONG CYLINDERS. A USEFUL
   DIAGNOSTIC TOOL CONTAINED WITHIN THE CODE IS THE ABILITY TO SOLVE
   THE FLUID BOUNDARY MODE EIGENVALUE PROBLEM

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

   THIS PROGRAM WAS DEVELOPED AND CODED BY JOHN A. DERUNTZ, JR.
   OF LOCKHEED MISSILES AND SPACE CO. RESEARCH LABS IN PALO ALTO
   CALIFORNIA. PLEASE CONSULT WITH AUTHOR BEFORE MAKING CHANGES
   AND ALSO REPORT ANY MALFUNCTIONS OR PROBLEMS. WRITE IN CARE OF
   LOCKHEED PALO ALTO RESEARCH LABORATORY, BLDG 205, DEPT 52-33,
   3251 HANOVER ST., PALO ALTO, CALIF., 94304 OR CALL 415-493-4411
   EXTS. 45069 OR 45133.                                 FEBRUARY, 1978

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                 M A X I M U M     V A L U E S

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

   MAXIMUM NUMBER OF STRUCTURAL GRID POINTS          . . . . . . . .   5 0 0

   MAXIMUM NUMBER OF GENERAL SURFACE ELEMENTS        . . . . . . . .   1 8 0

   MAXIMUM NUMBER OF SURFACE OF REVOLUTION SEGMENTS    . . . . . .       4 0

   MAXIMUM NUMBER OF SURFACE OF REVOLUTION FREEDOMS    . . . . . .       8 0

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

W A R N I N G     F R O M     T H E     P R O G R A M M E R     G E N E R A L

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

   THIS CODE CONTAINS THE SPECIAL INGREDIENT DMGASP NOT FOUND IN
   OTHER BRANDS. DMGASP IS A DATA MANAGEMENT UTILITY MODULE THAT
   WILL ACTIVATE AND DEACTIVATE ALL AUXILIARY STORAGE DATA FILES
   REFERENCED BY THE CODE. HENCE THE NAMES OF SUCH FILES SHOULD NOT
   APPEAR ON ANY CONTROL CARDS IN THE RUN STREAM WHICH MIGHT NORMALLY
   ACTIVATE AND DEACTIVATE THE FILES. THE USER IS ALSO CAUTIONED THAT
   PREVIOUSLY CREATED FILES MUST ALREADY BE RESIDENT IN THE SYSTEM
```

```
         BEFORE THE RUN IS INITIATED. IF A FILE HAS BEEN ROLLED-OUT TO TAPE
         DMGASP WILL ATTEMPT TO HAVE THE FILE ROLLED-IN EVERY 15 SECONDS
         FOR UP TO 15 MINUTES ON THE UNIVAC 1100-EXEC 8 OPERATING SYSTEM.
         IF AN EXISTING DATA FILE HAS NOT BEEN REFERENCED FOR SOME TIME IT
         IS THEREFORE GOOD POLICY TO SIMPLY ACTIVATE AND DEACTIVATE THE
         FILE BEFORE EXECUTION OF THIS CODE. IF THE USER ATTEMPTS TO CREATE
         A NEW DATA FILE WITH A NAME WHICH IS ALREADY ASSIGNED TO AN
         EXISTING FILE. THE UNIVAC VERSION OF DMGASP WILL MODIFY THE NAME
         OF THE FILE GENERATED BY THIS RUN TO AVOID ANY CONFLICT. FILE NAME
         DUPLICATION WILL CAUSE NO PROBLEM ON THE CDC SCOPE OPERATING
         SYSTEM AS SCOPE WILL SIMPLY CATALOG A NEW CYCLE OF THE SAME FILE.
         ON THE OTHER HAND THE CDC NOS SYSTEM IS SIMILAR TO UNIVAC IN THIS
         REGARD AND THE RUN WILL ABORT SINCE THE NAME-CHANGING FEATURE OF
         DMGASP HAS NOT BEEN IMPLEMENTED FOR NOS. QUALIFIER*FILENAME IS THE
         REQUIRED INPUT DATA FORMAT FOR ALL UNIVAC PERMANENT FILE NAMES.
         FOR CDC OPERATION QUALIFIER IS REPLACED BY THE FILE ID, WHICH IS
         THE USER ID BY DEFAULT

 * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                           P R O G R A M     S I Z E

 * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

         ALL ARRAYS REFERRENCED IN THIS CODE THAT ARE PROBLEM DEPENDENT
         RESIDE IN BLANK COMMON. THE SIZE OF BLANK COMMON IS DETERMINED BY
         A PARAMETER STATEMENT IN THE MAIN PROGRAM FOR THE UNIVAC 1100-OS
         VERSION, HENCE A RECOMPILATION IS NECESSARY TO INCREASE OR
         DECREASE CORE ALLOCATION. IN THE CDC 6600 VERSION RECOMPILATION IS
         UNNECESSARY AS THE LENGTH OF BLANK COMMON IS SET BY A FIELD LENGTH
         REQUEST IN THE CONTROL CARD DECK

         AT THIS TIME THE CODE HAS NOT BEEN SYSTEMATICALLY OVERLAYED TO
         CONSERVE SPACE IN THE INSTRUCTION BANK. THIS HAS BEEN DONE TO SOME
         EXTENT BUT HAS NOT BEEN INCLUDED HERE AS IT IS INCOMPLETE. PLEASE
         CONTACT THE AUTHOR FOR INFORMATION

 * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

         D E F I N I T I O N     O F     I N P U T     P A R A M E T E R S

 * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

         INPUT VARIABLE NAMES GIVEN BELOW ARE GENERALLY THOSE WHICH ARE
         ALSO USED IN THE CODING AND THE VARIABLE TYPES CORRESPOND TO
         STANDARD FORTRAN USAGE:

                         A   -   ALPHANUMERIC
                         E   -   FLOATING POINT
                         F   -   FIXED POINT
                         I   -   INTEGER
                         L   -   LOGICAL

         --------    ----              -----------
         VARIABLE    TYPE              DESCRIPTION
         --------    ----              -----------

         NSTR         I        NUMBER OF INPUT NODE POINTS WHICH ARE USED
```

		TO DEFINE THE STRUCTURAL MESH. AT THE VERY LEAST THIS NUMBER MUST INCLUDE ALL THE WET NODES, IE., THOSE LYING ON THE FLUID-STRUCTURE CONTACT BOUNDARY. IF THE ULTIMATE PURPOSE OF THIS RUN IS TO CONDUCT AN UNDERWATER SHOCK ANALYSIS WITH THE USA CODE FOR THE STRUCTURE IN QUESTION THEN IT IS ADVISABLE TO INCLUDE IN THE INPUT TO THIS PROCESSOR ALL THE DRY STRUCTURAL NODE POINTS AS WELL IN ORDER TO FACILITATE POST PROCESSING OF THE TRANSIENT RESPONSE ANALYSIS FOR THE DRY STRUCTURE. THIS NUMBER MAY ALSO INCLUDE ADDITIONAL NODE POINTS THAT ARE NOT PART OF THE STRUCTURE MODEL BUT WHICH ARE NECESSARY TO DEFINE THE FLUID MESH
NGEN	I	NUMBER OF GENERAL FLUID DEGREES OF FREEDOM WHOSE ASSOCIATED ELEMENTS CANNOT BE FORMED BY AN AUTOMATIC MESH GENERATION PROCEDURE
NSOR	I	NUMBER OF SURFACE OF REVOLUTION FLUID DEGREES OF FREEDOM
NSEG	I	NUMBER OF SURFACE OF REVOLUTION SEGMENTS IN FLUID MODEL
NCYL	I	NUMBER OF GENERAL FLUID CONTROL POINTS WHICH LIE ON A RIGHT CIRCULAR CYLINDRICAL SURFACE WHOSE ASSOCIATED RECTANGULAR ELEMENTS COVER THE ENTIRE LATERAL SURFACE. SUCH ELEMENTS CAN BE FORMED BY AN AUTOMATIC MESH GENERATION SCHEME WHICH IS EMBEDDED IN THE CODE AND THE AXIS OF THIS SURFACE WILL BE ORIENTED IN THE Z DIRECTION
DENS	E,F	FLUID MASS DENSITY
CEE	E,F	FLUID SPEED OF SOUND
PRTGMT	L	TRUE IF FLUID MESH GEOMETRY DATA IS TO BE LISTED. OTHERWISE FALSE
PRTTRN	L	TRUE IF FLUID-STRUCTURE TRANSFORMATION DATA IS TO BE LISTED. OTHERWISE FALSE
PRTAMF	L	TRUE IF FLUID MASS MATRIX IS TO BE LISTED. OTHERWISE FALSE IN WHICH CASE ONLY THE DIAGONAL TERMS ARE PRINTED
CALCAM	L	TRUE IF THE FLUID MASS MATRIX IS TO BE COMPUTED. OTHERWISE FALSE AND THE RUN WILL TERMINATE AFTER THE FLUID MESH GEOMETRY DATA HAS BEEN PROCESSED. USE A VALUE OF TRUE ONLY AFTER DEBUGGING OF THE GEOMETRY DATA HAS BEEN COMPLETED

EIGMAF	L	TRUE IF EIGENVALUES AND EIGENVECTORS OF THE FLUID BOUNDARY MODE PROBLEM ARE DESIRED, OTHERWISE FALSE
TWODIM	L	TRUE IF A TWO DIMENSIONAL PLANE STRAIN FLUID MASS MATRIX IS REQUIRED, OTHERWISE FALSE
GRDCRD	L	TRUE IF GRID CARDS ARE TO APPEAR IN THE INPUT DATA DECK, OTHERWISE FALSE. THE GRID CARDS DEFINE THE GLOBAL COORDINATES OF THE STRUCTURAL NODE POINTS IN A CARTESIAN REFERENCE FRAME. GRID POINT DATA MAY ENTER THROUGH A PERMANENT FILE (SEE FRWTGR)
QUAMOD	L	TRUE IF THE FLUID MESH INPUT GEOMETRY CORRESPONDS TO A QUARTER MODEL, OTHERWISE FALSE. THE X AND Y DIRECTIONS MUST CURRENTLY BE ASSIGNED TO THE SYMMETRY AXES
PCHCDS	L	TRUE IF THE DIAGONAL GENERALIZED AREA MATRIX IS TO BE PUNCHED OUT ON CARDS FOR INPUT TO NASTRAN, OTHERWISE FALSE
NASTAM	L	TRUE IF THE FLUID MASS MATRIX OR ITS MANIPULATED FORM WHICH APPEARS IN THE DAA EQUATION IS TO BE PUT IN THE PERMANENT FILE DESIGNATED BY FLUNAM IN A FORMAT WHICH CAN BE READ BY NASTRAN, OTHERWISE FALSE
STOMAS	L	TRUE IF THE FLUID MASS MATRIX ITSELF IS TO BE PUT IN PERMANENT STORAGE, OTHERWISE FALSE
STOINV	L	TRUE IF THE MANIPULATED FORM OF THE FLUID MASS MATRIX WHICH APPEARS IN THE DAA EQUATION IS TO BE PUT IN PERMANENT STORAGE, OTHERWISE FALSE
FRWTFL	L	TRUE IF THE PERMANENT FILE CONTAINING THE FLUID MASS MATRIX OR ITS MANIPULATED FORM IS TO BE CREATED BY BUFFERED, UNFORMATTED FORTRAN WRITE STATEMENTS, OTHERWISE FALSE AND DMGASP WILL CREATE THE FILE
FRWTGE	L	TRUE IF THE PERMANENT FILE CONTAINING THE FLUID MESH GEOMETRY IS TO BE CREATED BY BUFFERED, UNFORMATTED FORTRAN WRITE STATEMENTS, OTHERWISE FALSE AND DMGASP WILL CREATE THE FILE
FRWTGR	L	TRUE IF THE PERMANENT FILE CONTAINING STRUCTURAL GRID POINT COORDINATES HAS BEEN CREATED BY BUFFERED, UNFORMATTED FORTRAN WRITE STATEMENTS, OTHERWISE FALSE IN WHICH CASE IT IS ASSUMED THAT DMGASP WAS USED TO CREATE THE FILE. CONSULT A

		LISTING OF THE SUBROUTINE READST FOR THE FILE STRUCTURE THAT IS EXPECTED WHICH DIFFERS FOR THE TWO POSSIBLE CASES. THIS FILE MUST EXIST FOR INTERFACING WITH STAGS (SEE GRDCRD)
FLUNAM	A	NAME OF PERMANENT MASS STORAGE FILE WHICH WILL CONTAIN EITHER THE FLUID MASS MATRIX OR ITS MANIPULATED DAA FORM
GEONAM	A	NAME OF PERMANENT MASS STORAGE FILE WHICH WILL CONTAIN THE FLUID MESH GEOMETRY AND FLUID-STRUCTURE TRANSFORMATION DATA
GRDNAM	A	NAME OF PERMANENT MASS STORAGE FILE WHICH CONTAINS THE GLOBAL COORDINATES OF THE STRUCTURAL GRID POINTS
NHAR	I	INDEX OF CIRCUMFERENTIAL HARMONIC FOR SOR ELEMENTS TO BE USED IN FLUID BOUNDARY MODE ANALYSIS
NVEC	I	NUMBER OF FLUID BOUNDARY MODE EIGENVECTORS DESIRED. THESE ARE ORDERED STARTING WITH THE LOWEST ORDER MODES FIRST
NUMZ	I	NUMBER OF FICTITIOUS ELEMENTS TO BE ADDED IN AXIAL DIRECTION WHICH INCREASE THE HALF LENGTH OF THE SURFACE FOR THE SIMULATION OF A TWO DIMENSIONAL PLANE STRAIN FLUID MASS MATRIX. THESE ELEMENTS DO NOT INTRODUCE NEW DEGREES OF FREEDOM
ZLEN	E,F	LENGTH OF FICTITIOUS AXIAL ELEMENTS USED IN THE SIMULATION OF A TWO DIMENSIONAL PLANE STRAIN FLUID MASS MATRIX
CQ	E,F	TAKES ON THE VALUE OF EITHER PLUS OR MINUS ONE TO DENOTE SYMMETRIC OR ANTISYMMETRIC FLOW CONDITIONS IN EACH QUADRANT OF A FLUID MESH THAT IS TO BE REPRESENTED BY A QUARTER MODEL OF THE SURFACE
NTCY	I	NUMBER OF STRUCTURAL NODE POINTS THAT COUPLE WITH A CURVED RECTANGULAR FLUID ELEMENT WHICH IS TO BE AUTOMATICALLY FORMED FOR AN AXIAL SEGMENT OF A RIGHT CIRCULAR CYLINDRICAL SURFACE. AVAILABLE OPTIONS ARE: 2 - STRUCTURAL NODES WILL BE ON MIDPOINT OF CURVED SIDES 4 - STRUCTURAL NODES WILL BE AT CORNERS
NSEQ	I	STRUCTURAL GRID POINT NUMBER
NS	I	WILL EVENTUALLY CONTAIN POINTER TO DENOTE TYPE OF COORDINATE SYSTEM GRID POINT DATA

```
                                  IS REFERRED TO. CURRENTLY ONLY GLOBAL
                                  CARTESIAN COORDINATES ARE ALLOWABLE. SET
                                  TO ZERO

XC,YC,ZC        E,F               CARTESIAN COORDINATES OF STRUCTURAL GRID
                                  POINT

NEL             I                 GENERAL FLUID ELEMENT INDEX WHICH RUNS
                                  FROM 1 TO NGEN IN SEQUENTIAL ORDER

NC              I                 NUMBER OF CORNER POINTS OF GENERAL FLUID
                                  ELEMENT. CURRENTLY RESTRICTED TO THE
                                  VALUES 3 OR 4. SEE FLUID ELEMENT LIBRARY.
                                  THE CORNER POINTS WILL USUALLY PARTICIPATE
                                  IN THE FLUID-STRUCTURE TRANSFORMATION

NN              I                 NUMBER OF ADDITIONAL NEIGHBOR POINTS
                                  ASSOCIATED WITH A PARTICULAR GENERAL FLUID
                                  ELEMENT. CURRENTLY HAVING PERMISSIBLE
                                  VALUES OF 1, 2, 3, AND 5. SEE FLUID
                                  ELEMENT LIBRARY. THESE ADDITIONAL POINTS
                                  ALSO PARTICIPATE IN THE FLUID-STRUCTURE
                                  TRANSFORMATION

KURV            I                 FLUID ELEMENT CURVATURE FLAG. ACCEPTABLE
                                  VALUES ARE:

                                    0 - FLAT ELEMENT
                                    1 - CURVED ELEMENT. CODE WILL DETERMINE
                                        AVERAGE CURVATURE OF ELEMENT FROM
                                        NEIGHBOR POINT LOCATIONS. DO NOT USE
                                        THIS OPTION IF NN = 0
                                    2 - CURVED ELEMENT. USER MUST INPUT
                                        PRINCIPLE RADII OF CURVATURE. IF
                                        EITHER RADIUS IS SET TO 10000 OR
                                        GREATER THEN ITS ASSOCIATED
                                        CURVATURE WILL BE SET TO ZERO

NODE            I                 NODE POINT NUMBERS OF FLUID ELEMENT CORNER
                                  POINTS TAKEN IN COUNTER CLOCKWISE
                                  DIRECTION. ASSIGN A NEGATIVE VALUE TO ANY
                                  NODE NUMBERS WHICH ARE NOT PART OF THE
                                  STRUCTURAL FINITE ELEMENT MODEL SO THEY
                                  WILL NOT PARTICIPATE IN THE FLUID-
                                  STRUCTURE TRANSFORMATION. SEE FLUID
                                  ELEMENT LIBRARY

ITEM            I                 NODE POINT NUMBERS OF FLUID ELEMENT
                                  NEIGHBOR POINTS AGAIN TAKEN IN COUNTER
                                  CLOCKWISE ORDER STARTING FROM FIRST CORNER
                                  POINT. ANY INTERIOR POINTS MUST APPEAR
                                  LAST. SEE FLUID ELEMENT LIBRARY

RAD1            E,F               RADIUS OF CURVATURE OF FLUID ELEMENT IN
                                  DIRECTION FROM FIRST CORNER POINT TO
                                  SECOND CORNER POINT

RAD2            E,F               RADIUS OF CURVATURE OF FLUID ELEMENT IN
```

		DIRECTION PERPENDICULAR TO SIDE JOINING FIRST CORNER POINT AND SECOND CORNER POINT
NCIR	I	NUMBER OF CIRCUMFERENTIAL GENERAL ELEMENTS TO BE FORMED AUTOMATICALLY FOR AN AXIAL SEGMENT OF A RIGHT CIRCULAR CYLINDRICAL SURFACE
NLAS	I	NUMBER OF LAST FLUID ELEMENT IN SURFACE MESH WHICH PRECEEDES THE INPUT FOR THIS AXIAL SEGMENT
NSTART	I	NUMBER OF STRUCTURAL GRID NODE AT THE POINT ON THE CIRCUMFERENCE WHERE THIS SET OF CIRCUMFERENTIAL GENERAL ELEMENTS BEGIN
NDAX	I	INCREMENT TO BE APPLIED IN DESIGNATING THE NUMBER OF THE CORRESPONDING STRUCTURAL NODE AT THE OTHER AXIAL BOUNDARY OF THIS SET OF CIRCUMFERENTIAL GENERAL ELEMENTS
NDCR	I	INCREMENT TO BE APPLIED IN DESIGNATING THE NUMBER OF THE CORRESPONDING STRUCTURAL NODE ONE FLUID ELEMENT AWAY IN THE CIRCUMFERENTIAL DIRECTION
RAD	E,F	RADIUS OF CIRCULAR CYLINDRICAL SURFACE
DZ	E,F	AXIAL LENGTH OF CIRCULAL CYLINDRICAL SURFACE
ZCEN	E,F	CENTROIDAL COORDINATE IN THE Z DIRECTION FOR THIS SET OF CIRCUMFERENTIAL GENERAL ELEMENTS
NSR	I	SURFACE OF REVOLUTION ELEMENT INDEX WHICH RUNS FROM 1 TO NSOR IN SEQUENTIAL ORDER
NFREE	I	WILL HAVE THE VALUE 1, 2, OR 3 DEPENDING UPON WHETHER THE NORMAL FLUID VELOCITY OF THE SURFACE OF REVOLUTION ELEMENT IS IN THE X, Y, OR Z GLOBAL COORDINATE DIRECTION
NAXIS	I	WILL HAVE THE VALUE 1, 2, OR 3 DEPENDING UPON WHETHER THE AXIS OF REVOLUTION OF THE SURFACE OF REVOLUTION ELEMENT IS PARALLEL TO THE X, Y, OR Z GLOBAL COORDINATE DIRECTION
R1	E,F	RADIUS TO WET SURFACE FROM AXIS OF SOR ELEMENT AT STRUCTURAL GRID POINT CLOSEST TO ORIGIN OF GLOBAL COORDINATE SYSTEM
R2	E,F	RADIUS TO WET SURFACE FROM AXIS OF SOR ELEMENT AT STRUCTURAL GRID POINT FURTHEST FROM ORIGIN OF GLOBAL COORDINATE SYSTEM

```
N1            I          GRID POINT NUMBER OF STRUCTURAL NODE
                         CLOSEST TO ORIGIN OF GLOBAL COORDINATE
                         SYSTEM WHICH DEFINES ONE AXIAL BOUNDARY OF
                         THE SOR ELEMENT


N2            I          GRID POINT NUMBER OF STRUCTURAL NODE
                         FURTHEST FROM ORIGIN OF GLOBAL COORDINATE
                         SYSTEM WHICH DEFINES THE OTHER AXIAL
                         BOUNDARY OF THE SOR ELEMENT

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

           I N P U T    D A T A    C A R D    D E C K

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

ALL INPUT DATA EXCEPT ALPHANUMERIC DATA MUST BE RIGHT JUSTIFIED
IN EIGHT (8) COLUMN FIELDS WHICH CAN OCCUPY THE ENTIRE CARD.
ALPHANUMERIC DATA MUST BE LEFT JUSTIFIED IN SIXTEEN (16) COLUMN
FIELDS. FILE NAMES ARE RESTRICTED TO TWELVE (12) CHARACTERS FOR
UNIVAC OPERATION WHILE SIXTEEN (16) CHARACTERS ARE ALLOWED FOR CDC
OPERATION. HENCE A NAME LIKE ABCDE*FGHIJK IS THE LIMIT FOR UNIVAC
WHILE A CDC FILE NAME MAY HAVE FOUR (4) ADDITIONAL CHARACTERS

GENERAL PROBLEM DEFINITION (SUBROUTINE AMINPT):
-----------------------------------------------

72 COLUMN ALPHANUMERIC TITLE
NSTR     NGEN     NSOR     NSEG     NCYL
DENS     CEE
PRTGMT   PRTTRN   PRTAMF   CALCAM
EIGMAF   TWODIM   GRDCRD   QUAMOD
PCHCDS   NASTAM   STOMAS   STOINV
FRWTFL   FRWTGE   FRWTGR
FLUNAM            GEONAM            GRDNAM

IF EIGMAF = .TRUE. INCLUDE THE FOLLOWING CARD

NHAR     NVEC

IF TWODIM = .TRUE. INCLUDE THE FOLLOWING TWO CARDS

NUMZ
ZLEN

IF QUAMOD = .TRUE. INCLUDE THE FOLLOWING CARD

CQ(I), I=1,4

IF NCYL IS NOT EQUAL TO ZERO READ THE FOLLOWING CARD

NTCY

STRUCTURAL NODE COORDINATES (SUBROUTINE READST):
------------------------------------------------

IF GRDCRD = .TRUE. INCLUDE THE FOLLOWING CARDS
```

```
GRID    NSEQ    N       XC      YC      ZC          )
          .     .       .       .       .           )   TOTAL = NSTR
          .     .       .       .       .           )

GENERAL ELEMENT DEFINITION (SUBROUTINE GENELM):
-----------------------------------------------

IF NGEN IS NOT EQUAL TO ZERO READ THE FOLLOWING CARDS

GEN     NEL     NC      NN      KURV        )
        NODE(I), I=1,NC                     )
        ITEM(I), I=1,NN                     )   TOTAL NUMBER OF
                                            )
IF KURV = 3 READ THE FOLLOWING CARD         )   SETS = NGEN
                                            )
        RAD1    RAD2                        )

CYLINDRICAL SURFACE GENERAL ELEMENTS (SUBROUTINE CYLGEO):
---------------------------------------------------------

IF NCYL IS NOT EQUAL TO ZERO READ THE FOLLOWING CARDS FOR EACH
AXIAL SEGMENT

NCIR    NLAS    NSTART  NDAX    NDCR
RAD     DZ      ZCEN

SURFACE-OF-REVOLUTION ELEMENT DEFINITION (SUBROUTINE SORINP):
-------------------------------------------------------------

IF NSOR IS NOT EQUAL TO ZERO READ THE FOLLOWING CARD FOR EACH
SOR DEGREE OF FREEDOM

SOR     NSR     NFREE   NAXIS   R1      R2      N1      N2
```

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

              F L U I D     E L E M E N T     L I B R A R Y

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

   THE CORNER POINTS OF EACH OF THE ELEMENT TYPES SHOWN BELOW ARE
   ASSUMED TO LIE IN THE SAME PLANE AND THE DIRECTION OF THE UNIT
   NORMAL VECTOR IS TAKEN TO BE POSITIVE AS COMING UP FROM THE PAGE
   AND OUT INTO THE FLUID REGION. THE VIEWER IS THUS PLACED IN THE
   SAME RELATIVE POSITION AS A SCUBA DIVER GAZING AT THE SIDE OF A
   SUNKEN TREASURE SHIP. THE NODE ORDER FOR INPUT MUST ALWAYS BE IN
   THE COUNTERCLOCKWISE DIRECTION AS SHOWN BECAUSE THE RIGHT HAND
   RULE IS USED INTERNALLY TO DETERMINE THE POSITIVE OUTWARD
   DIRECTION. NOTE THAT CORNER POINTS ARE TAKEN FIRST, THEN ANY OTHER
   POINTS WHICH MAY BE INVOLVED IN THE FLUID-STRUCTURE TRANSFORMATION
   FOLLOW. YOU MAY PLAY CONNECT-THE-DOTS WITH YOUR PENCIL TO MAKE THE
   FIGURES MORE LEGIBLE IF YOU WISH

                                                    3
   BASIC FLUID ELEMENT CONFIGURATIONS:            .  .
                                                 .     .
          3                                   4          .
         .  .                                .            .
        .     .                             .  GENERAL     .
       .        .                          .                .
      .  TRIANGLE .                       .  QUADRILATERAL .
     .              .                    .                   .
    1.................2                 1.....................2

   BASIC FLUID ELEMENT CONFIGURATIONS   4
   WITH ADDITIONAL TRANSFORMATION        .  .
   POINTS:                              .     6
                                       .        .
                                      .     .     .
                                     .              .
          4...3                     .     .  GENERAL  .
               .                   .  6-NODE             3
          .  .                    .      .  QUADRILATERAL .
          6-NODE .               .                         .
        6         .             1..........5.................2
           .        .
        .     .  .    .
                   .    .                4
       .    GENERAL  . .                   .
                        5               .     .
      .  QUADRILATERAL    .                       .
                           .           .              7
    1.....................2                         .   .
                                      .  9-NODE   .       3
                                                .           .
                                     8..........9...........6
                                                 .            .
                                    .          .  GENERAL      ..
                                              .                 .
                                   .         .  QUADRILATERAL    .
                                            .                     .
                                  1.......5.......................2
```


3
4-NODE
TRIANGLE
4
1
2
3
5
5-NODE
TRIANGLE
4
1
2
3
6
6-NODE
5
TRIANGLE
4
1
2

The following discussion is provided as an aid to user understanding of the sample output that is included here.

First, the terms appearing under "Fluid Mesh Geometric Arrays" are defined as:

NCOR - number of corner points for a particular fluid element

X,Y,Z - global cartesian coordinates of the fluid element centroidal control point

NX,NY,NZ - components of the outward unit normal vector for the fluid element

NTRA - number of structural node points that are coupled to a particular fluid element for the purpose of force application

A00,A20,A11,A02 - area and moments and product of inertia of fluid element. Used internally for construction of the fluid mass matrix and of the fluid-structure transformation coefficients for general elements.

BII,CII - diagonal terms of B and C matrices used for construction of fluid mass matrix (see [9])

When SOR elements are included in the fluid mesh the following terms will appear in the output:

RAD - radius of fluid element control point from axis of revolution

NCIR - number of integration points used in cirdumferential direction

NAXI - see NAXIS in user manual

NFRE - see NFREE in user manual

Local Fluid-Structure Transformation Coefficients appear next. This is a summary that indicates which structural nodes couple with a particular fluid control point and the weighting factor for each. The weighting factors must always sum to unity for any fluid control point.

The eigenvalues and eigenvectors that follow the listing of the added mass matrix correspond to the "Fluid Boundary Mode" problem [9]. For the infinite cylindrical shell problem presented here, the exact eigenvalues should behave as $1/n$ with corresponding modes $\cos n\theta$ and $\sin n\theta$. The first eigenvalue listed, .11838+04, is an approximation to ∞ for $n=0$ and it can be seen that the subsequent eigenvalues are relatively well behaved.

```
PLANE STRAIN SIMULATION OF INFINITE CYLINDER
         0         0         0         0        36
        1.        1.
         T         T         T         T
         T         T         F         F
         F         F         T         F
         F         F         F
CYL*MASS            CYL*GEOM
         0        36
       500
      .175
         2
        36         0         1         1         2
        1.      .175        0.

@XQT
```

PLANE STRAIN SIMULATION OF INFINITE CYLINDER

MAXIMUM FLUID NODES = 85

SCRATCH ALLOCATION = 15000

FLUID MASS DENSITY = .10000000+01

FLUID SOUND SPEED = .10000000+01

FLUID MESH GEOMETRIC ARRAYS:

N	NCOR	X	Y	Z	NX	NY	NZ
1	4	.10000000+01	.00000000	.00000000	.10000000+01	.00000000	.00000000
2	4	.98480775+00	.17364818+00	.00000000	.98480775+00	.17364818+00	.00000000
3	4	.93969262+00	.34202014+00	.00000000	.93969262+00	.34202014+00	.00000000
4	4	.86602541+00	.49999999+00	.00000000	.86602541+00	.49999999+00	.00000000
5	4	.76604445+00	.64278761+00	.00000000	.76604445+00	.64278761+00	.00000000
6	4	.64278762+00	.76604444+00	.00000000	.64278762+00	.76604444+00	.00000000
7	4	.50000001+00	.86602540+00	.00000000	.50000001+00	.86602540+00	.00000000
8	4	.34202016+00	.93969262+00	.00000000	.34202016+00	.93969262+00	.00000000
9	4	.17364819+00	.98480775+00	.00000000	.17364819+00	.98480775+00	.00000000
10	4	.15893255-07	.10000000+01	.00000000	.15893255-07	.10000000+01	.00000000
11	4	-.17364816+00	.98480776+00	.00000000	-.17364816+00	.98480776+00	.00000000
12	4	-.34202012+00	.93969263+00	.00000000	-.34202012+00	.93969263+00	.00000000
13	4	-.49999997+00	.86602542+00	.00000000	-.49999997+00	.86602542+00	.00000000
14	4	-.64278758+00	.76604447+00	.00000000	-.64278758+00	.76604447+00	.00000000
15	4	-.76604442+00	.64278764+00	.00000000	-.76604442+00	.64278764+00	.00000000
16	4	-.86602538+00	.50000004+00	.00000000	-.86602538+00	.50000004+00	.00000000
17	4	-.93969262+00	.34202017+00	.00000000	-.93969262+00	.34202017+00	.00000000
18	4	-.98480775+00	.17364820+00	.00000000	-.98480775+00	.17364820+00	.00000000
19	4	-.10000000+01	.31786509-07	.00000000	-.10000000+01	.31786509-07	.00000000
20	4	-.98480776+00	-.17364814+00	.00000000	-.98480776+00	-.17364814+00	.00000000
21	4	-.93969264+00	-.34202011+00	.00000000	-.93969264+00	-.34202011+00	.00000000
22	4	-.86602543+00	-.49999996+00	.00000000	-.86602543+00	-.49999996+00	.00000000
23	4	-.76604448+00	-.64278757+00	.00000000	-.76604448+00	-.64278757+00	.00000000
24	4	-.64278768+00	-.76604439+00	.00000000	-.64278768+00	-.76604439+00	.00000000
25	4	-.50000005+00	-.86602537+00	.00000000	-.50000005+00	-.86602537+00	.00000000
26	4	-.34202018+00	-.93969261+00	.00000000	-.34202018+00	-.93969261+00	.00000000
27	4	-.17364825+00	-.98480774+00	.00000000	-.17364825+00	-.98480774+00	.00000000
28	4	-.47679764-07	-.10000000+01	.00000000	-.47679764-07	-.10000000+01	.00000000
29	4	.17364810+00	-.98480777+00	.00000000	.17364810+00	-.98480777+00	.00000000
30	4	.34202009+00	-.93969264+00	.00000000	.34202009+00	-.93969264+00	.00000000
31	4	.49999992+00	-.86602545+00	.00000000	.49999992+00	-.86602545+00	.00000000
32	4	.64278756+00	-.76604449+00	.00000000	.64278756+00	-.76604449+00	.00000000
33	4	.76604442+00	-.64278764+00	.00000000	.76604442+00	-.64278764+00	.00000000

34	4	.86602537+00	-.50000007+00	.00000000	.86602537+00	-.50000007+00	.00000000
35	4	.93969260+00	-.34202019+00	.00000000	.93969260+00	-.34202019+00	.00000000
36	4	.98480774+00	-.17364826+00	.00000000	.98480774+00	-.17364826+00	.00000000

N	NTRA	A00	A20	A11	A02	BII	CII
1	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
2	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
3	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
4	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
5	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
6	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
7	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
8	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
9	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
10	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
11	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
12	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
13	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
14	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
15	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
16	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
17	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
18	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
19	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
20	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
21	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
22	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
23	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
24	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
25	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
26	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
27	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
28	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
29	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
30	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
31	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
32	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
33	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
34	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
35	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01
36	2	.30543262-01	.77533404-04	.11102230-13	.77948942-04	.61613729+00	.64372196+01

LOCAL FLUID-STRUCTURE TRANSFORMATION COEFFICIENTS:

NFLU	NSTR	
1	1	2
	.50000+00	.50000+00
2	3	4
	.50000+00	.50000+00
3	5	6
	.50000+00	.50000+00
4	7	8
	.50000+00	.50000+00
5	9	10
	.50000+00	.50000+00

6	11	12
	.50000+00	.50000+00
7	13	14
	.50000+00	.50000+00
8	15	16
	.50000+00	.50000+00
9	17	18
	.50000+00	.50000+00
10	19	20
	.50000+00	.50000+00
11	21	22
	.50000+00	.50000+00
12	23	24
	.50000+00	.50000+00
13	25	26
	.50000+00	.50000+00
14	27	28
	.50000+00	.50000+00
15	29	30
	.50000+00	.50000+00
16	31	32
	.50000+00	.50000+00
17	33	34
	.50000+00	.50000+00
18	35	36
	.50000+00	.50000+00
19	37	38
	.50000+00	.50000+00
20	39	40
	.50000+00	.50000+00
21	41	42
	.50000+00	.50000+00
22	43	44
	.50000+00	.50000+00
23	45	46
	.50000+00	.50000+00
24	47	48
	.50000+00	.50000+00
25	49	50
	.50000+00	.50000+00
26	51	52
	.50000+00	.50000+00
27	53	54
	.50000+00	.50000+00
28	55	56
	.50000+00	.50000+00
29	57	58
	.50000+00	.50000+00
30	59	60
	.50000+00	.50000+00
31	61	62
	.50000+00	.50000+00
32	63	64
	.50000+00	.50000+00
33	65	66
	.50000+00	.50000+00
34	67	68
	.50000+00	.50000+00

```
35          69          70
         .50000+00   .50000+00
36          71          72
         .50000+00   .50000+00

+++  @ ASG.UPR        CYL*GEOM.,  F/      4/ TRK/  1024
+++  @ USE      2.    CYL*GEOM.

++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+         A U X I L I A R Y    S T O R A G E    T A B L E            +
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+                                                                    +
+ LDI    EXT-NAME UNT EC OPT SEC  CDLOC    NEXT  LIMIT     READ WRITTEN +
+  2     CYL*GEOM   2 36 UPR  28    237     237  65536        0    6600 +
+                                                                    +
+                   1 ACTIVE DEVICES ( 0 FULL)                        +
+       0 TP-OPS,      4 WRITES,        0 READS,        6600 WORDS XFD +
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++

+++  @ FREE           CYL*GEOM.
```

ADDED MASS MATRIX IN FLUID COORDINATES:

	1	2	3	4	5	6	7	8	9	10
1	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01
2	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01
3	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01
4	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01
5	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01
6	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01
7	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01
8	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01
9	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01
10	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01
11	.10037+01	.10033+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01
12	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01
13	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01
14	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01
15	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01
16	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01
17	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01
18	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01
19	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01
20	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01
21	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01
22	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01
23	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01
24	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01
25	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01
26	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01
27	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01
28	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01
29	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01
30	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01
31	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01
32	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01
33	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01

34	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01
35	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01
36	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01
	11	12	13	14	15	16	17	18	19	20
1	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01
2	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01
3	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01
4	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01
5	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01
6	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01
7	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01
8	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01
9	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01
10	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01
11	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01
12	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01
13	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01
14	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01
15	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01
16	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01
17	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01
18	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01
19	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01
20	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01
21	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01
22	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01
23	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01
24	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01
25	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01
26	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01
27	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01
28	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01
29	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01
30	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01
31	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01
32	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01
33	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01
34	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01
35	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01
36	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01
	21	22	23	24	25	26	27	28	29	30
1	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01
2	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01
3	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01
4	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01
5	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01
6	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01
7	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01
8	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01
9	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01
10	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01
11	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01
12	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01
13	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01
14	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01
15	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01
16	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01
17	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01

18	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01
19	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01
20	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01
21	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01
22	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01
23	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01
24	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01
25	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01
26	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01
27	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01
28	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01
29	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01
30	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01
31	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01
32	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01
33	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01
34	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01
35	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01
36	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01

	31	32	33	34	35	36
1	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01
2	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01	.10062+01
3	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01	.10055+01
4	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01	.10050+01
5	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01	.10047+01
6	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01	.10044+01
7	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01	.10042+01
8	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01	.10040+01
9	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01	.10038+01
10	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01	.10037+01
11	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01	.10035+01
12	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01	.10035+01
13	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01	.10034+01
14	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01	.10033+01
15	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01	.10033+01
16	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01	.10032+01
17	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01	.10032+01
18	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01	.10032+01
19	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01	.10032+01
20	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01	.10032+01
21	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01	.10033+01
22	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01	.10033+01
23	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01	.10034+01
24	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01	.10035+01
25	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01	.10035+01
26	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01	.10037+01
27	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01	.10038+01
28	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01	.10040+01
29	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01	.10042+01
30	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01	.10044+01
31	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01	.10047+01
32	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01	.10050+01
33	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01	.10055+01
34	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01	.10062+01
35	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01	.10074+01
36	.10047+01	.10050+01	.10055+01	.10062+01	.10074+01	.10102+01

+++ @ ASG,UPR CYL=MASS., F/ 4/ TRK/ 1024

```
+++  @ USE     3.    CYL+MASS.

+++  @ ASG.T          UNIT04., F4/     4/ TRK/   256
+++  @ USE     4.     UNIT04.
```

EIGENVALUES:

1	2	3	4	5	6	7	8	9	10
.11838+04	.99860+00	.99859+00	.49810+00	.49809+00	.33073+00	.33072+00	.24668+00	.24668+00	.19609+00
11	12	13	14	15	16	17	18	19	20
.19609+00	.16237+00	.16237+00	.13840+00	.13840+00	.12060+00	.12059+00	.10695+00	.10694+00	.96271-01
21	22	23	24	25	26	27	28	29	30
.96269-01	.87829-01	.87827-01	.81150-01	.81147-01	.75908-01	.75907-01	.71879-01	.71874-01	.68889-01
31	32	33	34	35	36				
.68887-01	.66821-01	.66818-01	.65607-01	.65606-01	.65207-01				

EIGENVECTORS:

	1	2	3	4	5	6	7	8	9	10
1	.95365+00	.13455+01	.91100-01	.12370+01	-.61289+00	-.12886+01	-.39697+00	.97952+00	-.92341+00	.83940-01
2	.95365+00	.13090+01	.32336+00	.13463+01	-.16504+00	-.13152+01	.30066+00	.13465+01	-.75511-01	.10853+01
3	.95365+00	.12326+01	.54582+00	.12930+01	.30273+00	-.98898+00	.91773+00	.10830+01	.80769+00	.13109+01
4	.95365+00	.11188+01	.75168+00	.10839+01	.73397+00	-.39798+00	.12889+01	.31296+00	.13130+01	.60012+00
5	.95365+00	.97099+00	.93471+00	.74401+00	.10767+01	.29963+00	.13147+01	-.60348+00	.12039+01	-.53934+00
6	.95365+00	.79371+00	.10893+01	.31441+00	.12895+01	.91696+00	.98825+00	-.12375+01	.53152+00	-.12935+01
7	.95365+00	.59230+00	.12109+01	-.15313+00	.13469+01	.12886+01	.39698+00	-.12926+01	-.38958+00	-.11236+01
8	.95365+00	.37290+00	.12956+01	-.60218+00	.12417+01	.13150+01	-.30066+00	-.74280+00	-.11284+01	-.15096+00
9	.95365+00	.14218+00	.13410+01	-.97859+00	.98682+00	.98898+00	-.91773+00	.15458+00	-.13392+01	.92960+00
10	.95365+00	-.92870-01	.13456+01	-.12370+01	.61288+00	.39800+00	-.12889+01	.97961+00	-.92341+00	.13460+01
11	.95365+00	-.32509+00	.13093+01	-.13462+01	.16503+00	-.29964+00	-.13147+01	.13463+01	-.75526-01	.60080+00
12	.95365+00	-.54744+00	.12333+01	-.12930+01	-.30273+00	-.91698+00	-.98825+00	.10830+01	.80769+00	-.31649+00
13	.95365+00	-.75316+00	.11198+01	-.10839+01	-.73397+00	-.12886+01	-.39699+00	.31301+00	.13130+01	-.12077+01
14	.95365+00	-.93593+00	.97223+00	-.74401+00	-.10767+01	-.13150+01	.30065+00	-.60347+00	.12039+01	-.12361+01
15	.95365+00	-.10904+01	.79515+00	-.31442+00	-.12895+01	-.98897+00	.91772+00	-.12376+01	.53151+00	-.38145+00
16	.95365+00	-.12116+01	.59391+00	.15310+00	-.13469+01	-.39802+00	.12889+01	-.12926+01	-.38959+00	.74576+00
17	.95365+00	-.12961+01	.37462+00	.60217+00	-.12417+01	.29958+00	.13147+01	-.74279+00	-.11284+01	.13402+01
18	.95365+00	-.13412+01	.14395+00	.97858+00	-.98681+00	.91695+00	.98828+00	.15450+00	-.13392+01	.97711+00
19	.95365+00	-.13455+01	-.91092-01	.12370+01	-.61289+00	.12886+01	.39701+00	.97958+00	-.92340+00	-.83950-01
20	.95365+00	-.13089+01	-.32337+00	.13462+01	-.16503+00	.13150+01	-.30063+00	.13463+01	-.75524-01	-.10851+01
21	.95365+00	-.12326+01	-.54582+00	.12930+01	.30273+00	.98899+00	-.91773+00	.10831+01	.80769+00	-.13110+01
22	.95365+00	-.11188+01	-.75168+00	.10839+01	.73397+00	.39805+00	-.12889+01	.31304+00	.13130+01	-.60037+00
23	.95365+00	-.97100+00	-.93471+00	.74402+00	.10767+01	-.29956+00	-.13148+01	-.60343+00	.12039+01	.53923+00
24	.95365+00	-.79371+00	-.10893+01	.31443+00	.12895+01	-.91692+00	-.98828+00	-.12375+01	.53151+00	.12936+01
25	.95365+00	-.59231+00	-.12109+01	-.15307+00	.13469+01	-.12886+01	-.39700+00	-.12926+01	-.38958+00	.11238+01
26	.95365+00	-.37291+00	-.12956+01	-.60213+00	.12417+01	-.13150+01	.30065+00	-.74284+00	-.11284+01	.15116+00
27	.95365+00	-.14219+00	-.13410+01	-.97858+00	.98682+00	-.98900+00	.91773+00	.15443+00	-.13392+01	-.92953+00
28	.95365+00	.92858-01	-.13456+01	-.12370+01	.61289+00	-.39805+00	.12889+01	.97946+00	-.92341+00	-.13461+01
29	.95365+00	.32509+00	-.13093+01	-.13462+01	.16504+00	.29954+00	.13148+01	.13462+01	-.75516-01	-.80098+00
30	.95365+00	.54743+00	-.12333+01	-.12930+01	-.30272+00	.91690+00	.98826+00	.10831+01	.80770+00	.31632+00
31	.95365+00	.75315+00	-.11198+01	-.10839+01	-.73397+00	.12886+01	.39700+00	.31313+00	.13130+01	.12077+01
32	.95365+00	.93598+00	-.97223+00	-.74404+00	-.10767+01	.13149+01	-.30064+00	-.60329+00	.12039+01	.12363+01
33	.95365+00	.10904+01	-.79515+00	-.31444+00	-.12895+01	.98900+00	-.91774+00	-.12374+01	.53153+00	.38167+00
34	.95365+00	.12116+01	-.59391+00	.15307+00	-.13469+01	.39810+00	-.12889+01	-.12926+01	-.38959+00	-.74569+00
35	.95365+00	.12961+01	-.37462+00	.60214+00	-.12417+01	-.29951+00	-.13147+01	-.74295+00	-.11284+01	-.13403+01
36	.95365+00	.13411+01	-.14395+00	.97855+00	-.98682+00	-.91684+00	-.98829+00	.15431+00	-.13392+01	-.97738+00

	11	12	13	14	15	16	17	18	19	20
1	.13473+01	-.70567+00	.11491+01	-.71234+00	-.11153+01	-.48015+00	-.12417+01	-.59091+00	.12130+01	.13866+00
2	.81747+00	-.13485+01	-.36482-01	-.13201+01	.33064+00	-.13249+01	.30239+00	-.12125+01	-.58800+00	-.13453+01

3	-.29628+00	-.64215+00	-.11858+01	-.18996+00	.13418+01	.21103-01	.13468+01	.59251+00	-.12139+01	.32955+00
4	-.11984+01	.70602+00	-.11493+01	.11898+01	.58709+00	.13318+01	.16535+00	.12118+01	.58843+00	.12304+01
5	-.12443+01	.13481+01	.36570-01	.10038+01	-.94019+00	.44139+00	-.12894+01	-.59247+00	.12139+01	-.75689+00
6	-.40126+00	.64215+00	.11858+01	-.50315+00	-.12302+01	-.11785+01	-.61313+00	-.12120+01	-.58851+00	-.96757+00
7	.72840+00	-.70590+00	.11493+01	-.13479+01	.98600-01	-.85060+00	.10764+01	.59252+00	-.12137+01	.10931+01
8	.13377+01	-.13482+01	-.36548-01	-.41900+00	.12977+01	.88287+00	.98705+00	.12119+01	.58847+00	.58783+00
9	.99134+00	-.64232+00	-.11859+01	.10612+01	.78908+00	.11571+01	-.73356+00	-.59250+00	.12136+01	-.12973+01
10	-.63299-01	.70584+00	-.11493+01	.11450+01	-.75798+00	-.48077+00	-.12418+01	-.12118+01	-.58845+00	-.13726+00
11	-.10727+01	.13482+01	.36590-01	-.27794+00	-.13075+01	-.13242+01	.30229+00	.59230+00	-.12136+01	.13449+01
12	-.13157+01	.64236+00	.11859+01	-.13351+01	-.13641+00	.20846-01	.13469+01	.12119+01	.58852+00	-.32967+00
13	-.61877+00	-.70577+00	.11493+01	-.63537+00	.12142+01	.13314+01	.16538+00	-.59221+00	.12135+01	-.12304+01
14	.52023+00	-.13482+01	-.36596-01	.90050+00	.96699+00	.44166+00	-.12894+01	-.12120+01	-.58855+00	.75694+00
15	.12876+01	-.64233+00	-.11859+01	.12515+01	-.55280+00	-.11780+01	-.61322+00	.59214+00	-.12135+01	.96764+00
16	.11350+01	.70571+00	-.11493+01	-.44532-01	-.13451+01	-.85097+00	.10765+01	.12119+01	.58852+00	-.10931+01
17	.17165+00	.13481+01	.36591-01	-.12820+01	-.36722+00	.88231+00	.98714+00	-.59205+00	.12135+01	-.58817+00
18	-.91440+00	.64254+00	.11859+01	-.83227+00	.10938+01	.11576+01	-.73378+00	-.12118+01	-.58849+00	.12976+01
19	-.13472+01	-.70568+00	.11493+01	.71247+00	.11155+01	-.48036+00	-.12419+01	.59171+00	-.12136+01	.13738+00
20	-.81749+00	-.13482+01	-.36593-01	.13197+01	-.33078+00	-.13244+01	.30242+00	.12119+01	.58866+00	-.13452+01
21	.29623+00	-.64257+00	-.11859+01	.19027+00	-.13417+01	.20220-01	.13469+01	-.59166+00	.12135+01	.32959+00
22	.11983+01	.70563+00	-.11493+01	-.11895+01	-.58701+00	.13315+01	.16529+00	-.12119+01	-.58867+00	.12309+01
23	.12443+01	.13482+01	.36571-01	-.10040+01	.94019+00	.44221+00	-.12895+01	.59150+00	-.12134+01	-.75707+00
24	.40131+00	.64259+00	.11859+01	.50263+00	.12301+01	-.11779+01	-.61308+00	.12119+01	.58866+00	-.96803+00
25	-.72833+00	-.70562+00	.11493+01	.13479+01	-.98697-01	-.85142+00	.10766+01	-.59136+00	.12134+01	.10931+01
26	-.13377+01	-.13482+01	-.36598-01	.41946+00	-.12977+01	.88226+00	.98697+00	-.12119+01	-.58871+00	.58858+00
27	-.99138+00	-.64253+00	-.11858+01	-.10609+01	-.78899+00	.11580+01	-.73386+00	.59128+00	-.12133+01	-.12974+01
28	.63216-01	.70557+00	-.11493+01	-.11452+01	.75807+00	-.48012+00	-.12418+01	.12120+01	.58868+00	-.13816+00
29	.10727+01	.13481+01	.36581-01	.27738+00	.13075+01	-.13248+01	.30262+00	-.59123+00	.12132+01	.13452+01
30	.13157+01	.64261+00	.11858+01	.13351+01	.13630+00	.20061-01	.13469+01	-.12119+01	-.58868+00	-.32870+00
31	.61883+00	-.70549+00	.11492+01	.63584+00	-.12143+01	.13317+01	.16519+00	.59102+00	-.12132+01	-.12312+01
32	-.52017+00	-.13482+01	-.36591-01	-.90019+00	-.96689+00	.44243+00	-.12895+01	.12119+01	.58867+00	.75614+00
33	-.12876+01	-.64267+00	-.11858+01	-.12516+01	.55287+00	-.11779+01	-.61303+00	-.59086+00	.12133+01	.96870+00
34	-.11351+01	.70555+00	-.11492+01	.44048-01	.13450+01	-.85149+00	.10766+01	-.12118+01	-.58864+00	-.10923+01
35	-.17167+00	.13481+01	.36624-01	.12817+01	.36719+00	.88203+00	.98696+00	.59067+00	-.12133+01	-.58957+00
36	.91441+00	.64274+00	.11858+01	.83281+00	-.10939+01	.11580+01	-.73389+00	.12120+01	.58880+00	.12971+01

	21	22	23	24	25	26	27	28	29	30
1	-.13413+01	-.69815+00	.11824+01	.55539+00	-.12377+01	-.65568-01	.13464+01	-.80572-01	.13451+01	.70929+00
2	.94490-01	.13232+01	.20513+00	-.13420+01	.15544+00	-.98934+00	-.91388+00	-.80317+00	-.10820+01	-.11870+01
3	.13086+01	-.20785+00	-.13227+01	.78802+00	.10826+01	.13379+01	-.17153+00	.13122+01	.31177+00	.13478+01
4	-.54900+00	-.11803+01	.69958+00	.55333+00	-.12382+01	-.73084+00	.11342+01	-.12076+01	.60464+00	-.11477+01
5	-.11179+01	.10154+01	.84413+00	-.13414+01	.15560+00	-.39852+00	-.12867+01	.53782+00	-.12383+01	.63989+00
6	.93728+00	.48605+00	-.12771+01	.78791+00	.10825+01	.12432+01	.51999+00	.38363+00	.12928+01	.39536-01
7	.79233+00	-.13481+01	.29444-01	.55385+00	-.12382+01	-.11995+01	.61848+00	-.11254+01	-.74244+00	-.70815+00
8	-.12124+01	.43619+00	.12569+01	-.13419+01	.15581+00	.29865+00	-.13154+01	.13404+01	-.15548+00	.11867+01
9	-.37122+00	.10499+01	-.88922+00	.78775+00	.10824+01	.81540+00	.10726+01	-.92821+00	.98056+00	-.13473+01
10	.13413+01	-.11545+01	-.64864+00	.55451+00	-.12383+01	-.13468+01	-.63459-01	.81708-01	-.13468+01	.11470+01
11	-.94582-01	-.26015+00	.13329+01	-.13424+01	.15589+00	.91590+00	-.99104+00	.80296+00	.10831+01	-.63934+00
12	-.13085+01	.13323+01	-.26310+00	.78775+00	.10823+01	.16943+00	.13376+01	-.13119+01	-.31273+00	-.39565-01
13	.54902+00	-.65114+00	-.11530+01	.55470+00	-.12381+01	-.11337+01	-.72864+00	.12069+01	-.60385+00	.70785+00
14	.11178+01	-.88702+00	.10518+01	-.13423+01	.15581+00	.12881+01	-.40091+00	-.53706+00	.12380+01	-.11864+01
15	-.93719+00	.12578+01	.43360+00	.78752+00	.10823+01	-.52206+00	.12442+01	-.38404+00	-.12930+01	.13471+01
16	-.79229+00	.26860-01	-.13484+01	.55466+00	-.12381+01	-.61708+00	-.11988+01	.11253+01	.74298+00	-.11470+01
17	.12124+01	-.12760+01	.48875+00	-.13422+01	.15583+00	.13153+01	.29698+00	-.13401+01	.15446+00	.63937+00
18	.37121+00	.84565+00	.10140+01	.78756+00	.10822+01	-.10736+01	.81720+00	.92786+00	-.97937+00	.39896-01
19	-.13413+01	.69794+00	-.11824+01	.55438+00	-.12379+01	.64649-01	-.13478+01	-.81643-01	.13458+01	-.70879+00
20	.94656-01	-.13232+01	-.20518+00	-.13417+01	.15566+00	.99057+00	.91560+00	-.80262+00	-.10826+01	.11879+01
21	.13084+01	.20721+00	.13228+01	.78700+00	.10823+01	-.13382+01	.17065+00	.13112+01	.31286+00	-.13486+01
22	-.54914+00	.11813+01	-.69970+00	.55492+00	-.12380+01	.72987+00	-.11349+01	-.12062+01	.60336+00	.11481+01
23	-.11176+01	-.10151+01	-.84415+00	-.13419+01	.15579+00	.39978+00	.12883+01	.53657+00	-.12375+01	-.63989+00

24	.93728+00	-.48706+00	.12772+01	.78668+00	.10822+01	-.12439+01	-.52131+00	.38408+00	.12928+01	-.39849-01
25	.79212+00	.13483+01	-.29538-01	.55534+00	-.12381+01	.11992+01	-.61818+00	-.11250+01	-.74341+00	.70883+00
26	-.12124+01	-.43530+00	-.12570+01	-.13419+01	.15535+00	-.29771+00	.13161+01	.13396+01	-.15348+00	-.11876+01
27	-.37110+00	-.10506+01	.88933+00	.78646+00	.10822+01	-.81641+00	-.10737+01	-.92716+00	.97666+00	.13483+01
28	.13413+01	.11540+01	.64864+00	.55538+00	-.12381+01	.13472+01	.64125-01	.80695-01	-.13462+01	-.11477+01
29	-.94698-01	.26148+00	-.13330+01	-.13419+01	.15589+00	-.91552+00	.99104+00	.80347+00	.10839+01	.63926+00
30	-.13085+01	-.13331+01	.26314+00	.78648+00	.10822+01	-.17018+00	-.13380+01	-.13115+01	-.31447+00	.40797-01
31	.54916+00	.65049+00	.11530+01	.55539+00	-.12380+01	.11342+01	.72909+00	.12057+01	-.60223+00	-.71008+00
32	.11178+01	.88821+00	-.10519+01	-.13419+01	.15585+00	-.12890+01	.40059+00	-.53584+00	.12372+01	.11889+01
33	-.93740+00	-.12581+01	-.43347+00	.78643+00	.10821+01	.52166+00	-.12440+01	-.38468+00	-.12933+01	-.13489+01
34	-.79224+00	-.27863-01	.13483+01	.55581+00	-.12380+01	.61744+00	.11989+01	.11252+01	.74465+00	.11475+01
35	.12126+01	.12773+01	-.48882+00	-.13424+01	.15597+00	-.13156+01	-.29743+00	-.13392+01	.15212+00	-.63868+00
36	.37109+00	-.84591+00	-.10140+01	.78656+00	.10819+01	.10740+01	-.81636+00	.92652+00	-.97756+00	-.41190-01

	31	32	33	34	35	36
1	.11386+01	.37644+00	-.12761+01	-.72628+00	.11543+01	-.96128+00
2	-.62444+00	-.79595+00	.10505+01	.91157+00	-.10148+01	.96067+00
3	-.57249-01	.11200+01	-.69752+00	-.10698+01	.84465+00	-.95932+00
4	.72362+00	-.13093+01	.26047+00	.11958+01	-.64894+00	.95781+00
5	-.11962+01	.13403+01	.20801+00	-.12853+01	.43336+00	-.95636+00
6	.13484+01	-.12096+01	-.65151+00	.13355+01	-.20459+00	.95499+00
7	-.11392+01	.93307+00	.10161+01	-.13453+01	-.30146-01	-.95395+00
8	.62470+00	-.54419+00	-.12579+01	.13144+01	.26371+00	.95325+00
9	.56961-01	.89491-01	.13483+01	-.12433+01	-.48948+00	-.95256+00
10	-.72324+00	.37619+00	-.12765+01	.11343+01	.70061+00	.95189+00
11	.11956+01	-.79660+00	.10511+01	-.99062+00	-.89053+00	-.95125+00
12	-.13476+01	.11211+01	-.69906+00	.81685+00	.10534+01	.95066+00
13	.11386+01	-.13104+01	.26276+00	-.61825+00	-.11843+01	-.95017+00
14	-.62449+00	.13416+01	.20520+00	.40074+00	.12791+01	.94979+00
15	-.56878-01	-.12108+01	-.64856+00	-.17112+00	-.13350+01	-.94969+00
16	.72290+00	.93384+00	.10141+01	-.63464-01	.13503+01	.95000+00
17	-.11953+01	-.54420+00	-.12574+01	.29612+00	-.13247+01	-.95038+00
18	.13477+01	.89110-01	.13488+01	-.51996+00	.12593+01	.95061+00
19	-.11393+01	.37656+00	-.12775+01	.72826+00	-.11560+01	-.95061+00
20	.62576+00	-.79674+00	.10521+01	-.91460+00	.10179+01	.95055+00
21	.55373-01	.11208+01	-.69985+00	.10732+01	-.84895+00	-.95054+00
22	-.72162+00	-.13095+01	.26307+00	-.11993+01	.65441+00	.95054+00
23	.11945+01	.13403+01	.20546+00	.12890+01	-.44008+00	-.95063+00
24	-.13473+01	-.12094+01	-.64909+00	-.13394+01	.21234+00	.95093+00
25	.11391+01	.93258+00	.10146+01	.13492+01	.21790-01	-.95122+00
26	-.62563+00	-.54314+00	-.12580+01	-.13181+01	-.25510+00	.95150+00
27	-.55360-01	.88254-01	.13498+01	.12470+01	.48079+00	-.95205+00
28	.72141+00	.37725+00	-.12789+01	-.11378+01	-.69208+00	.95277+00
29	-.11942+01	-.79739+00	.10541+01	.99404+00	.88227+00	-.95349+00
30	.13472+01	.11215+01	-.70275+00	-.82020+00	-.10454+01	.95418+00
31	-.11393+01	-.13105+01	.26698+00	.62147+00	.11768+01	-.95498+00
32	.62618+00	.13413+01	.20090+00	-.40379+00	-.12726+01	.95608+00
33	.54761-01	-.12102+01	-.64458+00	.17376+00	.13299+01	-.95739+00
34	-.72089+00	.93318+00	.10104+01	.61418-01	-.13468+01	.95864+00
35	.11938+01	-.54367+00	-.12542+01	-.29455+00	.13225+01	-.95978+00
36	-.13469+01	.88711-01	.13466+01	.51859+00	-.12578+01	.96081+00

```
+++  @ FREE            UNIT04.

+++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+          A U X I L I A R Y    S T O R A G E    T A B L E           +
+++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+                                                                     +
+ LDI   EXT-NAME UNT EC OPT SEC  CDLOC   NEXT  LIMIT     READ WRITTEN +
```

```
+  3     CYL*MASS    3 36 UPR  28      47      47  65536         0     1296 +
+                                                                          +
+                          1 ACTIVE DEVICES ( 0 FULL)                      +
+        0 TP-OPS,        6 WRITES,        1 READS,     10488 WORDS XFD   +
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++

+++  * FREE              CYL*MASS.
```

APPENDIX C

USER INFORMATION FOR THE AUGMENTED MATRIX PREPROCESSOR AUGMAT

The following includes modifications which were made under separate contract to the Naval Surface Weapons Center, Contract Number N60921-77-C-0112.

This appendix includes a copy of the users manual, and a sample input deck and subsequent output for the infinite cylindrical shell problem presented in Section 4.

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                                 A U G M A T

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      THIS FUNCTIONAL COMPONENT OF THE UNDERWATER SHOCK ANALYSIS CODE
      ACCEPTS DATA FROM THE FLUID MASS MATRIX PROCESSOR AND THE
      STRUCTURAL ANALYZER TO CONSTRUCT THE SPECIFIC CONSTANTS AND ARRAYS
      THAT ARE USED IN THE STAGGERED SOLUTION PROCEDURE FOR THE
      TRANSIENT RESPONSE ANALYSIS OF SUBMERGED STRUCTURES

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      THIS PROGRAM WAS DEVELOPED AND CODED BY JOHN A. DERUNTZ, JR.
      OF LOCKHEED MISSILES AND SPACE CO. RESEARCH LABS IN PALO ALTO
      CALIFORNIA. PLEASE CONSULT WITH AUTHOR BEFORE MAKING CHANGES
      AND ALSO REPORT ANY MALFUNCTIONS OR PROBLEMS. WRITE IN CARE OF
      LOCKHEED PALO ALTO RESEARCH LABORATORY, BLDG 205, DEPT 52-33,
      3251 HANOVER ST., PALO ALTO, CALIF., 94304 OR CALL 415-493-4411
      EXTS. 45069 OR 45133.                               FEBRUARY, 1978

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

  W A R N I N G     F R O M     T H E     P R O G R A M M E R     G E N E R A L

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      THIS CODE CONTAINS THE SPECIAL INGREDIENT DMGASP NOT FOUND IN
      OTHER BRANDS. DMGASP IS A DATA MANAGEMENT UTILITY MODULE THAT
      WILL ACTIVATE AND DEACTIVATE ALL AUXILIARY STORAGE DATA FILES
      REFERENCED BY THE CODE. HENCE THE NAMES OF SUCH FILES SHOULD NOT
      APPEAR ON ANY CONTROL CARDS IN THE RUN STREAM WHICH MIGHT NORMALLY
      ACTIVATE AND DEACTIVATE THE FILES. THE USER IS ALSO CAUTIONED THAT
      PREVIOUSLY CREATED FILES MUST ALREADY BE RESIDENT IN THE SYSTEM
      BEFORE THE RUN IS INITIATED. IF A FILE HAS BEEN ROLLED-OUT TO TAPE
      DMGASP WILL ATTEMPT TO HAVE THE FILE ROLLED-IN EVERY 15 SECONDS
      FOR UP TO 15 MINUTES ON THE UNIVAC 1100-EXEC 8 OPERATING SYSTEM.
      IF AN EXISTING DATA FILE HAS NOT BEEN REFERENCED FOR SOME TIME IT
      IS THEREFORE GOOD POLICY TO SIMPLY ACTIVATE AND DEACTIVATE THE
      FILE BEFORE EXECUTION OF THIS CODE. IF THE USER ATTEMPTS TO CREATE
      A NEW DATA FILE WITH A NAME WHICH IS ALREADY ASSIGNED TO AN
      EXISTING FILE, THE UNIVAC VERSION OF DMGASP WILL MODIFY THE NAME
      OF THE FILE GENERATED BY THIS RUN TO AVOID ANY CONFLICT. FILE NAME
      DUPLICATION WILL CAUSE NO PROBLEM ON THE CDC SCOPE OPERATING
      SYSTEM AS SCOPE WILL SIMPLY CATALOG A NEW CYCLE OF THE SAME FILE.
      ON THE OTHER HAND THE CDC NOS SYSTEM IS SIMILAR TO UNIVAC IN THIS
      REGARD AND THE RUN WILL ABORT SINCE THE NAME-CHANGING FEATURE OF
      DMGASP HAS NOT BEEN IMPLEMENTED FOR NOS. QUALIFIER*FILENAME IS THE
      REQUIRED INPUT DATA FORMAT FOR ALL UNIVAC PERMANENT FILE NAMES.
      FOR CDC OPERATION QUALIFIER IS REPLACED BY THE FILE ID, WHICH IS
      THE USER ID BY DEFAULT

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                             P R O G R A M     S I Z E
```

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

        ALL ARRAYS REFERRENCED IN THIS CODE THAT ARE PROBLEM DEPENDENT
        RESIDE IN BLANK COMMON. THE SIZE OF BLANK COMMON IS DETERMINED BY
        A PARAMETER STATEMENT IN THE MAIN PROGRAM FOR THE UNIVAC 1100-OS
        VERSION. HENCE A RECOMPILATION IS NECESSARY TO INCREASE OR
        DECREASE CORE ALLOCATION. IN THE CDC 6600 VERSION RECOMPILATION IS
        UNNECESSARY AS THE LENGTH OF BLANK COMMON IS SET BY A FIELD LENGTH
        REQUEST IN THE CONTROL CARD DECK

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

        D E F I N I T I O N    O F    I N P U T    P A R A M E T E R S

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

        INPUT VARIABLE NAMES GIVEN BELOW ARE GENERALLY THOSE WHICH ARE
        ALSO USED IN THE CODING AND THE VARIABLE TYPES CORRESPOND TO
        STANDARD FORTRAN USAGE:

                       A    -    ALPHANUMERIC
                       E    -    FLOATING POINT
                       F    -    FIXED POINT
                       I    -    INTEGER
                       L    -    LOGICAL

        --------       ----                      -----------
        VARIABLE       TYPE                      DESCRIPTION
        --------       ----                      -----------

        NSTR           I         NUMBER OF NODE POINTS IN STRUCTURAL MODEL

        NGEN           I         NUMBER OF GENERAL FLUID DEGREES OF FREEDOM

        NSOR           I         NUMBER OF SURFACE OF REVOLUTION FLUID
                                 DEGREES OF FREEDOM

        NSEG           I         NUMBER OF SURFACE OF REVOLUTION SEGMENTS
                                 IN FLUID MODEL

        NSFR           I         NUMBER OF STRUCTURAL DEGREES OF FREEDOM.
                                 WHEN INTERFACING WITH THE NONLINEAR
                                 STRUCTURAL ANALYZER STAGS THIS PARAMETER
                                 IS ALWAYS ONE LARGER THAN THE NUMBER OF
                                 ACTUAL DEGREES OF FREEDOM SINCE STAGS ADDS
                                 ONE FICTITIOUS EQUATION AND DEGREE OF
                                 FREEDOM TO THE SYSTEM FOR SOME STRANGE
                                 REASON KNOWN ONLY TO BO ALMROTH AND FRANK
                                 BROGAN. THIS EXTRA FREEDOM ALWAYS APPEARS
                                 FIRST IN THE EQUATION SET

        NFRE           I         THE LARGEST DEGREE OF FREEDOM INDEX AT ANY
                                 STRUCTURAL NODE WHICH IS REFERENCED IN THE
                                 ANALYSIS. FREEDOMS 1, 2, AND 3 ARE ASSUMED
                                 TO BE TRANSLATIONAL WHILE 4, 5, AND 6 ARE
                                 RESERVED FOR ROTATIONS

        NFTR           I         THE LARGEST TRANSLATIONAL DEGREE OF
```

```
                                FREEDOM INDEX AT ANY NODE WHICH IS
                                REFERENCED IN THE ANALYSIS

         NMOD         I         THE LARGEST NUMBER OF RIGID BODY FLUID
                                DEGREES OF FREEDOM ASSOCIATED WITH ANY ONE
                                SURFACE OF REVOLUTION SEGMENT (MAXIMUM OF
                                TWO)

         NSETLC       I         NUMBER OF DATA SETS REQUIRED TO DEFINE THE
                                TYPE OF STRUCTURAL COORDINATE SYSTEM WITH
                                WHICH ANY PARTICULAR FLUID ELEMENT MUST
                                INTERACT

         NDICOS       I         DESIGNATES THE TYPE OF COORDINATE SYSTEM
                                USED IN THE STRUCTURAL SOLUTION.
                                ACCEPTABLE VALUES ARE:

                                  0 - GLOBAL COORDINATES
                                  1 - LOCAL COORDINATES WITH THE FIRST
                                      DEGREE OF FREEDOM NORMAL TO THE
                                      FLUID-STRUCTURE CONTACT BOUNDARY
                                  2 - LOCAL COORDINATES WITH THE SECOND
                                      DEGREE OF FREEDOM NORMAL TO THE
                                      FLUID-STRUCTURE CONTACT BOUNDARY
                                  3 - LOCAL COORDINATES WITH THE THIRD
                                      DEGREE OF FREEDOM NORMAL TO THE
                                      FLUID-STRUCTURE CONTACT BOUNDARY

                                AT THIS TIME OPTIONS 1, 2, OR 3 MAY BE
                                USED ONLY FOR RIGHT CIRCULAR CYLINDERS OR
                                SPHERES. MORE LATITUDE IN THESE CHOICES IS
                                ULTIMATELY PLANNED

         JSTART       I         FIRST OF ONE OR MORE FLUID ELEMENTS HAVING
                                THE SAME VALUE OF NDICOS

         JSTOP        I         LAST OF ONE OR MORE FLUID ELEMENTS HAVING
                                THE SAME VALUE OF NDICOS

         JINC         I         INCREMENT TO BE APPLIED IN ASSIGNING THE
                                VALUE OF NDICOS TO FLUID ELEMENTS IN THE
                                RANGE FROM JSTART TO JSTOP

         FRWTGE       L         TRUE IF THE PERMANENT FILE CONTAINING THE
                                FLUID MESH GEOMETRY WAS CREATED BY
                                BUFFERED FORTRAN WRITE STATEMENTS.
                                OTHERWISE FALSE

         FRWTST       L         TRUE IF THE PERMANENT FILE CONTAINING THE
                                STRUCTURAL MASS AND STIFFNESS MATRICES
                                WAS CREATED BY BUFFERED FORTRAN WRITE
                                STATEMENTS. OTHERWISE FALSE

         FRWTFL       L         TRUE IF THE PERMANENT FILE CONTAINING THE
                                FLUID MASS MATRIX WAS CREATED BY BUFFERED
                                FORTRAN WRITE STATEMENTS. OTHERWISE FALSE

         FLUSKY       L         TRUE IF THE FLUID MASS MATRIX HAS BEEN
```

```
                                   STORED IN SKYLINE FORM. OTHERWISE FALSE

         DAAFRM         L          TRUE IF THE STORED FLUID MATRIX CONSISTS
                                   OF THE INVERTED FLUID MASS MATRIX WHICH
                                   HAS BEEN PRE- AND POST-MULTIPLIED BY THE
                                   DIAGONAL FLUID ELEMENT AREA MATRIX AND
                                   THEN MULTIPLIED BY BOTH THE MASS DENSITY
                                   AND THE SPEED OF SOUND OF THE FLUID. THE
                                   RESULTING MATRIX IS THE MOST CONVENIENT
                                   FORM FOR USE IN THE DAA EQUATION. IF FALSE
                                   THEN THIS PROCESSOR WILL DO THE JOB

         PRTGMT         L          TRUE IF FLUID MESH GEOMETRY DATA IS TO BE
                                   LISTED. OTHERWISE FALSE

         PRTTRN         L          TRUE IF FLUID-STRUCTURE TRANSFORMATION
                                   DATA IS TO BE LISTED. OTHERWISE FALSE

         RHO            E,F        FLUID MASS DENSITY

         CEE            E,F        FLUID SPEED OF SOUND

         STRNAM         A          NAME OF PERMANENT MASS STORAGE FILE WHICH
                                   CONTAINS THE STRUCTURAL MASS AND STIFFNESS
                                   MATRICES AS WELL AS BOOKEEPING INFORMATION
                                   RELATING THE INTERNAL AND EXTERNAL DEGREES
                                   OF FREEDOM. WHEN INTERFACING WITH THE
                                   NONLINEAR STRUCTURAL ANALYZER STAGS THE
                                   STIFFNESS MATRIX IS NOT PRESENT

         FLUNAM         A          NAME OF PERMANENT MASS STORAGE FILE WHICH
                                   CONTAINS EITHER THE FLUID MASS MATRIX OR
                                   ITS MANIPULATED DAA FORM

         GEONAM         A          NAME OF PERMANENT MASS STORAGE FILE WHICH
                                   CONTAINS THE FLUID MESH GEOMETRY AND
                                   FLUID-STRUCTURE TRANSFORMATION DATA

         PRENAM         L          NAME OF PERMANENT MASS STORAGE FILE
                                   CREATED BY THIS PROCESSOR WHICH CONTAINS
                                   ALL THE INFORMATION REQUIRED TO CONDUCT
                                   THE UNDERWATER SHOCK ANALYSIS OF THE
                                   STRUCTURE IN QUESTION EXCEPT FOR THE
                                   EXCITATION AND INTEGRATION DATA

    * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                 I N P U T     D A T A     C A R D     D E C K

    * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

         ALL INPUT DATA EXCEPT ALPHANUMERIC DATA MUST BE RIGHT JUSTIFIED
         IN EIGHT (8) COLUMN FIELDS WHICH CAN OCCUPY THE ENTIRE CARD.
         ALPHANUMERIC DATA MUST BE LEFT JUSTIFIED IN SIXTEEN (16) COLUMN
         FIELDS. FILE NAMES ARE RESTRICTED TO TWELVE (12) CHARACTERS FOR
         UNIVAC OPERATION WHILE SIXTEEN (16) CHARACTERS ARE ALLOWED FOR CDC
         OPERATION. HENCE A NAME LIKE ABCDE*FGHIJK IS THE LIMIT FOR UNIVAC
         WHILE A CDC FILE NAME MAY HAVE FOUR (4) ADDITIONAL CHARACTERS
```

```
GENERAL PROBLEM DEFINITION (MAIN PROGRAM PREPROC):
--------------------------------------------------

72 COLUMN ALPHANUMERIC TITLE
NSTR     NGEN     NSOR     NSEG
NSFR     NFRE     NFTR     NMOD
NSETLC
NDICOS   JSTART   JSTOP    JINC      )
   .        .        .        .      )   TOTAL = NSETLC
   .        .        .        .      )
FRWTGE   FRWTST   FRWTFL
FLUSKY   DAAFRM
PRTGMT   PRTTRN
RHO      CEE
STRNAM            FLUNAM            GEONAM            PRENAM
```

The following discussion is provided as an aid to user understanding of the sample output that is included here.

After a summary of the fluid mesh geometry arrays (see Appendix B) the first item needing explanation is that entitled "Fluid Element Wetted Freedom Indicator". This is simply a listing of the input variable NDICOS (see user manual) for each fluid element.

The section "Structural Grid Point Numbers Associated With Internal Sequence Numbers" contains a correspondence table that relates the internal sequence numbers assigned by the fluid mass processor with the external structural node number assigned by the user.

The next item entitled "Grid Point and Freedom Number for Each Row of Stiffness Matrix" identifies an integer vector that is constructed by the user in the Skyline Utility (see Figure 3-1, also Appendix F). For each structural equation the entry in the vector consists of ten times the structural node number plus the local degree of freedom number.

The last item requiring explanation is the "Freedom/Equation Correspondence Table". This is an integer matrix of 6 rows and as many columns as there are structural node points. Any particular row corresponds to a local degree of freedom number while a column corresponds to the internal sequence number for a particular external node number. The matrix entry for any particular set of row and column is the structural equation number for that pair.

```
PRE-PROCESSING RUN FOR INFINITE CYLINDER SIMULATION
        72        36         0         0
       432         6         3         0
         1
         1         1        36         1
         F         F         F
         F         F
         T         T
        1.        1.
INF*CYLSKY      CYL*MASS        CYL*GEOM        CYL*PREPN

@XQT
```

PRE-PROCESSING RUN FOR INFINITE CYLINDER SIMULATION

FLUID MASS DENSITY = .10000000+01

FLUID SOUND SPEED = .10000000+01

```
+++ @ ASG,UPR      CYL*PREPN.,  F/    4/ TRK/  1024
+++ @ USE    16,   CYL*PREPN.

+++ @ ASG,AX        CYL*GEOM.
+++ @ USE    14,    CYL*GEOM.

+++ @ FREE          CYL*GEOM.
```

FLUID MESH GEOMETRIC ARRAYS:

N	NTRA	X	Y	Z	NX	NY	NZ	A00
1	2	.10000000+01	.00000000	.00000000	.10000000+01	.00000000	.00000000	.30543262-01
2	2	.98480775+00	.17364818+00	.00000000	.98480775+00	.17364818+00	.00000000	.30543262-01
3	2	.93969262+00	.34202014+00	.00000000	.93969262+00	.34202014+00	.00000000	.30543262-01
4	2	.86602541+00	.49999999+00	.00000000	.86602541+00	.49999999+00	.00000000	.30543262-01
5	2	.76604445+00	.64278761+00	.00000000	.76604445+00	.64278761+00	.00000000	.30543262-01
6	2	.64278762+00	.76604444+00	.00000000	.64278762+00	.76604444+00	.00000000	.30543262-01
7	2	.50000001+00	.86602540+00	.00000000	.50000001+00	.86602540+00	.00000000	.30543262-01
8	2	.34202016+00	.93969262+00	.00000000	.34202016+00	.93969262+00	.00000000	.30543262-01
9	2	.17364819+00	.98480775+00	.00000000	.17364819+00	.98480775+00	.00000000	.30543262-01
10	2	.15893255-07	.10000000+01	.00000000	.15893255-07	.10000000+01	.00000000	.30543262-01
11	2	-.17364816+00	.98480776+00	.00000000	-.17364816+00	.98480776+00	.00000000	.30543262-01
12	2	-.34202012+00	.93969263+00	.00000000	-.34202012+00	.93969263+00	.00000000	.30543262-01
13	2	-.49999997+00	.86602542+00	.00000000	-.49999997+00	.86602542+00	.00000000	.30543262-01
14	2	-.64278758+00	.76604447+00	.00000000	-.64278758+00	.76604447+00	.00000000	.30543262-01
15	2	-.76604442+00	.64278764+00	.00000000	-.76604442+00	.64278764+00	.00000000	.30543262-01
16	2	-.86602538+00	.50000004+00	.00000000	-.86602538+00	.50000004+00	.00000000	.30543262-01
17	2	-.93969262+00	.34202017+00	.00000000	-.93969262+00	.34202017+00	.00000000	.30543262-01
18	2	-.98480775+00	.17364820+00	.00000000	-.98480775+00	.17364820+00	.00000000	.30543262-01
19	2	-.10000000+01	.31786509-07	.00000000	-.10000000+01	.31786509-07	.00000000	.30543262-01
20	2	-.98480776+00	-.17364814+00	.00000000	-.98480776+00	-.17364814+00	.00000000	.30543262-01
21	2	-.93969264+00	-.34202011+00	.00000000	-.93969264+00	-.34202011+00	.00000000	.30543262-01
22	2	-.86602543+00	-.49999996+00	.00000000	-.86602543+00	-.49999996+00	.00000000	.30543262-01
23	2	-.76604448+00	-.64278757+00	.00000000	-.76604448+00	-.64278757+00	.00000000	.30543262-01
24	2	-.64278768+00	-.76604439+00	.00000000	-.64278768+00	-.76604439+00	.00000000	.30543262-01
25	2	-.50000005+00	-.86602537+00	.00000000	-.50000005+00	-.86602537+00	.00000000	.30543262-01
26	2	-.34202018+00	-.93969261+00	.00000000	-.34202018+00	-.93969261+00	.00000000	.30543262-01
27	2	-.17364825+00	-.98480774+00	.00000000	-.17364825+00	-.98480774+00	.00000000	.30543262-01
28	2	-.47679764-07	-.10000000+01	.00000000	-.47679764-07	-.10000000+01	.00000000	.30543262-01
29	2	.17364810+00	-.98480777+00	.00000000	.17364810+00	-.98480777+00	.00000000	.30543262-01
30	2	.34202009+00	-.93969264+00	.00000000	.34202009+00	-.93969264+00	.00000000	.30543262-01

31	2	.49999992+00	-.86602545+00	.00000000	.49999992+00	-.86602545+00	.00000000	.30543262-01
32	2	.64278756+00	-.76604449+00	.00000000	.64278756+00	-.76604449+00	.00000000	.30543262-01
33	2	.76604442+00	-.64278764+00	.00000000	.76604442+00	-.64278764+00	.00000000	.30543262-01
34	2	.86602537+00	-.50000007+00	.00000000	.86602537+00	-.50000007+00	.00000000	.30543262-01
35	2	.93969260+00	-.34202019+00	.00000000	.93969260+00	-.34202019+00	.00000000	.30543262-01
36	2	.98480774+00	-.17364826+00	.00000000	.98480774+00	-.17364826+00	.00000000	.30543262-01

LOCAL FLUID-STRUCTURE TRANSFORMATION COEFFICIENTS:

NFLU	NSTR	
1	1	2
	.50000+00	.50000+00
2	3	4
	.50000+00	.50000+00
3	5	6
	.50000+00	.50000+00
4	7	8
	.50000+00	.50000+00
5	9	10
	.50000+00	.50000+00
6	11	12
	.50000+00	.50000+00
7	13	14
	.50000+00	.50000+00
8	15	16
	.50000+00	.50000+00
9	17	18
	.50000+00	.50000+00
10	19	20
	.50000+00	.50000+00
11	21	22
	.50000+00	.50000+00
12	23	24
	.50000+00	.50000+00
13	25	26
	.50000+00	.50000+00
14	27	28
	.50000+00	.50000+00
15	29	30
	.50000+00	.50000+00
16	31	32
	.50000+C0	.50000+00
17	33	34
	.50000+00	.50000+00
18	35	36
	.50000+00	.50000+00
19	37	38
	.50000+00	.50000+00
20	39	40
	.50000+00	.50000+00
21	41	42
	.50000+00	.50000+00
22	43	44
	.50000+00	.50000+00
23	45	46
	.50000+00	.50000+00
24	47	48

```
          .50000+00   .50000+00
  25         49          50
          .50000+00   .50000+00
  26         51          52
          .50000+00   .50000+00
  27         53          54
          .50000+00   .50000+00
  28         55          56
          .50000+00   .50000+00
  29         57          58
          .50000+00   .50000+00
  30         59          60
          .50000+00   .50000+00
  31         61          62
          .50000+00   .50000+00
  32         63          64
          .50000+00   .50000+00
  33         65          66
          .50000+00   .50000+00
  34         67          68
          .50000+00   .50000+00
  35         69          70
          .50000+00   .50000+00
  36         71          72
          .50000+00   .50000+00

 FLUID ELEMENT WETTED FREEDOM INDICATOR:

          1          2          3          4          5          6          7          8          9         10
          1          1          1          1          1          1          1          1          1          1

         11         12         13         14         15         16         17         18         19         20
          1          1          1          1          1          1          1          1          1          1

         21         22         23         24         25         26         27         28         29         30
          1          1          1          1          1          1          1          1          1          1

         31         32         33         34         35         36
          1          1          1          1          1          1


 GENERALIZED FLUID AREAS:

          1          2          3          4          5          6          7          8          9         10
  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01
         11         12         13         14         15         16         17         18         19         20
  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01
         21         22         23         24         25         26         27         28         29         30
  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01
         31         32         33         34         35         36
  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01  .30543-01
+++  @ ASG,AX      INF*CYLSKY.
+++  @ USE    18,  INF*CYLSKY.

 DIAGONAL STRUCTURAL MASS MATRIX:

          1          2          3          4          5          6          7          8          9         10
```

.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
11	12	13	14	15	16	17	18	19	20
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
21	22	23	24	25	26	27	28	29	30
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
31	32	33	34	35	36	37	38	39	40
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
41	42	43	44	45	46	47	48	49	50
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
51	52	53	54	55	56	57	58	59	60
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
61	62	63	64	65	66	67	68	69	70
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
71	72	73	74	75	76	77	78	79	80
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
81	82	83	84	85	86	87	88	89	90
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
91	92	93	94	95	96	97	98	99	100
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
101	102	103	104	105	106	107	108	109	110
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
111	112	113	114	115	116	117	118	119	120
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
121	122	123	124	125	126	127	128	129	130
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
131	132	133	134	135	136	137	138	139	140
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
141	142	143	144	145	146	147	148	149	150
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
151	152	153	154	155	156	157	158	159	160
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
161	162	163	164	165	166	167	168	169	170
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
171	172	173	174	175	176	177	178	179	180
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
181	182	183	184	185	186	187	188	189	190
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
191	192	193	194	195	196	197	198	199	200
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
201	202	203	204	205	206	207	208	209	210
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
211	212	213	214	215	216	217	218	219	220
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
221	222	223	224	225	226	227	228	229	230
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
231	232	233	234	235	236	237	238	239	240
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
241	242	243	244	245	246	247	248	249	250
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
251	252	253	254	255	256	257	258	259	260
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
261	262	263	264	265	266	267	268	269	270
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
271	272	273	274	275	276	277	278	279	280
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
281	282	283	284	285	286	287	288	289	290
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
291	292	293	294	295	296	297	298	299	300

.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
301	302	303	304	305	306	307	308	309	310
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
311	312	313	314	315	316	317	318	319	320
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
321	322	323	324	325	326	327	328	329	330
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
331	332	333	334	335	336	337	338	339	340
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
341	342	343	344	345	346	347	348	349	350
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
351	352	353	354	355	356	357	358	359	36C
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
361	362	363	364	365	366	367	368	369	370
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
371	372	373	374	375	376	377	378	379	380
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
381	382	383	384	385	386	387	388	389	390
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
391	392	393	394	395	396	397	398	399	400
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
401	402	403	404	405	406	407	408	409	410
.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02
411	412	413	414	415	416	417	418	419	420
.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000	.00000	.00000
421	422	423	424	425	426	427	428	429	430
.11973-02	.11973-02	.11973-02	.00000	.00000	.00000	.11973-02	.11973-02	.11973-02	.00000
431	432								
.00000	.00000								

+++ @ FREE INF*CYLSKY.

STRUCTURAL GRID POINT NUMBERS ASSOCIATED WITH INTERNAL SEQUENCE NUMBERS:

1	2	3	4	5	6	7	8	9	10
1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60
51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70
61	62	63	64	65	66	67	68	69	70
71	72								
71	72								

GRID POINT AND FREEDOM NUMBER FOR EACH ROW OF STIFFNESS MATRIX:

1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	21	22	23	24
11	12	13	14	15	16	17	18	19	20
25	26	31	32	33	34	35	36	41	42
21	22	23	24	25	26	27	28	29	30
43	44	45	46	51	52	53	54	55	56
31	32	33	34	35	36	37	38	39	40
61	62	63	64	65	66	71	72	73	74
41	42	43	44	45	46	47	48	49	50
75	76	81	82	83	84	85	86	91	92
51	52	53	54	55	56	57	58	59	60
93	94	95	96	101	102	103	104	105	106
61	62	63	64	65	66	67	68	69	70
111	112	113	114	115	116	121	122	123	124
71	72	73	74	75	76	77	78	79	80
125	126	131	132	133	134	135	136	141	142
81	82	83	84	85	86	87	88	89	90
143	144	145	146	151	152	153	154	155	156
91	92	93	94	95	96	97	98	99	100
161	162	163	164	165	166	171	172	173	174
101	102	103	104	105	106	107	108	109	110
175	176	181	182	183	184	185	186	191	192
111	112	113	114	115	116	117	118	119	120
193	194	195	196	201	202	203	204	205	206
121	122	123	124	125	126	127	128	129	130
211	212	213	214	215	216	221	222	223	224
131	132	133	134	135	136	137	138	139	140
225	226	231	232	233	234	235	236	241	242
141	142	143	144	145	146	147	148	149	150
243	244	245	246	251	252	253	254	255	256
151	152	153	154	155	156	157	158	159	160
261	262	263	264	265	266	271	272	273	274
161	162	163	164	165	166	167	168	169	170
275	276	281	282	283	284	285	286	291	292
171	172	173	174	175	176	177	178	179	180
293	294	295	296	301	302	303	304	305	306
181	182	183	184	185	186	187	188	189	190

311	312	313	314	315	316	321	322	323	324
191	192	193	194	195	196	197	198	199	200
325	326	331	332	333	334	335	336	341	342
201	202	203	204	205	206	207	208	209	210
343	344	345	346	351	352	353	354	355	356
211	212	213	214	215	216	217	218	219	220
361	362	363	364	365	366	371	372	373	374
221	222	223	224	225	226	227	228	229	230
375	376	381	382	383	284	385	386	391	392
231	232	233	234	235	236	237	238	239	240
393	394	395	396	401	402	403	404	405	406
241	242	243	244	245	246	247	248	249	250
411	412	413	414	415	416	421	422	423	424
251	252	253	254	255	256	257	258	259	260
425	426	431	432	433	434	435	436	441	442
261	262	263	264	265	266	267	268	269	270
443	444	445	446	451	452	453	454	455	456
271	272	273	274	275	276	277	278	279	280
461	462	463	464	465	466	471	472	473	474
281	282	283	284	285	286	287	288	289	290
475	476	481	482	483	484	485	486	491	492
291	292	293	294	295	296	297	298	299	300
493	494	495	496	501	502	503	504	505	506
301	302	303	304	305	306	307	308	309	310
511	512	513	514	515	516	521	522	523	524
311	312	313	314	315	316	317	318	319	320
525	526	531	532	533	534	535	536	541	542
321	322	323	324	325	326	327	328	329	330
543	544	545	546	551	552	553	554	555	556
331	332	333	334	335	336	337	338	339	340
561	562	563	564	565	566	571	572	573	574
341	342	343	344	345	346	347	348	349	350
575	576	581	582	583	584	585	586	591	592
351	352	353	354	355	356	357	358	359	360
593	594	595	596	601	602	603	604	605	606
361	362	363	364	365	366	367	368	369	370
611	612	613	614	615	616	621	622	623	624
371	372	373	374	375	376	377	378	379	380
625	626	631	632	633	634	635	636	641	642

381	382	383	384	385	386	387	388	389	390
643	644	645	646	651	652	653	654	655	656
391	392	393	394	395	396	397	398	399	400
661	662	663	664	665	666	671	672	673	674
401	402	403	404	405	406	407	408	409	410
675	676	681	682	683	684	685	686	691	692
411	412	413	414	415	416	417	418	419	420
693	694	695	696	701	702	703	704	705	706
421	422	423	424	425	426	427	428	429	430
711	712	713	714	715	716	721	722	723	724
431	432								
725	726								

FREEDOM/EQUATION CORRESPONDENCE TABLE:

	1	2	3	4	5	6	7	8	9	10
1	1	7	13	19	25	31	37	43	49	55
2	2	8	14	20	26	32	38	44	50	56
3	3	9	15	21	27	33	39	45	51	57
4	4	10	16	22	28	34	40	46	52	58
5	5	11	17	23	29	35	41	47	53	59
6	6	12	18	24	30	36	42	48	54	60
	11	12	13	14	15	16	17	18	19	20
1	61	67	73	79	85	91	97	103	109	115
2	62	68	74	80	86	92	98	104	110	116
3	63	69	75	81	87	93	99	105	111	117
4	64	70	76	82	88	94	100	106	112	118
5	65	71	77	83	89	95	101	107	113	119
6	66	72	78	84	90	96	102	108	114	120
	21	22	23	24	25	26	27	28	29	30
1	121	127	133	139	145	151	157	163	169	175
2	122	128	134	140	146	152	158	164	170	176
3	123	129	135	141	147	153	159	165	171	177
4	124	130	136	142	148	154	160	166	172	178
5	125	131	137	143	149	155	161	167	173	179
6	126	132	138	144	150	156	162	168	174	180
	31	32	33	34	35	36	37	38	39	40
1	181	187	193	199	205	211	217	223	229	235
2	182	188	194	200	206	212	218	224	230	236
3	183	189	195	201	207	213	219	225	231	237
4	184	190	196	202	208	214	220	226	232	238
5	185	191	197	203	209	215	221	227	233	239
6	186	192	198	204	210	216	222	228	234	240
	41	42	43	44	45	46	47	48	49	50
1	241	247	253	259	265	271	277	283	289	295
2	242	248	254	260	266	272	278	284	290	296
3	243	249	255	261	267	273	279	285	291	297

```
 4     244     250     256     262     268     274     280     286     292     298
 5     245     251     257     263     269     275     281     287     293     299
 6     246     252     258     264     270     276     282     288     294     300

        51      52      53      54      55      56      57      58      59      60
 1     301     307     313     319     325     331     337     343     349     355
 2     302     308     314     320     326     332     338     344     350     356
 3     303     309     315     321     327     333     339     345     351     357
 4     304     310     316     322     328     334     340     346     352     358
 5     305     311     317     323     329     335     341     347     353     359
 6     306     312     318     324     330     336     342     348     354     360

        61      62      63      64      65      66      67      68      69      70
 1     361     367     373     379     385     391     397     403     409     415
 2     362     368     374     380     386     392     398     404     410     416
 3     363     369     375     381     387     393     399     405     411     417
 4     364     370     376     382     388     394     400     406     412     418
 5     365     371     377     383     389     395     401     407     413     419
 6     366     372     378     384     390     396     402     408     414     420

        71      72
 1     421     427
 2     422     428
 3     423     429
 4     424     430
 5     425     431
 6     426     432

+++  @ ASG,AX        CYL*MASS.
+++  @ USE    12,    CYL*MASS.

+++  @ FREE          CYL*MASS.

++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+          A U X I L I A R Y   S T O R A G E   T A B L E             +
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+                                                                    +
+ LDI   EXT-NAME UNT EC OPT SEC  CDLOC   NEXT  LIMIT     READ WRITTEN +
+ 14   CYL*PREPN  16 36 UPR  28      2     86  65536       73    2247 +
+                                                                    +
+                   1 ACTIVE DEVICES ( 0 FULL)                       +
+       0 TP-OPS,        9 WRITES,       11 READS,     11082 WORDS XFD +
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++

+++  @ FREE         CYL*PREPN.

- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -
       SUMMARY OF DATA STORED ON PERMANENT FILE
             ***   CYL*PREPN          ***
- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -
RECORD      RECORD DESCRIPTION       SECTOR       NUMBER
                                    LOCATION     OF WORDS
- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -

   1     FILE LIBRARY DATA              0            31
```

2	FLUID GEOMETRY AND TRANSFORMATION DATA	2	540
3	GENERALIZED FLUID AREAS	22	36
4	FREEDOM/EQUATION CORRESPONDENCE TABLE	24	432
5	DIAGONAL STRUCTURAL MASS INV	40	432
6	DIAGONAL POINTERS FOR DAA STRUCTURAL MASS INV	56	37
7	SKYLINE ENTRIES FOR DAA STRUCTURAL MASS INV	58	36
8	DIAGONAL POINTERS FOR DAA VIRTUAL MASS INV	60	37
9	SKYLINE ENTRIES FOR DAA VIRTUAL MASS INV	62	666

APPENDIX D

USER INFORMATION FOR THE TIME INTEGRATION PROCESSOR TIMINT

The following includes modifications which were made under separate contract to the Naval Surface Weapons Center, Contract Number N60921-77-C-0112.

This appendix includes a copy of the users manual, and a sample input deck and subsequent output for the infinite cylindrical shell problem presented in Section 4.

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                          T I M I N T

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      THIS FUNCTIONAL COMPONENT OF THE UNDERWATER SHOCK ANALYSIS CODE
      CONDUCTS A STEP-BY-STEP DIRECT NUMERICAL TIME INTEGRATION OF THE
      GOVERNING EQUATIONS OF SUBMERGED STRUCTURES EXPOSED TO SPHERICAL
      SHOCK WAVES OF ARBITRARY PRESSURE PROFILE AND SOURCE LOCATION. THE
      FLUID EQUATIONS UTILIZE THE WELL-KNOWN DOUBLY ASYMPTOTIC
      APPROXIMATION (DAA) WHILE THE STRUCTURE ITSELF MAY BE TREATED BY A
      VARIETY OF LINEAR OR NONLINEAR PROGRAM MODULES THAT CARRY OUT THE
      SPATIAL ANALYSIS AT EACH TIME STEP. THE CODE USES THE STAGGERED
      SOLUTION PROCEDURE WHEREIN THE STRUCTURAL RESPONSE EQUATIONS AND
      THE FLUID RESPONSE EQUATIONS ARE SOLVED SEPARATELY AT EACH TIME
      STEP THROUGH EXTRAPOLATION OF THE TERMS WHICH COUPLE THE TWO
      SYSTEMS

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      THIS PROGRAM WAS DEVELOPED AND CODED BY JOHN A. DERUNTZ, JR.
      OF LOCKHEED MISSILES AND SPACE CO. RESEARCH LABS IN PALO ALTO
      CALIFORNIA. PLEASE CONSULT WITH AUTHOR BEFORE MAKING CHANGES
      AND ALSO REPORT ANY MALFUNCTIONS OR PROBLEMS. WRITE IN CARE OF
      LOCKHEED PALO ALTO RESEARCH LABORATORY, BLDG 205, DEPT 52-33,
      3251 HANOVER ST., PALO ALTO, CALIF., 94304 OR CALL 415-493-4411
      EXTS. 45069 OR 45133.                              FEBRUARY, 1978

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                    M A X I M U M     V A L U E S

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      MAXIMUM NUMBER OF INPUT PRESSURE DATA POINTS   . . . . . . . . .   2 0 1

      MAXIMUM NUMBER OF DIFFERENT TIME STEP SIZES    . . . . . . . . .     1 0

      MAXIMUM NUMBER OF TRANSIENT RESPONSE DISPLAYS  . . . . . . . . .   1 0 0

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

              R U N     T I M E     I N F O R M A T I O N

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      THE FOLLOWING INFORMATION IS PROVIDED FOR THE ESTIMATION OF CPU
      TIME IN SECONDS TO WHICH MUST BE ADDED INPUT/OUTPUT CHARGES,
      CORE-BLOCK TIME, EXECUTIVE REQUESTS, FILE CHARGES, ETC. THE RULE
      TO FOLLOW IS TO ESTIMATE CPU TIME AND THEN INCREASE THIS TO ARRIVE
      AT AN APPROXIMATE SYSTEM CHARGE ESTIMATE. FOR SMALL PROBLEMS THE
      SYSTEM CHARGES CAN EASILY DOMINATE AND A LARGE FACTOR WOULD HAVE
      TO BE APPLIED TO THE RUN TIME COMPUTED BELOW. FOR FAIRLY LARGE
      PROBLEMS (2500 DOF) THIS FACTOR DROPS DOWN TO ABOUT TWO (2) FOR
      UNIVAC OPERATION
```

```
THE ESTIMATES FOR STRUCTURAL FACTORIZATION AND ADVANCEMENT TIMES
GIVEN BELOW DO NOT APPLY TO THE USA-STAGS SYSTEM. PLEASE CONSULT A
STAGS MANUAL

DEFINITION OF VARIABLES REQUIRED FOR RUN TIME COMPUTATION:

     NSTEP      NUMBER OF TIME STEPS

     NTINC      NUMBER OF DIFFERENT TIME STEP INCREMENTS

     NDISP      NUMBER OF DEGREES OF FREEDOM FOR WHICH TRANSIENT
                RESPONSE HISTORIES ARE TO BE DISPLAYED AT CONCLUSION
                OF RUN

     NSFR       NUMBER OF DEGREES OF FREEDOM OF STRUCTURAL SYSTEM

     NFLU       NUMBER OF DEGREES OF FREEDOM OF FLUID SYSTEM

     BAVE       AVERAGE HALF BAND WIDTH OF STRUCTURAL STIFFNESS
                MATRIX

     BRMS       ROOT MEAN SQUARE HALF BAND WIDTH OF STRUCTURAL
                STIFFNESS MATRIX. USE AVERAGE HALF BAND WIDTH IF
                THIS QUANTITY IS NOT READILY AVAILABLE

     TCPU       TOTAL CENTRAL PROCESSING UNIT TIME REQUIRED FOR
                LISTED ITEMS BELOW

                TCPU = TPRE + NTINC*(TFS+TFF) + NSTEP*(TAS+TAF) + TDISP

     TPRE       CPU TIME SPENT ON PRE-PROCESSING BEFORE TIME
                INTEGRATION COMMENCES

                TPRE = 1000.*CS*(NSFR+NFLU)

     TFS        TIME REQUIRED TO FACTOR STRUCTURAL EQUATION SYSTEM

                TFS = CS*NSFR*BRMS**2/2.

     TAS        TIME REQUIRED FOR ADVANCEMENT OF ONE TIME STEP FOR
                STRUCTURAL SYSTEM

                TAS = 3.*CS*NSFR*BAVE

     TFF        TIME REQUIRED TO FACTOR FLUID EQUATION SYSTEM

                TFF = CS*NFLU**3/6.

     TAF        TIME REQUIRED FOR ADVANCEMENT OF ONE TIME STEP FOR
                FLUID SYSTEM

                TAF = CS*NFLU**2

     TDISP      CPU TIME SPENT ON DISPLAY OF RESPONSE HISTORIES

                TDISP = 500.*CS*NSTEP*NDISP

     CS         UNIT OPERATION CONSTANT IN SECONDS, CONSISTING OF A
```

```
                    FLOATING ADDITION, A FLOATING MULTIPLY, AND INDEXING

                    V A L U E S    O F    C O N S T A N T    C S
                    - - - - - -    - -    - - - - - - - -    - -

                                   O P E R A T I N G    S Y S T E M

                    PRECISION      UNIVAC          UNIVAC          CDC
                                    1108            1110           6600

                      SINGLE      5.5X10-6        3.2X10-6       1.5X10-6

                      DOUBLE      9.0X10-6        4.5X10-6         - - -

                    AT THIS TIME THE CODE OPERATES ONLY IN SINGLE
                    PRECISION

          IN ADDITION TO BILLABLE CHARGES DUE TO EXECUTION OF THIS CODE
          THERE WILL PROBABLY BE A DAILY CHARGE FOR PERMANENT FILE STORAGE.
          RESPONSE AND RESTART FILES CREATED BY THIS CODE CAN BE EXTREMELY
          LENGTHY HENCE SUCH OUTPUT FROM LARGE RUNS SHOULD BE TRANSFERRED TO
          TAPE AT THE EARLIEST OPPORTUNITY TO MINIMIZE THESE CHARGES

 * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

  W A R N I N G    F R O M    T H E    P R O G R A M M E R    G E N E R A L

 * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

          THIS CODE CONTAINS THE SPECIAL INGREDIENT DMGASP NOT FOUND IN
          OTHER BRANDS. DMGASP IS A DATA MANAGEMENT UTILITY MODULE THAT
          WILL ACTIVATE AND DEACTIVATE ALL AUXILIARY STORAGE DATA FILES
          REFERENCED BY THE CODE. HENCE THE NAMES OF SUCH FILES SHOULD NOT
          APPEAR ON ANY CONTROL CARDS IN THE RUN STREAM WHICH MIGHT NORMALLY
          ACTIVATE AND DEACTIVATE THE FILES. THE USER IS ALSO CAUTIONED THAT
          PREVIOUSLY CREATED FILES MUST ALREADY BE RESIDENT IN THE SYSTEM
          BEFORE THE RUN IS INITIATED. IF A FILE HAS BEEN ROLLED-OUT TO TAPE
          DMGASP WILL ATTEMPT TO HAVE THE FILE ROLLED-IN EVERY 15 SECONDS
          FOR UP TO 15 MINUTES ON THE UNIVAC 1100-EXEC 8 OPERATING SYSTEM.
          IF AN EXISTING DATA FILE HAS NOT BEEN REFERENCED FOR SOME TIME IT
          IS THEREFORE GOOD POLICY TO SIMPLY ACTIVATE AND DEACTIVATE THE
          FILE BEFORE EXECUTION OF THIS CODE. IF THE USER ATTEMPTS TO CREATE
          A NEW DATA FILE WITH A NAME WHICH IS ALREADY ASSIGNED TO AN
          EXISTING FILE, THE UNIVAC VERSION OF DMGASP WILL MODIFY THE NAME
          OF THE FILE GENERATED BY THIS RUN TO AVOID ANY CONFLICT. FILE NAME
          DUPLICATION WILL CAUSE NO PROBLEM ON THE CDC SCOPE OPERATING
          SYSTEM AS SCOPE WILL SIMPLY CATALOG A NEW CYCLE OF THE SAME FILE.
          ON THE OTHER HAND THE CDC NOS SYSTEM IS SIMILAR TO UNIVAC IN THIS
          REGARD AND THE RUN WILL ABORT SINCE THE NAME-CHANGING FEATURE OF
          DMGASP HAS NOT BEEN IMPLEMENTED FOR NOS. QUALIFIER*FILENAME IS THE
          REQUIRED INPUT DATA FORMAT FOR ALL UNIVAC PERMANENT FILE NAMES.
          FOR CDC OPERATION QUALIFIER IS REPLACED BY THE FILE ID, WHICH IS
          THE USER ID BY DEFAULT

 * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                          P R O G R A M    S I Z E
```

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      ALL ARRAYS REFERRENCED IN THIS CODE THAT ARE PROBLEM DEPENDENT
      RESIDE IN BLANK COMMON. THE SIZE OF BLANK COMMON IS DETERMINED BY
      A PARAMETER STATEMENT IN THE MAIN PROGRAM FOR THE UNIVAC 1100-OS
      VERSION. HENCE A RECOMPILATION IS NECESSARY TO INCREASE OR
      DECREASE CORE ALLOCATION. IN THE CDC 6600 VERSION RECOMPILATION IS
      UNNECESSARY AS THE LENGTH OF BLANK COMMON IS SET BY A FIELD LENGTH
      REQUEST IN THE CONTROL CARD DECK

      AT THIS TIME THE CODE HAS NOT BEEN SYSTEMATICALLY OVERLAYED TO
      CONSERVE SPACE IN THE INSTRUCTION BANK. THIS HAS BEEN DONE TO SOME
      EXTENT BUT HAS NOT BEEN INCLUDED HERE AS IT IS INCOMPLETE. PLEASE
      CONTACT THE AUTHOR FOR INFORMATION

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      D E F I N I T I O N     O F     I N P U T     P A R A M E T E R S

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      INPUT VARIABLE NAMES GIVEN BELOW ARE GENERALLY THOSE WHICH ARE
      ALSO USED IN THE CODING AND THE VARIABLE TYPES CORRESPOND TO
      STANDARD FORTRAN USAGE:

                    A   -    ALPHANUMERIC
                    E   -    FLOATING POINT
                    F   -    FIXED POINT
                    I   -    INTEGER
                    L   -    LOGICAL

      --------    ----                   -----------
      VARIABLE    TYPE                   DESCRIPTION
      --------    ----                   -----------

      XC,YC,ZC     E,F       CARTESIAN COORDINATES OF THE LOCATION OF
                             SPHERICAL CHARGE IN FLUID MESH SYSTEM

      SC           E,F       CHARGE STANDOFF, ABSOLUTE VALUE OF THE
                             SHORTEST DISTANCE BETWEEN THE CHARGE
                             LOCATION AND THE STRUCTURE. THE INTEGATION
                             PROCESS STARTS AT TIME EQUAL TO ZERO WITH
                             THE SPHERICAL WAVE JUST TOUCHING THE
                             STRUCTURE AT THE POINT ASSOCIATED WITH
                             THIS MINIMUM DISTANCE

      JPHIST        I        NUMBER OF EQUALLY SPACED INCIDENT PRESSURE
                             HISTORY DATA POINTS. SEE ABOVE FOR MAXIMUM
                             NUMBER ALLOWED BY CORE ALLOCATION

      DTHIST       E,F       TIME INTERVAL ASSOCIATED WITH ANY TWO
                             SUCCESSIVE INCIDENT PRESSURE HISTORY DATA
                             POINTS

      PNORM        E,F       CONSTANT MULTIPLICATIVE FACTOR TO BE
                             APPLIED TO THE INPUT PRESSURE HISTORY DATA
                             POINTS
```

PHIST		INCIDENT PRESSURE HISTORY DATA POINTS. THE VALUES USED IN THE TIME INTEGRATION PROCESS ARE THE PRODUCT OF PHIST AND PNORM TO ALLOW FOR THE POSSIBILITY THAT THE INPUT DATA MAY HAVE BEEN EXPERIMENTALLY OBTAINED AT A POINT WHICH IS NOT EQUAL TO SC ABOVE. PNORM MUST THEREFORE REFLECT THE 1/R SCALING DIFFERENCE BETWEEN SC AND THE LOCATION OF THE PRESSURE SENSOR DURING THE PULSE CHARACTERIZATION EXPERIMENT. IF THE INCIDENT PRESSURE GOES TO ZERO AT SOME POINT AND REMAINS THERE THEN DATA NEED ONLY BE PROVIDED FOR THAT TIME SPAN AND THE CODE WILL AUTOMATICALLY ENSURE THAT THE INCIDENT PRESSURE REMAINS ZERO THEREAFTER. WHEN RESTARTING THE TRANSIENT ANALYSIS THE REQUIRED INCIDENT PRESSURE DATA IS IDENTICAL TO THAT USED IN THE INITIAL RUN
NTINT	I	NUMBER OF TIME STEP SIZES TO BE USED IN THE INTEGRATION PROCESS. SEE ABOVE FOR MAXIMUM NUMBER ALLOWED BY CORE ALLOCATION
STRTIM	E,F	THE STARTING TIME AT WHICH ANY PARTICULAR STEP SIZE IS TO BE USED UNTIL IT IS EITHER SUPERCEEDED BY ANOTHER STEP SIZE OR, THE ENTIRE TRANSIENT ANALYSIS HAS BEEN COMPLETED
DELTIM		TIME STEP SIZE ASSOCIATED WITH STRTIM ABOVE
FINTIM		TIME AT WHICH THE PRESENT ANALYSIS IS TO BE TERMINATED
PRENAM	A	NAME OF PRE-PROCESSED MASS STORAGE FILE CONTAINING ALL FLUID AND STRUCTURE DATA WHICH DOES NOT DEPEND UPON ABOVE LOAD AND INTEGRATION PARAMETERS
POSNAM	A	NAME OF MASS STORAGE FILE AVAILABLE FOR POST-PROCESSING WHICH CONTAINS SYSTEM RESPONSES
RESNAM	A	NAME OF MASS STORAGE FILE WHICH CONTAINS INFORMATION FOR RESTARTING THE TRANSIENT RESPONSE ANALYSIS
NSAVER	I	FREQUENCY OF SAVING SYSTEM RESPONSES ON PERMANENT FILE POSNAM. NSAVER EXPRESSED IN NUMBER OF TIME STEPS
NRESET	I	FREQUENCY OF SAVING RESTART INFORMATION ON PERMANENT FILE RESNAM. NRESET EXPRESSED IN NUMBER OF TIME STEPS
LOCBEG	I	LOCATION IN POSNAM FILE WHERE RESPONSES

		FROM CURRENT RUN ARE TO BE PLACED. THIS LOCATION IS MEASURED EITHER IN SECTORS (28 WORDS) ON UNIVAC SYSTEMS OR PHYSICAL RECORD UNITS (PRU OF 64 WORDS) ON CDC HARDWARE. A ZERO VALUE IS THE DESIGNATION OF THE BEGINNING OF THE FILE FOR EITHER SYSTEM IN THIS CODE. IF LOCBEG = 0, A NEW PERMANENT FILE IS ASSIGNED FOR THE RUN WITH THE NAME DENOTED BY POSNAM, OTHERWISE POSNAM IS TAKEN TO BE AN EXISTING FILE. UNDER RESTART CONDITIONS THE APPROPRIATE VALUE OF LOCBEG IS ASCERTAINED FROM OUTPUT GENERATED DURING PRECEEDING RUNS
LOCRES	I	LOCATION IN PERMANENT FILE RESNAM WHERE RESTART DATA IS TO BE FOUND. SEE LOCBEG FOR DEFINITION OF LOCATION. SET EQUAL TO ZERO IN CURRENT RUN IS NOT A RESTART. OTHERWISE APPROPRIATE VALUE OF LOCRES IS ASCERTAINED FROM OUTPUT GENERATED DURING PRECEEDING RUNS
LOCWRT	I	LOCATION IN PERMANENT FILE RESNAM WHERE NEW RESTART DATA GENERATED IN THE CURRENT RUN IS TO BE WRITTEN. SEE LOCBEG FOR DEFINITION OF LOCATION. IF LOCWRT = 0, A NEW PERMANENT FILE IS ASSIGNED FOR THE RUN WITH THE NAME DENOTED BY RESNAM, OTHERWISE RESNAM IS TAKEN TO BE AN EXISTING FILE. UNDER RESTART CONDITIONS THE APPROPRIATE VALUE OF LOCWRT IS ASCERTAINED FROM OUTPUT GENERATED DURING PRECEEDING RUNS
FORWRT	L	TRUE IF PERMANENT FILE DENOTED BY POSNAM IS TO BE CREATED USING UNFORMATTED FORTRAN WRITE. OTHERWISE FILE WILL BE CREATED BY DIRECT TRANSFER USING THE DATA MANAGEMENT SYSTEM DMGASP
DISPLA	L	TRUE IF SELECTED TRANSIENT RESPONSE HISTORIES ARE TO BE DISPLAYED, OTHERWISE FALSE
NPREVT	I	NUMBER OF TIME STEPS PREVIOUSLY COMPUTED WITH RESPONSES SAVED IN PERMANENT FILE DENOTED BY POSNAM. NPREVT WILL BE NONZERO ONLY FOR RESTART RUNS. IT ENSURES THAT ANY RESPONSE DISPLAY MADE IN CONJUNCTION WITH THE TIME INTEGRATION RUN WILL INCLUDE THE ENTIRE HISTORY AVAILABLE FROM THAT FILE AND NOT JUST THE PORTION COMPUTED DURING THE CURRENT RUN
LISTRE	L	TRUE IF TRANSIENT RESPONSE HISTORIES ARE TO BE LISTED IN TABULAR FORM, OTHERWISE FALSE
PRTPLT	L	TRUE IF PRINTER PLOTS ARE TO BE GENERATED FOR TRANSIENT RESPONSE HISTORIES,

		OTHERWISE FALSE
NWETHS	I	NUMBER OF STRUCTURAL HISTORIES (EITHER DISPLACEMENTS OR VELOCITIES) TO BE DISPLAYED FOR WHICH THE APPROPRIATE STRUCTURAL FREEDOMS CAN BE IDENTIFIED INTERNALLY THROUGH THE FREEDOM/EQUATION CORRESPONDENCE TABLE. ALL STRUCTURAL NODES WHICH PARTICIPATE IN THE FLUID-STRUCTURE TRANSFORMATION WILL FALL INTO THIS CATEGORY AS WELL AS ANY OTHERS WHOSE GRID POINT COORDIATES WERE ENTERED AS DATA FOR THE FLUID MASS PROCESSOR
NDRYHS	I	NUMBER OF STRUCTURAL HISTORIES (EITHER DISPLACEMENTS OR VELOCITIES) TO BE DISPLAYED FOR WHICH THE APPROPRIATE STRUCTURAL FREEDOMS CANNOT BE IDENTIFIED INTERNALLY THROUGH THE FREEDOM/EQUATION CORRESPONDENCE TABLE. DRY STRUCTURE NODE POINTS CAN FALL INTO THIS CATEGORY IF THE USER DID NOT INCLUDE THEM IN THE DATA STREAM FOR THE FLUID MASS PROCESSOR. IN THIS CASE ONE MUST IDENTIFY THE INTERNAL SEQUENCE NUMBER APPROPRIATE TO THE DESIRED DEGREE OF FREEDOM BY A MYSTICAL PROCESS WHICH INVOLVES THE INTIMATE KNOWLEDGE OF THE ELIMINATION ORDER AND ANY REDUCTION OF THE NUMBER OF ACTIVE FREEDOMS DUE TO THE APPLICATION OF CONSTRAINTS. MORAL OF THE STORY - RUN ALL STRUCTURAL GRID POINTS THROUGH THE FLUID MASS PROCESSOR EVEN IF THEY NEVER GET WET
NODOUT	I	EXTERNAL INDENTIFICATION NUMBER OF STRUCTURAL NODE FOR WHICH A TIME HISTORY DISPLAY IS DESIRED
NFROUT	I	STRUCTURAL DEGREE OF FREEDOM NUMBER FOR WHICH A TIME HISTORY DISPLAY IS DESIRED
NEQHST	I	INTERNAL SEQUENCE NUMBER DETERMINED BY HAND FOR STRUCTURAL DEGREES OF FREEDOM WHICH ARE TO BE DISPLAYED AND ARE NOT INCLUDED IN THE FREEDOM/EQUATION CORRESPONDENCE TABLE FOR REASONS KNOWN ONLY TO THE USER
NPREHS	I	NUMBER OF FLUID PRESSURE HISTORIES TO BE DISPLAYED
NEQHPR	I	FLUID CONTROL POINT NUMBER FOR WHICH A TIME HISTORY DISPLAY IS DESIRED FOR THE TOTAL PRESSURE
SCALEF	L	TRUE IF A MULTIPLICATIVE CONSTANT FACTOR IS TO BE APPLIED TO THE DISPLAYED VALUES

```
                                  OF THE STRUCTURAL DISPLACEMENT AND
                                  VELOCITY HISTORIES, OTHERWISE FALSE

        FACTOR        E,F         VALUE OF MULTIPLICATIVE LENGTH CONVERSION
                                  FACTOR TO BE APPLIED TO THE DISPLAYED
                                  STRUCTURAL TRANSIENT RESPONSE HISTORIES

        SHSPEC        L           TRUE IF PSEUDO-VELOCITY SHOCK SPECTRA ARE
                                  ALSO DESIRED FOR STRUCTURAL FREEDOMS WHOSE
                                  VELOCITY RESPONSE IS TO BE DISPLAYED,
                                  OTHERWISE FALSE

        SHLIST        L           TRUE IF PSEUDO-VELOCITY SHOCK SPECTRA ARE
                                  TO BE LISTED IN TABULAR FORM, OTHERWISE
                                  FALSE

        SHPRPL        L           TRUE IF PRINTER PLOTS ARE TO BE GENERATED
                                  FOR PSEUDO-VELOCITY SHOCK SPECTRA,
                                  OTHERWISE FALSE

        FREQLW        E,F         LOWER LIMIT OF FREQUENCY RANGE TO BE
                                  SCANNED FOR PSEUDO-VELOCITY SHOCK SPECTRA

        FREQUP        E,F         UPPER LIMIT OF FREQUENCY RANGE TO BE
                                  SCANNED FOR PSEUDO-VELOCITY SHOCK SPECTRA

        DFREQ         E,F         FREQUENCY INCREMENT TO BE USED IN
                                  GENERATING PSEUDO-VELOCITY SHOCK SPECTRA

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

              I N P U T    D A T A    C A R D    D E C K

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

        ALL INPUT DATA EXCEPT ALPHANUMERIC DATA MUST BE RIGHT JUSTIFIED
        IN EIGHT (8) COLUMN FIELDS WHICH CAN OCCUPY THE ENTIRE CARD.
        ALPHANUMERIC DATA MUST BE LEFT JUSTIFIED IN SIXTEEN (16) COLUMN
        FIELDS. FILE NAMES ARE RESTRICTED TO TWELVE (12) CHARACTERS FOR
        UNIVAC OPERATION WHILE SIXTEEN (16) CHARACTERS ARE ALLOWED FOR CDC
        OPERATION. HENCE A NAME LIKE ABCDE·FGHIJK IS THE LIMIT FOR UNIVAC
        WHILE A CDC FILE NAME MAY HAVE FOUR (4) ADDITIONAL CHARACTERS

        GENERAL PROBLEM DEFINITION (SUBROUTINE INPDAT):
        -----------------------------------------------

        72 COLUMN ALPHNUMERIC TITLE
        XC      YC      ZC      SC
        JPHIST
        DTHIST  PNORM
        PHIST(I), I=1,JPHIST
        NTINT
        STRTIM  DELTIM          )
          .       .             )   TOTAL = NTINT
          .       .             )
        FINTM
        PRENAM          POSNAM          RESNAM
        NSAVER  NRESET
```

```
LOCBEG  LOCRES  LOCWRT
FORWRT

POST PROCESSING (SUBROUTINE POSTRE):
------------------------------------

DISPLA

IF DISPLA = .FALSE. THIS TERMINATES THE INPUT DATA DECK

NPREVT

POST PROCESSING (SUBROUTINE RESDSP):
------------------------------------

LISTRE  PRTPLT

POST PROCESSING (SUBROUTINE STRDSP):
------------------------------------

NWETHS  NDRYHS                                )
NODOUT  NFROUT          )                     )
  .       .             )   TOTAL = NWETHS    )   THIS SET FOR
  .       .             )                     )
NODOUT  NFROUT  NEQHST  )                     )   DISPLACEMENTS
  .       .       .     )   TOTAL = NDRYHS    )
  .       .       .     )                     )

NWETHS  NDRYHS                                )
NODOUT  NFROUT          )                     )
  .       .             )   TOTAL = NWETHS    )   THIS SET FOR
  .       .             )                     )
NODOUT  NFROUT  NEQHST  )                     )   VELOCITIES
  .       .       .     )   TOTAL = NDRYHS    )
  .       .             )                     )

POST PROCESSING (SUBROUTINE RESDSP):
------------------------------------

NPREHS
NEQHPR                  )
  .                     )   TOTAL = NPREHS
  .                     )

POST PROCESSING (SUBROUTINE FILBUF):
------------------------------------

SCALEF

IF SCALEF = .TRUE. READ THE FOLLOWING CARD

FACTOR

POST PROCESSING (SUBROUTINE RESDSP):
------------------------------------

SHSPEC
```

```
IF SHSPEC = .TRUE. READ THE FOLLOWING CARDS

SHLIST  SHPRPL
FREQLW  FREQUP  DFREQ
```

AD-A061 443 LOCKHEED MISSILES AND SPACE CO INC PALO ALTO CALIF PA--ETC F/G 19/4
THE UNDERWATER SHOCK ANALYSIS (USA) CODE, A REFERENCE MANUAL.(U)
FEB 78 J A DERUNTZ, T L GEERS, C A FELIPPA DNA001-76-C-0285
UNCLASSIFIED LMSC/D624328 DNA-4524F NL

2 OF 2
AD
A061443



END
DATE
FILMED
2-79
DDC

The following discussion is provided as an aid to user understanding of the sample output that is included here.

First, the amount of storage required for the run given in the output refers solely to the blank common that is set in the main program, UNWASH. An error exit is taken if insufficient storage is available and the user must see that more is provided either by a recompilation on UNIVAC 1100-OS or by a field length request on CDC.

Sector address information for the response and restart files that is listed at various places in the output is extremely important for subsequent restart runs.

Although transient response results can be displayed as part of the run such output has been deferred to the post processing phase in Appendix E for this sample problem.

```
PLANE STEP WAVE SIDE ON TO INFINITE CYLINDER
  10000.      0.       0.   9999.
      2
    50.       1.
     1.       1.
      3
     0.     .025
     1.      .05
     2.       .1
     5.
CYL*PREPN        CYL*RESPON        CYL*RESTAR
      1       30
      0        0        0
      F
      F
```

```
PLANE STEP WAVE SIDE ON TO INFINITE CYLINDER


CHARGE LOCATION DATA:

XC =      .10000000+05

YC =      .00000000

ZC =      .00000000

SC =      .99990000+04

PRESSURE HISTORY DATA:   DTHIST =    .50000000+02

            1           2
       .10000+01   .10000+01

+++  @ ASG,AX          CYL*PREPN.
+++  @ USE      16,    CYL*PREPN.

+++  @ ASG,T              POOL01., F4/      4/ TRK/   256
+++  @ USE      20,       POOL01.

+++  @ ASG,UP         CYL*RESPON.,  F/      4/ TRK/  1024
+++  @ USE      12,   CYL*RESPON.

+++  @ ASG,UP         CYL*RESTAR.,  F/      4/ TRK/  1024
+++  @ USE      14,   CYL*RESTAR.

+++  @ ASG,AX         INF*CYLSKY.
+++  @ USE      22,   INF*CYLSKY.

  12314 WORDS OF STORAGE REQUIRED FOR THIS RUN


+++  @ ASG,T              UNIT13., F4/      4/ TRK/   256
+++  @ USE      13,       UNIT13.

+++  @ ASG,T              UNIT18., F4/      4/ TRK/   256
+++  @ USE      18,       UNIT18.

+++  @ FREE               UNIT13.

RESTART DATA FOR T =     .750000 WRITTEN AT LOCATION     0 ON PERMANENT FILE CYL*RESTAR

POST PROCESSING RESPONSE FILE LOCATION IS  1054
```

```
+++  @ ASG,T            UNIT13., F4/     4/ TRK/   256
+++  @ USE    13,       UNIT13.

+++  @ FREE             UNIT13.

   RESTART DATA FOR T =   2.000000 WRITTEN AT LOCATION   121 ON PERMANENT FILE CYL*RESTAR

   POST PROCESSING RESPONSE FILE LOCATION IS  2074

+++  @ ASG,T            UNIT13., F4/     4/ TRK/   256
+++  @ USE    13,       UNIT13.

+++  @ FREE             UNIT13.

   RESTART DATA FOR T =   5.000000 WRITTEN AT LOCATION   242 ON PERMANENT FILE CYL*RESTAR

   POST PROCESSING RESPONSE FILE LOCATION IS  3094

   SECTOR ADDRESS OF RESTART FILE CYL*RESTAR         AT EXIT IS   363

   SECTOR ADDRESS OF RESPONSE FILE CYL*RESPON         AT EXIT IS  3094

+++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+            A U X I L I A R Y    S T O R A G E    T A B L E            +
+++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+                                                                       +
+ LDI    EXT-NAME UNT EC OPT SEC   CDLOC    NEXT  LIMIT      READ WRITTEN +
+ 10  CYL*RESPON  12 36 UP   28     3094    3094  65536         0   82173 +
+ 12  CYL*RESTAR  14 36 UP   28      363     363  65536         0    9939 +
+ 14   CYL*PREPN  16 36 AX   28       56     128  65536    151956       0 +
+ 16      UNIT18  18 32 T    28       96     576  16384   2733696   48384 +
+ 18      POOL01  20 32 T    28       74      74  16384    247068  120045 +
+ 20  INF*CYLSKY  22 36 AX   28      613     640  65536   1500367       0 +
+                                                                       +
+                   6 ACTIVE DEVICES ( 0 FULL)                          +
+       0 TP-OPS,     585 WRITES,     2776 READS,    4896220 WORDS XFD  +
+++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++

+++  @ FREE        CYL*RESTAR.

+++  @ FREE        CYL*RESPON.
```

APPENDIX E

USER INFORMATION FOR THE POSTPROCESSOR POSTPR

The following includes modifications which were made under separate contract to the Naval Surface Weapons Center, Contract Number N60921-77-C-0112.

This appendix includes a copy of the users manual, and a sample input deck and subsequent output for the infinte cylindrical shell problem presented in Section 4.

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                              P O S T P R

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

   THIS FUNCTIONAL COMPONENT OF THE UNDERWATER SHOCK ANALYSIS CODE
   IS RESPONSIBLE FOR THE TABULATION AND PRINTER-PLOT GRAPHIC DISPLAY
   OF SELECTED TRANSIENT RESPONSES AND PSEUDO-VELOCITY SHOCK SPECTRA
   UPON COMPLETION OF AN UNDERWATER SHOCK ANALYSIS OF A SUBMERGED
   STRUCTURE

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

   THIS PROGRAM WAS DEVELOPED AND CODED BY JOHN A. DERUNTZ, JR.
   OF LOCKHEED MISSILES AND SPACE CO. RESEARCH LABS IN PALO ALTO
   CALIFORNIA. PLEASE CONSULT WITH AUTHOR BEFORE MAKING CHANGES
   AND ALSO REPORT ANY MALFUNCTIONS OR PROBLEMS. WRITE IN CARE OF
   LOCKHEED PALO ALTO RESEARCH LABORATORY, BLDG 205, DEPT 52-33,
   3251 HANOVER ST., PALO ALTO, CALIF., 94304 OR CALL 415-493-4411
   EXTS. 45069 OR 45133.                                FEBRUARY, 1978

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

 W A R N I N G    F R O M    T H E    P R O G R A M M E R    G E N E R A L

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

   THIS CODE CONTAINS THE SPECIAL INGREDIENT DMGASP NOT FOUND IN
   OTHER BRANDS. DMGASP IS A DATA MANAGEMENT UTILITY MODULE THAT
   WILL ACTIVATE AND DEACTIVATE ALL AUXILIARY STORAGE DATA FILES
   REFERENCED BY THE CODE. HENCE THE NAMES OF SUCH FILES SHOULD NOT
   APPEAR ON ANY CONTROL CARDS IN THE RUN STREAM WHICH MIGHT NORMALLY
   ACTIVATE AND DEACTIVATE THE FILES. THE USER IS ALSO CAUTIONED THAT
   PREVIOUSLY CREATED FILES MUST ALREADY BE RESIDENT IN THE SYSTEM
   BEFORE THE RUN IS INITIATED. IF A FILE HAS BEEN ROLLED-OUT TO TAPE
   DMGASP WILL ATTEMPT TO HAVE THE FILE ROLLED-IN EVERY 15 SECONDS
   FOR UP TO 15 MINUTES ON THE UNIVAC 1100-EXEC 8 OPERATING SYSTEM.
   IF AN EXISTING DATA FILE HAS NOT BEEN REFERENCED FOR SOME TIME IT
   IS THEREFORE GOOD POLICY TO SIMPLY ACTIVATE AND DEACTIVATE THE
   FILE BEFORE EXECUTION OF THIS CODE. IF THE USER ATTEMPTS TO CREATE
   A NEW DATA FILE WITH A NAME WHICH IS ALREADY ASSIGNED TO AN
   EXISTING FILE, THE UNIVAC VERSION OF DMGASP WILL MODIFY THE NAME
   OF THE FILE GENERATED BY THIS RUN TO AVOID ANY CONFLICT. FILE NAME
   DUPLICATION WILL CAUSE NO PROBLEM ON THE CDC SCOPE OPERATING
   SYSTEM AS SCOPE WILL SIMPLY CATALOG A NEW CYCLE OF THE SAME FILE.
   ON THE OTHER HAND THE CDC NOS SYSTEM IS SIMILAR TO UNIVAC IN THIS
   REGARD AND THE RUN WILL ABORT SINCE THE NAME-CHANGING FEATURE OF
   DMGASP HAS NOT BEEN IMPLEMENTED FOR NOS. QUALIFIER*FILENAME IS THE
   REQUIRED INPUT DATA FORMAT FOR ALL UNIVAC PERMANENT FILE NAMES.
   FOR CDC OPERATION QUALIFIER IS REPLACED BY THE FILE ID, WHICH IS
   THE USER ID BY DEFAULT

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                         P R O G R A M    S I Z E
```

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      ALL ARRAYS REFERRENCED IN THIS CODE THAT ARE PROBLEM DEPENDENT
      RESIDE IN BLANK COMMON. THE SIZE OF BLANK COMMON IS DETERMINED BY
      A PARAMETER STATEMENT IN THE MAIN PROGRAM FOR THE UNIVAC 1100-OS
      VERSION. HENCE A RECOMPILATION IS NECESSARY TO INCREASE OR
      DECREASE CORE ALLOCATION. IN THE CDC 6600 VERSION RECOMPILATION IS
      UNNECESSARY AS THE LENGTH OF BLANK COMMON IS SET BY A FIELD LENGTH
      REQUEST IN THE CONTROL CARD DECK

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      D E F I N I T I O N    O F    I N P U T    P A R A M E T E R S

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

      INPUT VARIABLE NAMES GIVEN BELOW ARE GENERALLY THOSE WHICH ARE
      ALSO USED IN THE CODING AND THE VARIABLE TYPES CORRESPOND TO
      STANDARD FORTRAN USAGE:

                    A    -    ALPHANUMERIC
                    E    -    FLOATING POINT
                    F    -    FIXED POINT
                    I    -    INTEGER
                    L    -    LOGICAL

      --------      ----                     -----------
      VARIABLE      TYPE                     DESCRIPTION
      --------      ----                     -----------

      JFINTM        I         NUMBER OF TIME POINTS TO BE DISPLAYED

      PRENAM        A         NAME OF PRE-PROCESSED MASS STORAGE FILE
                              CONTAINING ALL FLUID AND STRUCTURE DATA
                              WHICH DOES NOT DEPEND UPON ABOVE LOAD AND
                              INTEGRATION PARAMETERS

      POSNAM        A         NAME OF MASS STORAGE FILE AVAILABLE FOR
                              POST-PROCESSING WHICH CONTAINS SYSTEM
                              RESPONSES

      FORWRT        L         TRUE IF PERMANENT FILE DENOTED BY POSNAM
                              HAS BEEN CREATED USING UNFORMATTED FORTRAN
                              WRITE. OTHERWISE FILE WAS CREATED BY
                              DIRECT TRANSFER USING THE DATA MANAGEMENT
                              SYSTEM DMGASP

      LISTRE        L         TRUE IF TRANSIENT RESPONSE HISTORIES ARE
                              TO BE LISTED IN TABULAR FORM, OTHERWISE
                              FALSE

      PRTPLT        L         TRUE IF PRINTER PLOTS ARE TO BE GENERATED
                              FOR TRANSIENT RESPONSE HISTORIES,
                              OTHERWISE FALSE

      NWETHS        I         NUMBER OF STRUCTURAL HISTORIES (EITHER
                              DISPLACEMENTS OR VELOCITIES) TO BE
                              DISPLAYED FOR WHICH THE APPROPRIATE
```

		STRUCTURAL FREEDOMS CAN BE IDENTIFIED INTERNALLY THROUGH THE FREEDOM/EQUATION CORRESPONDENCE TABLE. ALL STRUCTURAL NODES WHICH PARTICIPATE IN THE FLUID-STRUCTURE TRANSFORMATION WILL FALL INTO THIS CATEGORY AS WELL AS ANY OTHERS WHOSE GRID POINT COORDIATES WERE ENTERED AS DATA FOR THE FLUID MASS PROCESSOR
NDRYHS	I	NUMBER OF STRUCTURAL HISTORIES (EITHER DISPLACEMENTS OR VELOCITIES) TO BE DISPLAYED FOR WHICH THE APPROPRIATE STRUCTURAL FREEDOMS CANNOT BE IDENTIFIED INTERNALLY THROUGH THE FREEDOM/EQUATION CORRESPONDENCE TABLE. DRY STRUCTURE NODE POINTS CAN FALL INTO THIS CATEGORY IF THE USER DID NOT INCLUDE THEM IN THE DATA STREAM FOR THE FLUID MASS PROCESSOR. IN THIS CASE ONE MUST IDENTIFY THE INTERNAL SEQUENCE NUMBER APPROPRIATE TO THE DESIRED DEGREE OF FREEDOM BY A MYSTICAL PROCESS WHICH INVOLVES THE INTIMATE KNOWLEDGE OF THE ELIMINATION ORDER AND ANY REDUCTION OF THE NUMBER OF ACTIVE FREEDOMS DUE TO THE APPLICATION OF CONSTRAINTS. MORAL OF THE STORY - RUN ALL STRUCTURAL GRID POINTS THROUGH THE FLUID MASS PROCESSOR EVEN IF THEY NEVER GET WET
NODOUT	I	EXTERNAL INDENTIFICATION NUMBER OF STRUCTURAL NODE FOR WHICH A *TIME HISTORY* DISPLAY IS DESIRED
NFROUT	I	STRUCTURAL DEGREE OF FREEDOM NUMBER FOR WHICH A TIME HISTORY DISPLAY IS DESIRED
NEQHST	I	INTERNAL SEQUENCE NUMBER DETERMINED BY HAND FOR STRUCTURAL DEGREES OF FREEDOM WHICH ARE TO BE DISPLAYED AND ARE NOT INCLUDED IN THE FREEDOM/EQUATION CORRESPONDENCE TABLE FOR REASONS KNOWN ONLY TO THE USER
NPREHS	I	NUMBER OF FLUID PRESSURE HISTORIES TO BE DISPLAYED
NEQHPR	I	FLUID CONTROL POINT NUMBER FOR WHICH A TIME HISTORY DISPLAY IS DESIRED FOR THE TOTAL PRESSURE
SCALEF	L	TRUE IF A MULTIPLICATIVE CONSTANT FACTOR IS TO BE APPLIED TO THE DISPLAYED VALUES OF THE STRUCTURAL DISPLACEMENT AND VELOCITY HISTORIES, OTHERWISE FALSE
FACTOR	E,F	VALUE OF MULTIPLICATIVE LENGTH CONVERSION FACTOR TO BE APPLIED TO THE DISPLAYED STRUCTURAL TRANSIENT RESPONSE HISTORIES

```

          SHSPEC        L          TRUE IF PSEUDO-VELOCITY SHOCK SPECTRA ARE
                                   ALSO DESIRED FOR STRUCTURAL FREEDOMS WHOSE
                                   VELOCITY RESPONSE IS TO BE DISPLAYED,
                                   OTHERWISE FALSE

          SHLIST        L          TRUE IF PSEUDO-VELOCITY SHOCK SPECTRA ARE
                                   TO BE LISTED IN TABULAR FORM, OTHERWISE
                                   FALSE

          SHPRPL        L          TRUE IF PRINTER PLOTS ARE TO BE GENERATED
                                   FOR PSEUDO-VELOCITY SHOCK SPECTRA,
                                   OTHERWISE FALSE

          FREQLW        E,F        LOWER LIMIT OF FREQUENCY RANGE TO BE
                                   SCANNED FOR PSEUDO-VELOCITY SHOCK SPECTRA

          FREQUP        E,F        UPPER LIMIT OF FREQUENCY RANGE TO BE
                                   SCANNED FOR PSEUDO-VELOCITY SHOCK SPECTRA

          DFREQ         E,F        FREQUENCY INCREMENT TO BE USED IN
                                   GENERATING PSEUDO-VELOCITY SHOCK SPECTRA

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

                    I N P U T    D A T A    C A R D    D E C K

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

          ALL INPUT DATA EXCEPT ALPHANUMERIC DATA MUST BE RIGHT JUSTIFIED
          IN EIGHT (8) COLUMN FIELDS WHICH CAN OCCUPY THE ENTIRE CARD.
          ALPHANUMERIC DATA MUST BE LEFT JUSTIFIED IN SIXTEEN (16) COLUMN
          FIELDS. FILE NAMES ARE RESTRICTED TO TWELVE (12) CHARACTERS FOR
          UNIVAC OPERATION WHILE SIXTEEN (16) CHARACTERS ARE ALLOWED FOR CDC
          OPERATION. HENCE A NAME LIKE ABCDE-FGHIJK IS THE LIMIT FOR UNIVAC
          WHILE A CDC FILE NAME MAY HAVE FOUR (4) ADDITIONAL CHARACTERS

          GENERAL DISPLAY DEFINITION (MAIN PROGRAM POSTPR):
          -------------------------------------------------

          JFINTM
          PRENAM          POSNAM
          FORWRT

          POST PROCESSING (SUBROUTINE RESDSP):
          ------------------------------------

          LISTRE  PRTPLT

          POST PROCESSING (SUBROUTINE STRDSP):
          ------------------------------------

          NWETHS  NDRYHS                           )
          NODOUT  NFROUT          )                )
             .       .            )   TOTAL = NWETHS   )   THIS SET FOR
             .       .            )                )
          NODOUT  NFROUT  NEQHST  )                )   DISPLACEMENTS
             .               .    )   TOTAL = NDRYHS   )
```

```
        .       .        .   )                        )

      NWETHS  NDRYHS                                  )
      NODOUT  NFROUT         )                        )
        .       .            )   TOTAL = NWETHS       )   THIS SET FOR
        .       .            )                        )
      NODOUT  NFROUT  NEQHST )                        )   VELOCITIES
        .       .        .   )   TOTAL = NDRYHS       )
        .       .            )                        )

      POST PROCESSING (SUBROUTINE RESDSP):
      ------------------------------------

      NPREHS
      NEQHPR                 )
        .                    )   TOTAL = NPREHS
        .                    )

      POST PROCESSING (SUBROUTINE FILBUF):
      ------------------------------------

      SCALEF

      IF SCALEF = .TRUE. READ THE FOLLOWING CARD

      FACTOR

      POST PROCESSING (SUBROUTINE RESDSP):
      ------------------------------------

      SHSPEC

      IF SHSPEC = .TRUE. READ THE FOLLOWING CARDS

      SHLIST  SHPRPL
      FREQLW  FREQUP  DFREQ
```

The following discussion is provided as an aid to user understanding of the sample output that is included here.

Perhaps the only item needing discussion is the transient response tabular listings. The desired responses are displayed in matrix form so that each row contains the entire history of a particular degree of freedom except for the first row which is time. Each column therefore contains the instantaneous values of the complete set of response variables desired at a particular time. Each row is identified by the structural or fluid node and its degree of freedom. The letters D, V, and P stand for displacement, velocity, and pressure, respectively.

Essentially the same format is used for the pseudo-velocity shock spectra except that the first row is now frequency rather than time.

```
 1          91
 2      CYL*PREPN       CYL*RESPON
 3           F
 4           T        T
 5           2        0
 6          19        1
 7          19        2
 8           4        0
 9           1        1
10          19        1
11          19        2
12          37        1
13           3
14           1
15          10
16          19
17           F
18           T
19           T        T
20          0.       3.      .025

@XQT

+++  @ ASG,AX          CYL*PREPN.
+++  @ USE      16,    CYL*PREPN.

+++  @ ASG,AX         CYL*RESPON.
+++  @ USE      12,   CYL*RESPON.

+++  @ FREE            CYL*PREPN.
```

TRANSIENT RESPONSE HISTORIES:

	1	2	3	4	5	6	7	8	9	10
	-.00000	.25000-01	.50000-01	.75000-01	.10000+00	.12500+00	.15000+00	.17500+00	.20000+00	.22500+00
19/1 D	.00000	-.12753-05	-.77224-05	-.23777-04	-.51038-04	-.87027-04	-.12574-03	-.15885-03	-.17670-03	-.16889-03
19/2 D	.00000	.29236-08	.29659-07	.15176-06	.53017-06	.14413-05	.32893-05	.66442-05	.12424-04	.22524-04
1/1 V	.00000	-.27908+00	-.73153+00	-.10611+01	-.12968+01	-.14663+01	-.15894+01	-.16799+01	-.17468+01	-.17966+01
19/1 V	.00000	-.10202-03	-.41375-03	-.87059-03	-.13103-02	-.15688-02	-.15284-02	-.11204-02	-.30774-03	.93239-03
19/2 V	.00000	.23388-06	.19049-05	.78632-05	.22409-04	.50478-04	.97367-04	.17102-03	.29135-03	.51665-03
37/1 V	.00000	-.50264-04	-.20279-03	-.42395-03	-.63343-03	-.75075-03	-.71896-03	-.50667-03	-.99344-04	.50879-03
1/0 P	.11765+00	.16364+01	.12208+01	.89650+00	.67491+00	.52977+00	.43563+00	.37507+00	.33664+00	.31318+00
10/0 P	-.00000	.64211-03	.13266-02	.15793-02	.12674-02	.51319-03	-.51817-03	-.16963-02	-.29549-02	-.42601-02
19/0 P	-.00000	.31632-03	.64677-03	.75973-03	.59625-03	.21450-03	-.30061-03	-.88081-03	-.14982-02	-.21359-02

	11	12	13	14	15	16	17	18	19	20
	.25000+00	.27500+00	.30000+00	.32500+00	.35000+00	.37500+00	.40000+00	.42500+00	.45000+00	.47500+00
19/1 D	-.12468-03	-.33284-04	.11673-03	.33923-03	.65309-03	.10853-02	.16751-02	.24783-02	.35705-02	.50459-02
19/2 D	.41557-04	.80926-04	.16707-03	.35588-03	.75424-03	.15467-02	.30205-02	.55762-02	.97110-02	.15963-01
1/1 V	-.18337+01	-.18616+01	-.18827+01	-.18987+01	-.19107+01	-.19198+01	-.19266+01	-.19320+01	-.19363+01	-.19399+01
19/1 V	.26046-02	.47071-02	.72938-02	.10507-01	.14602-01	.19976-01	.27207-01	.37051-01	.50322-01	.67713-01
19/2 V	.10060-02	.21436-02	.47480-02	.10357-01	.21512-01	.41886-01	.76013-01	.12845+00	.20234+00	.29782+00
37/1 V	.13107-02	.22867-02	.34199-02	.46970-02	.61007-02	.76049-02	.91797-02	.10801-01	.12450-01	.14108-01
1/0 P	.30042+00	.29529+00	.29521+00	.29860+00	.30449+00	.31230+00	.32132+00	.33097+00	.34080+00	.35064+00
10/0 P	-.54643-02	-.64894-02	-.73561-02	-.78268-02	-.75895-02	-.60410-02	-.26846-02	.31091-02	.12001-01	.24398-01
19/0 P	-.27410-02	-.32975-02	-.38479-02	-.43822-02	-.48936-02	-.53403-02	-.57484-02	-.61354-02	-.65133-02	-.68839-02

	21	22	23	24	25	26	27	28	29	30
	.50000+00	.52500+00	.55000+00	.57500+00	.60000+00	.62500+00	.65000+00	.67500+00	.70000+00	.72500+00
19/1 D	.70125-02	.95814-02	.12854-01	.16908-01	.21792-01	.27523-01	.34093-01	.41485-01	.49680-01	.58673-01
19/2 D	.24821-01	.36618-01	.51450-01	.69152-01	.89355-01	.11161+00	.13551+00	.16086+00	.18760+00	.21585+00
1/1 V	-.19428+01	-.19453+01	-.19475+01	-.19496+01	-.19518+01	-.19544+01	-.19572+01	-.19601+01	-.19628+01	-.19654+01
19/1 V	.89611-01	.11590+00	.14588+00	.17844+00	.21228+00	.24620+00	.27945+00	.31187+00	.34376+00	.37567+00
19/2 V	.41079+00	.53296+00	.65361+00	.76259+00	.85365+00	.92645+00	.98622+00	.10411+01	.10985+01	.11614+01
37/1 V	.15760-01	.17385-01	.18957-01	.20457-01	.21873-01	.23199-01	.24451-01	.25671-01	.26953-01	.28471-01
1/0 P	.36038+00	.37009+00	.37962+00	.38874+00	.39726+00	.40518+00	.41254+00	.41963+00	.42657+00	.43336+00
10/0 P	.40222-01	.59207-01	.80372-01	.10236+00	.12391+00	.14412+00	.16207+00	.17789+00	.19175+00	.20410+00
19/0 P	-.72627-02	-.76020-02	-.79074-02	-.81906-02	-.84383-02	-.86033-02	-.86646-02	-.84981-02	-.79680-02	-.68358-02

	31	32	33	34	35	36	37	38	39	40
	.75000+00	.77500+00	.80000+00	.82500+00	.85000+00	.87500+00	.90000+00	.92500+00	.95000+00	.97500+00
19/1 D	.68471-01	.79093-01	.90568-01	.10293+00	.11624+00	.13053+00	.14589+00	.16230+00	.17937+00	.19641+00
19/2 D	.24572+00	.27724+00	.31035+00	.34489+00	.38074+00	.41785+00	.45624+00	.49598+00	.53711+00	.57958+00
1/1 V	-.19680+01	-.19708+01	-.19740+01	-.19778+01	-.19818+01	-.19859+01	-.19898+01	-.19935+01	-.19972+01	-.20012+01
19/1 V	.40815+00	.44161+00	.47637+00	.51285+00	.55138+00	.59238+00	.63649+00	.67625+00	.68944+00	.67359+00
19/2 V	.12281+01	.12939+01	.13545+01	.14089+01	.14592+01	.15093+01	.15620+01	.16174+01	.16729+01	.17246+01
37/1 V	.30514-01	.33522-01	.38112-01	.45086-01	.55394-01	.70052-01	.90004-01	.11592+00	.14801+00	.18582+00
1/0 P	.43984+00	.44577+00	.45103+00	.45569+00	.46000+00	.46422+00	.46849+00	.47276+00	.47679+00	.48036+00
10/0 P	.21527+00	.22498+00	.23254+00	.23712+00	.23969+00	.23941+00	.23659+00	.28201+00	.41764+00	.47729+00
19/0 P	-.47574-02	-.12426-02	.43564-02	.12816-01	.25006-01	.41737-01	.63648-01	.91014-01	.12358+00	.16046+00

	41	42	43	44	45	46	47	48	49	50
	.10000+01	.10500+01	.11000+01	.11500+01	.12000+01	.12500+01	.13000+01	.13500+01	.14000+01	.14500+01
19/1 D	.21255+00	.23953+00	.25837+00	.26878+00	.27197+00	.26993+00	.26408+00	.25557+00	.24544+00	.23453+00
19/2 D	.62326+00	.71376+00	.80806+00	.90588+00	.10065+01	.11082+01	.12092+01	.13076+01	.14016+01	.14898+01
1/1 V	-.20056+01	-.20148+01	-.20238+01	-.20327+01	-.20426+01	-.20540+01	-.20661+01	-.20775+01	-.20884+01	-.20997+01
19/1 V	.61773+00	.46115+00	.29254+00	.12395+00	.36494-02	-.85187-01	-.14908+00	-.19103+00	-.21411+00	-.22255+00
19/2 V	.17703+01	.18495+01	.19228+01	.19899+01	.20329+01	.20377+01	.20036+01	.19317+01	.18253+01	.17050+01
37/1 V	.22819+00	.32560+00	.41620+00	.48444+00	.54146+00	.59348+00	.64543+00	.69647+00	.74335+00	.78584+00

1/0 P	.48338+00	.48843+00	.49360+00	.49876+00	.50277+00	.50515+00	.50686+00	.50900+00	.51160+00	.51401+00
10/0 P	.68044+00	.63747+00	.73945+00	.65715+00	.61509+00	.59371+00	.58605+00	.59083+00	.60688+00	.63137+00
19/0 P	.20016+00	.27911+00	.34677+00	.39782+00	.43517+00	.46655+00	.49693+00	.52523+00	.54825+00	.56570+00
	51	52	53	54	55	56	57	58	59	60
	.15000+01	.15500+01	.16000+01	.16500+01	.17000+01	.17500+01	.18000+01	.18500+01	.19000+01	.19500+01
19/1 D	.22342+00	.21240+00	.20145+00	.19036+00	.17891+00	.16707+00	.15499+00	.14278+00	.13053+00	.11822+00
19/2 D	.15726+01	.16516+01	.17291+01	.18068+01	.18850+01	.19629+01	.20389+01	.21126+01	.21852+01	.22582+01
1/1 V	-.21114+01	-.21225+01	-.21311+01	-.21356+01	-.21338+01	-.21228+01	-.20997+01	-.20639+01	-.20182+01	-.19698+01
19/1 V	-.22189+00	-.21876+00	-.21909+00	-.22481+00	-.23323+00	-.24009+00	-.24345+00	-.24456+00	-.24549+00	-.24690+00
19/2 V	.16063+01	.15542+01	.15466+01	.15609+01	.15679+01	.15450+01	.14959+01	.14540+01	.14492+01	.14705+01
37/1 V	.82717+00	.86966+00	.91221+00	.95321+00	.99368+00	.10363+01	.10826+01	.11319+01	.11852+01	.12475+01
1/0 P	.51619+00	.51950+00	.52568+00	.53641+00	.55369+00	.57979+00	.61654+00	.66353+00	.71661+00	.76831+00
10/0 P	.65875+00	.68372+00	.70149+00	.71100+00	.71596+00	.72093+00	.72776+00	.73511+00	.74077+00	.74407+00
19/0 P	.58021+00	.59436+00	.60699+00	.61587+00	.62194+00	.62671+00	.63050+00	.63064+00	.62528+00	.60940+00
	61	62	63	64	65	66	67	68	69	70
	.20000+01	.21000+01	.22000+01	.23000+01	.24000+01	.25000+01	.26000+01	.27000+01	.28000+01	.29000+01
19/1 D	.10587+00	.81879-01	.60223-01	.42058-01	.27701-01	.16760-01	.77386-02	-.10276-02	-.96763-02	-.17404-01
19/2 D	.23320+01	.24800+01	.26326+01	.27987+01	.29806+01	.31720+01	.33656+01	.35544+01	.37381+01	.39234+01
1/1 V	-.19266+01	-.18708+01	-.18589+01	-.18487+01	-.18217+01	-.18166+01	-.18299+01	-.18303+01	-.18223+01	-.18310+01
19/1 V	-.24721+00	-.23263+00	-.20049+00	-.16282+00	-.12433+00	-.94482-01	-.85949-01	-.89375-01	-.83599-01	-.70953-01
19/2 V	.14810+01	.14797+01	.15708+01	.17517+01	.18860+01	.19437+01	.19276+01	.18483+01	.18247+01	.18822+01
37/1 V	.13090+01	.13842+01	.14106+01	.14193+01	.14244+01	.14344+01	.14602+01	.15032+01	.15586+01	.16132+01
1/0 P	.80997+00	.85045+00	.86017+00	.86809+00	.88455+00	.89267+00	.88632+00	.88181+00	.88384+00	.88063+00
10/0 P	.74494+00	.75460+00	.77830+00	.81181+00	.84819+00	.87635+00	.88609+00	.88285+00	.88306+00	.89138+00
19/0 P	.63839+00	.71348+00	.74690+00	.76222+00	.77211+00	.78568+00	.81198+00	.85412+00	.90791+00	95939+00
	71	72	73	74	75	76	77	78	79	80
	.30000+01	.31000+01	.32000+01	.33000+01	.34000+01	.35000+01	.36000+01	.37000+01	.38000+01	.39000+01
19/1 D	-.24176-01	-.30355-01	-.35606-01	-.39271-01	-.41266-01	-.42588-01	-.44682-01	-.47855-01	-.51302-01	-.54542-01
19/2 D	.41109+01	.42912+01	.44600+01	.46209+01	.47778+01	.49325+01	.50897+01	.52534+01	.54217+01	.55896+01
1/1 V	-.18427+01	-.18357+01	-.18271+01	-.18281+01	-.18203+01	-.18003+01	-.17790+01	-.17497+01	-.17150+01	-.17013+01
19/1 V	-.64492-01	-.59076-01	-.45945-01	-.27358-01	-.12553-01	-.13886-01	-.28000-01	-.35451-01	-.33480-01	-.31329-01
19/2 V	.18667+01	.17409+01	.16337+01	.15860+01	.15503+01	.15446+01	.16001+01	.16729+01	.16941+01	.16639+01
37/1 V	.16427+01	.16398+01	.16256+01	.16237+01	.16377+01	.16491+01	.16424+01	.16296+01	.16311+01	.16441+01
1/0 P	.87477+00	.87829+00	.88710+00	.89367+00	.90385+00	.92189+00	.94494+00	.97388+00	.10037+01	.10173+01
10/0 P	.90092+00	.90996+00	.92265+00	.94031+00	.95623+00	.95939+00	.95026+00	.94253+00	.94338+00	.94977+00
19/0 P	.98789+00	.98480+00	.96453+00	.95080+00	.95370+00	.96086+00	.95590+00	.94178+00	.93452+00	.93915+00
	81	82	83	84	85	86	87	88	89	90
	.40000+01	.41000+01	.42000+01	.43000+01	.44000+01	.45000+01	.46000+01	.47000+01	.48000+01	.49000+01
19/1 D	-.57413-01	-.59651-01	-.61445-01	-.63129-01	-.64571-01	-.65986-01	-.68261-01	-.71559-01	-.74743-01	-.76830-01
19/2 D	.57567+01	.59294+01	.61117+01	.62978+01	.64815+01	.66611+01	.68364+01	.70087+01	.71806+01	.73514+01
1/1 V	-.17130+01	-.17281+01	-.17396+01	-.17459+01	-.17386+01	-.17299+01	-.17399+01	-.17560+01	-.17562+01	-.17464+01
19/1 V	-.26093-01	-.18668-01	-.17204-01	-.16490-01	-.12332-01	-.15969-01	-.29544-01	.36408-01	-.27277-01	-.14461-01
19/2 V	.16763+01	.17792+01	.18660+01	.18570+01	.18154+01	.17766+01	.17299+01	.17158+01	.17222+01	.16939+01
37/1 V	.16504+01	.16473+01	.16542+01	.16769+01	.16938+01	.17025+01	.17235+01	.17497+01	.17574+01	.17477+01
1/0 P	.10083+01	.98889+00	.97146+00	.96321+00	.96779+00	.97517+00	.97050+00	.95784+00	.95298+00	.95944+00
10/0 P	.95942+00	.96902+00	.97425+00	.97733+00	.98058+00	.97878+00	.96980+00	.96336+00	.96876+00	.98075+00
19/0 P	.94442+00	.94325+00	.94584+00	.95959+00	.97420+00	.98419+00	.99815+00	.10150+01	.10211+01	.10114+01
	91									
	.50000+01									
19/1 D	-.78088-01									
19/2 D	.75195+01									
1/1 V	-.17399+01									
19/1 V	-.10706-01									

19/2	V	.16681+01
37/1	V	.17340+01
1/0	P	.96874+00
10/0	P	.98798+00
19/0	P	.99333+00

DISPLACEMENT RESPONSE OF STRUCTURAL NODE 19, FREEDOM NUMBER 1:




3.0
3.5
4.0
4.5
5.0
5.5
6.0
.2720
0.0
-.2720


DISPLACEMENT RESPONSE OF STRUCTURAL NODE 19, FREEDOM NUMBER 2:
-0.00
.50
1.00
1.5
2.0
2.5
3.0
7.519
0.0
-7.519


3.0
3.5
4.0
4.5
5.0
5.5
6.0
7.519
0.0
-7.519

VELOCITY RESPONSE OF STRUCTURAL NODE 1, FREEDOM NUMBER 1:




3.0
3.5
4.0
4.5
5.0
5.5
6.0
2.136
0.0
-2.136

VELOCITY RESPONSE OF STRUCTURAL NODE 19, FREEDOM NUMBER 1:





6.0
5.5
5.0
4.5
4.0
3.5
3.0
.6894
0.0
-.6894

VELOCITY RESPONSE OF STRUCTURAL NODE 19, FREEDOM NUMBER 2:




3.0
3.5
4.0
4.5
5.0
5.5
6.0
2.038
0.0
-2.038

VELOCITY RESPONSE OF STRUCTURAL NODE 37, FREEDOM NUMBER 1:




3.0
3.5
4.0
4.5
5.0
5.5
6.0
1.757
0.0
-1.757

PRESSURE RESPONSE OF FLUID NODE 1:




6.0
5.5
5.0
4.5
4.0
3.5
3.0
1.636
0.0
-1.636

PRESSURE RESPONSE OF FLUID NODE 10:





3.0
3.5
4.0
4.5
5.0
5.5
6.0
.9880
0.0
-.9880

PRESSURE RESPONSE OF FLUID NODE 19:





+++ @ ASG,T UNIT13., F4/ 4/ TRK/ 256
+++ @ USE 13,

+++ ● FREE UNIT13.

PSEUDO-VELOCITY SHOCK SPECTRA:

	1	2	3	4	5	6	7	8	9	10
	.00000	.25000-01	.50000-01	.75000-01	.10000+00	.12500+00	.15000+00	.17500+00	.20000+00	.22500+00
1/1	.00000	.13014+01	.18344+01	.19197+01	.19774+01	.20305+01	.21886+01	.22251+01	.22209+01	.22064+01
19/1	.00000	.42646-01	.84839-01	.12613+00	.16609+00	.20429+00	.26137+00	.32711+00	.39992+00	.49659+00
19/2	.00000	.10901+01	.16846+01	.16952+01	.17332+01	.16892+01	.16142+01	.16533+01	.16951+01	.17248+01
37/1	.00000	.84302+00	.14346+01	.16052+01	.15292+01	.14698+01	.14013+01	.13251+01	.12529+01	.11983+01
	11	12	13	14	15	16	17	18	19	20
	.25000+00	.27500+00	.30000+00	.32500+00	.35000+00	.37500+00	.40000+00	.42500+00	.45000+00	.47500+00
1/1	.22076+01	.21887+01	.21424+01	.20849+01	.20077+01	.19200+01	.19095+01	.19027+01	.18967+01	.18902+01
19/1	.57905+00	.65309+00	.72302+00	.79459+00	.86051+00	.91182+00	.95711+00	.99446+00	.10390+01	.10748+01
19/2	.17546+01	.17780+01	.17904+01	.17898+01	.17753+01	.17586+01	.18029+01	.18885+01	.19297+01	.19885+01
37/1	.11490+01	.10963+01	.10394+01	.98378+00	.92907+00	.87375+00	.82580+00	.78668+00	.75383+00	.72507+00
	21	22	23	24	25	26	27	28	29	30
	.50000+00	.52500+00	.55000+00	.57500+00	.60000+00	.62500+00	.65000+00	.67500+00	.70000+00	.72500+00
1/1	.18835+01	.18772+01	.18709+01	.18645+01	.18571+01	.18496+01	.18440+01	.19723+01	.20882+01	.21073+01
19/1	.11012+01	.11305+01	.11575+01	.11675+01	.11599+01	.11747+01	.11593+01	.11619+01	.11530+01	.11495+01
19/2	.21126+01	.22619+01	.24620+01	.26596+01	.27382+01	.27053+01	.26852+01	.25425+01	.23028+01	.20715+01
37/1	.69944+00	.67562+00	.65309+00	.63425+00	.61466+00	.59839+00	.58112+00	.56750+00	.55211+00	.53961+00
	31	32	33	34	35	36	37	38	39	40
	.75000+00	.77500+00	.80000+00	.82500+00	.85000+00	.87500+00	.90000+00	.92500+00	.95000+00	.97500+00
1/1	.21711+01	.21366+01	.21064+01	.20922+01	.20138+01	.20158+01	.19031+01	.18830+01	.18247+01	.17736+01
19/1	.11434+01	.11451+01	.11518+01	.11564+01	.11506+01	.11504+01	.11510+01	.11429+01	.11264+01	.11259+01
19/2	.18421+01	.16585+01	.14813+01	.13504+01	.12829+01	.11949+01	.11163+01	.10808+01	.10630+01	.10429+01
37/1	.52770+00	.51454+00	.50361+00	.49422+00	.48392+00	.47276+00	.46455+00	.45731+00	.44942+00	.44088+00
	41	42	43	44	45	46	47	48	49	50
	.10000+01	.10250+01	.10500+01	.10750+01	.11000+01	.11250+01	.11500+01	.11750+01	.12000+01	.12250+01
1/1	.17451+01	.17379+01	.17249+01	.17158+01	.17072+01	.17023+01	.16951+01	.16858+01	.16742+01	.16798+01
19/1	.11194+01	.11063+01	.10869+01	.10728+01	.10651+01	.10757+01	.11138+01	.11078+01	.10812+01	.11177+01
19/2	.10273+01	.10099+01	.99269+00	.97822+00	.96218+00	.94684+00	.93399+00	.91986+00	.90508+00	.89430+00
37/1	.43170+00	.42636+00	.44755+00	.48110+00	.49497+00	.53597+00	.53319+00	.53282+00	.54147+00	.50232+00
	51	52	53	54	55	56	57	58	59	60
	.12500+01	.12750+01	.13000+01	.13250+01	.13500+01	.13750+01	.14000+01	.14250+01	.14500+01	.14750+01
1/1	.17505+01	.18412+01	.18527+01	.18375+01	.18510+01	.18279+01	.17660+01	.17392+01	.17000+01	.16934+01
19/1	.10651+01	.10064+01	.10030+01	.97805+00	.95344+00	.92307+00	.88025+00	.84340+00	.85533+00	.83648+00
19/2	.88246+00	.86960+00	.85768+00	.84835+00	.83819+00	.82722+00	.81548+00	.80688+00	.79877+00	.79001+00
37/1	.50696+00	.46752+00	.43867+00	.40775+00	.37769+00	.36234+00	.35386+00	.34400+00	.34035+00	.33630+00
	61	62	63	64	65	66	67	68	69	70
	.15000+01	.15250+01	.15500+01	.15750+01	.16000+01	.16250+01	.16500+01	.16750+01	.17000+01	.17250+01
1/1	.16390+01	.16210+01	.15990+01	.15673+01	.15628+01	.15572+01	.15507+01	.15431+01	.15345+01	.15249+01
19/1	.79135+00	.77641+00	.76106+00	.74546+00	.72977+00	.71412+00	.69861+00	.68334+00	.66839+00	.65382+00
19/2	.78064+00	.87869+00	.10789+01	.13343+01	.14083+01	.16471+01	.16841+01	.16272+01	.16961+01	.14589+01
37/1	.33188+00	.32709+00	.32194+00	.31647+00	.31068+00	.30461+00	.29827+00	.29502+00	.29182+00	.28839+00
	71	72	73	74	75	76	77	78	79	80
	.17500+01	.17750+01	.18000+01	.18250+01	.18500+01	.18750+01	.19000+01	.19250+01	.19500+01	.19750+01
1/1	.15786+01	.16681+01	.16702+01	.16511+01	.16675+01	.16171+01	.15754+01	.15579+01	.14862+01	.14629+01
19/1	.63966+00	.63128+00	.62454+00	.61810+00	.61200+00	.60625+00	.60086+00	.59583+00	.59115+00	.58680+00
19/2	.13985+01	.13197+01	.12954+01	.11722+01	.10146+01	.97377+00	.89731+00	.79299+00	.67025+00	.63994+00
37/1	.28474+00	.28089+00	.27688+00	.27271+00	.26842+00	.26403+00	.25956+00	.25503+00	.25046+00	.24588+00

	81	82	83	84	85	86	87	88	89	90
	.20000+01	.20250+01	.20500+01	.20750+01	.21000+01	.21250+01	.21500+01	.21750+01	.22000+01	.22250+01
1/1	.14544+01	.14452+01	.14352+01	.14246+01	.14217+01	.14191+01	.14160+01	.14124+01	.14083+01	.14037+01
19/1	.58276+00	.57900+00	.57547+00	.57215+00	.56899+00	.56594+00	.56296+00	.56000+00	.55701+00	.55393+00
19/2	.62441+00	.61714+00	.61198+00	.60661+00	.60106+00	.59532+00	.58940+00	.58332+00	.57708+00	.57070+00
37/1	.24130+00	.23674+00	.23222+00	.22775+00	.22333+00	.21898+00	.21471+00	.21538+00	.20954+00	.21449+00

	91	92	93	94	95	96	97	98	99	100
	.22500+01	.22750+01	.23000+01	.23250+01	.23500+01	.23750+01	.24000+01	.24250+01	.24500+01	.24750+01
1/1	.13986+01	.13976+01	.14629+01	.15070+01	.15447+01	.15356+01	.15199+01	.14579+01	.13403+01	.13309+01
19/1	.55073+00	.54735+00	.54374+00	.53985+00	.53565+00	.53108+00	.52610+00	.52068+00	.51986+00	.52220+00
19/2	.56417+00	.55750+00	.55072+00	.54382+00	.53680+00	.52977+00	.52537+00	.52086+00	.60781+00	.67320+00
37/1	.21652+00	.22477+00	.25016+00	.26635+00	.27196+00	.26633+00	.26580+00	.31912+00	.30518+00	.29343+00

	101	102	103	104	105	106	107	108	109	110
	.25000+01	.25250+01	.25500+01	.25750+01	.26000+01	.26250+01	.26500+01	.26750+01	.27000+01	.27250+01
1/1	.13217+01	.13316+01	.13180+01	.13157+01	.13146+01	.13100+01	.13067+01	.13031+01	.12991+01	.12964+01
19/1	.52435+00	.52628+00	.52794+00	.52930+00	.53032+00	.53095+00	.53118+00	.53096+00	.53026+00	.52906+00
19/2	.62558+00	.55560+00	.62221+00	.58126+00	.59594+00	.62188+00	.63133+00	.62350+00	.59845+00	.61271+00
37/1	.34239+00	.33017+00	.31349+00	.30253+00	.29094+00	.29785+00	.30171+00	.29524+00	.28251+00	.26966+00

	111	112	113	114	115	116	117	118	119	120
	.27500+01	.27750+01	.28000+01	.28250+01	.28500+01	.28750+01	.29000+01	.29250+01	.29500+01	.29750+01
1/1	.14662+01	.15600+01	.16309+01	.16700+01	.16998+01	.16102+01	.15540+01	.14413+01	.13010+01	.12356+01
19/1	.52734+00	.52508+00	.52225+00	.51884+00	.51486+00	.51028+00	.50512+00	.49938+00	.49307+00	.48620+00
19/2	.62470+00	.67364+00	.78839+00	.90180+00	.88474+00	.94333+00	.93318+00	.96958+00	.94031+00	.94437+00
37/1	.25886+00	.26088+00	.25964+00	.27704+00	.27359+00	.25928+00	.24275+00	.25174+00	.23984+00	.24993+00

	121
	.30000+01
1/1	.12281+01
19/1	.47879+00
19/2	.97503+00
37/1	.25167+00

PSEUDO-VELOCITY SHOCK SPECTRUM FOR STRUCTURAL NODE 1, FREEDOM NUMBER 1:



PSEUDO-VELOCITY SHOCK SPECTRUM FOR STRUCTURAL NODE 19, FREEDOM NUMBER 1:



PSEUDO-VELOCITY SHOCK SPECTRUM FOR STRUCTURAL NODE 19, FREEDOM NUMBER 2:



PSEUDO-VELOCITY SHOCK SPECTRUM FOR STRUCTURAL NODE 37, FREEDOM NUMBER 1:



+++ @ FREE CYL*RESPON.

APPENDIX F

USER INSTRUCTIONS FOR INTERFACING WITH USA

To use the Underwater Shock Analysis (USA) Code in its linear stand-alone mode, the user must first construct a permanent data file that contains the structural mass and stiffness matrices and some assorted bookkeeping information. The purpose of this appendix is to describe the structure of the file and to specify how it is to be created. At this time utility routines that carry out this task have been written for SPAR and NASTRAN. An abbreviated form of this file is also required when USA is coupled with a nonlinear structural analyzer and such an interface also exists for STAGS.

USA contains the data management utility module DMGASP that carries out all data transfer activities between core and peripheral storage. This is done by unformatted and unbuffered data transmissions and it is imperative that DMGASP be used to create the structural interface file. Otherwise the user must supply or have access to a similar means of direct transfer. Section 3 of [10] contains a comprehensive discussion of the half-dozen or so DMGASP commands that are required to activate, position, write upon, read from, and free a peripheral storage device. Subsidiary commands also exist for error handling and listing of selected information pertaining to auxiliary storage.

The current configuration of USA uses a diagonal mass matrix associated with a lumped mass representation of the structure, assumes that there is no velocity dependent structural damping, and further, only, single precision matrices may be processed. In addition, if the stiffness matrix has been reordered or reduced in any way for input to USA the mass matrix must also be reordered or condensed so that its degrees of freedom (DOF) are the same and appear in the same order as in the stiffenss matrix. Finally, the stiffness matrix must be placed in a multi-block* skyline format as discussed in [13]. This description consists of a Matrix Master Record (MMR) followed by a series of Matrix Value Records (MVR) which contain the numerical values of the matrix. These are the only constructs the user need be concerned with; all others required are already embedded in USA. During construction of the MMR a logical device index (LDI) must be set in the record which USA will access later. For UNIVAC operation, this should be set equal to twenty (20), while for CDC operation this should be set as two (2).

The file structure required is shown in Table F-1 where NDOF stands for the number of structural DOF which USA must process. NMMR is the number of words in the matrix master record, and NWBL is the number of words in each matrix value record (which is expected to be the same for each record). NWBL should also be an integer multiple of 448 for most efficient use of storage.

* For small problems a single block is permissible.

Table F-1

Record	Number of Words	Data
1	1	NDOF
2	NDOF	Diagonal Mass Matrix
3	1	NDOF
4	NDOF	Grid Point/DOF Vector
5	1	NMMR
6	NMMR	Matrix Master Record for Stiffness Matrix
7	NWBL	First Matrix Value Record for Stiffness Matrix
.	NWBL	Second Matrix Value Record for Stiffness Matrix
.	.	
.	NWBL	Last Matrix Value Record for Stiffness Matrix

The Grid Point/DOF vector consists of an integer value for each global DOF from 1 through NDOF that is constructed as ten times the external node number plus the local DOF number that apply to that particular structural equation.

For example, if the 87th DOF to appear in the mass and stiffness matrices corresponds to the second degree of freedom at a node identified externally as 4637 then the 87th entry in the Grid Point/DOF vector would be 46372. Local translational degrees of freedom should be numbered 1-3, rotational degrees of freedom should be numbered from 4-6 and any others should be numbered with 7-9. If more than 9 degrees of freedom are carried at any node it is a simple matter to change the factor of ten to one hundred in a few places in USA to accommodate this.

It should be noted that records 1-4 are accessed by the USA pre-processor AUGMAT before the time integration phase of the analysis commences. This portion of the file is required for both USA in the linear stand-alone mode, and for USA when it is interfaced with a nonlinear structural analyzer. In this latter case, the fifth and succeeding records do not exist.

DISTRIBUTION LIST

DEPARTMENT OF DEFENSE

Assistant to the Secretary of Defense
Atomic Energy
ATTN: Executive Assistant

Defense Advanced Rsch. Proj. Agency
ATTN: TIO
ATTN: A. Lachmindji
ATTN: STO, K. Kresa
ATTN: R. Chapman

Defense Civil Preparedness Agency
Assistant Director for Research
ATTN: Admin. Officer

Defense Documentation Center
Cameron Station
12 cy ATTN: TC

Defense Intelligence Agency
ATTN: DI-7E
ATTN: DB-4C, E. O'Farrell
ATTN: DT-1C
ATTN: DT-2
2 cy ATTN: DB-4E

Defense Nuclear Agency
ATTN: DDST
2 cy ATTN: SPSS
4 cy ATTN: TITL

Field Command
Defense Nuclear Agency
ATTN: FCPR, J. Hill
ATTN: FCPR

Interservice Nuclear Weapons School
ATTN: Document Control

Joint Strat. Tgt. Planning Staff
ATTN: NRI-STINFO, Library

Livermore Division, Field Command, DNA
Department of Defense
Lawrence Livermore Laboratory
ATTN: FCPRL

NATO School (SHAPE)
ATTN: U.S. Documents Officer

Under Secretary of Defense for Rsch. & Engrg.
ATTN: Strategic & Space Systems (OS)

DEPARTMENT OF THE ARMY

Deputy Chief of Staff for Ops. & Plans
Department of the Army
ATTN: MOCA-ADL

Deputy Chief of Staff for Rsch. Dev. & Acq.
Department of the Army
ATTN: DAMA-AOA-M
ATTN: DAMA-CSM-N, G. Ogden

DEPARTMENT OF THE ARMY (Continued)

Harry Diamond Laboratories
Department of the Army
ATTN: DELHD-TI
ATTN: DELHD-NP

Redstone Scientific Information Ctr.
U.S. Army R&D Command
ATTN: Chief, Documents

U.S. Army Ballistic Research Labs
ATTN: Technical Library, E. Baicy

U.S. Army Communications Command
ATTN: Technical Reference Division

U.S. Army Engr. Waterways Exper. Station
ATTN: Library
ATTN: W. Flathau
ATTN: J. Strange

U.S. Army Mat. & Mechanics Rsch. Ctr.
ATTN: Technical Library
ATTN: R. Shea

U.S. Army Materiel Dev. & Readiness Cmd.
ATTN: DRXAM-TL

U.S. Army Mobility Equip. R&D Cmd.
ATTN: DRDME-WC

U.S. Army Nuclear & Chemical Agency
ATTN: Library

U.S. Army War College
ATTN: Library

DEPARTMENT OF THE NAVY

Civil Engineering Laboratory
Naval Construction Battalion Center
ATTN: Code L08A
ATTN: R. Odello

David W. Taylor Naval Ship R&D Ctr.
ATTN: Code L42-3
ATTN: Code 1740.5, B. Whang
ATTN: Code 1740.1, W. Sykes
ATTN: Code 1171
ATTN: Code 2740, Y. Wang
ATTN: Code 172, R. Jones
3 cy ATTN: Code 177, E. Palmer

Naval Facilities Engineering Command
ATTN: Code 09M22C

Naval Postgraduate School
ATTN: Code 2124, Tech. Rpts. Librarian
ATTN: R. Newton

Naval Research Laboratory
ATTN: Code 2627, Technical Library
ATTN: Code 8442, H. Hwang
ATTN: Code 8440, F. Rosenthal
2 cy ATTN: Code 8403A, G. O'Hara

DEPARTMENT OF THE NAVY (Continued)

Chief of Naval Material
ATTN: MAT 0323

Naval Ocean Systems Center
ATTN: Technical Library

Naval Sea Systems Command
ATTN: ORD-91313
ATTN: Code 03511, C. Pohler

Naval Ship Engineering Center
ATTN: Code 09G3
ATTN: NSEC 6110.01
ATTN: NSEC 6105C1
ATTN: NSEC 6120D
ATTN: NSEC 6105G
2 cy ATTN: NSEC 6105

Naval Surface Weapons Center
Dahlgren Laboratory
ATTN: Technical Library & Info. Services Br.

Naval Weapons Center
ATTN: Code 533

Naval Weapons Evaluation Facility
ATTN: Code 10

Office of Naval Research
ATTN: Code 715
ATTN: Code 474, N. Perrone

Office of the Chief of Naval Operations
ATTN: OP 981
ATTN: OP 03EG

Strategic Systems Project Office
Department of the Navy
ATTN: NSP-43
ATTN: NSP-272

Naval Electronic Systems Command
ATTN: PME 117-21A

Naval Surface Weapons Center
ATTN: Code F31
2 cy ATTN: Code R14, I. Blatstein

Naval Underwater Systems Center
ATTN: Code EM, J. Kalinowski

DEPARTMENT OF THE AIR FORCE

Air Force Institute of Technology, Air University
ATTN: Library, AFIT Bldg. 640, Area B

Air Force Weapons Laboratory
ATTN: SUL

Assistant Chief of Staff
Intelligence
Department of the Air Force
ATTN: INATA

Rome Air Development Center
Air Force Systems Command
ATTN: Documents Library/TSLD

DEPARTMENT OF THE AIR FORCE (Continued)

Strategic Air Command/XPFS
ATTN: NRI-STINFO, Library

Air Force Geophysics Laboratory
ATTN: SUDL

Aeronautical Systems Division, AFSC
ATTN: Technical Library

DEPARTMENT OF ENERGY

Department of Energy
Albuquerque Operations Office
ATTN: Doc. Con. for Technical Library

Department of Energy
Library Room G-042
ATTN: Doc. Con. for Classified Library

Department of Energy
Nevada Operations Office
ATTN: Doc. Con. for Technical Library

Lawrence Livermore Laboratory
ATTN: Doc. Con. for Tech. Info. Dept. Library

Sandia Laboratories
Livermore Laboratory
ATTN: Doc. Con. for Library & Security Classification Division

Los Alamos Scientific Laboratory
ATTN: Doc. Con. for Reports Library

Sandia Laboratories
ATTN: Doc. Con. for 3141

OTHER GOVERNMENT AGENCY

Department of the Interior
Bureau of Mines
ATTN: Technical Library

DEPARTMENT OF DEFENSE CONTRACTORS

Aerospace Corporation
ATTN: Tech. Info. Services

Avco Research & Systems Group
ATTN: Library, A830

Battelle Memorial Institute
ATTN: Library

BDM Corporation
ATTN: Corporate Library

The Boeing Company
ATTN: Aerospace Library

Agbabian Associates
ATTN: M. Agbabian

Calspan Corporation
ATTN: Library

EG&G Washington Analytical Services Ctr., Inc.
ATTN: Library

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

University of Denver
Colorado Seminary
Denver Research Institute
ATTN: Sec. Officer for F. Venditti

General Electric Company-TEMPO
Center for Advanced Studies
ATTN: DASIAC

IIT Research Institute
ATTN: Documents Library

General Dynamics Corporation
Electric Boat Division
ATTN: L. Chan

Cambridge Acoustical Assoc., Inc.
ATTN: M. Junger

Civil/Nuclear Systems Corporation
ATTN: T. Duffy

Columbia University
Dept. of Civil Engineering
ATTN: F. DiMaggio
ATTN: H. Bleich

Institute for Defense Analyses
ATTN: Classified Library

Kaman AviDyne
Division of Kaman Sciences Corporation
ATTN: Library
ATTN: E. Criscione
ATTN: G. Zartarian

Kaman Sciences Corporation
ATTN: Library

Lockheed Missiles & Space Company, Inc.
ATTN: TIC-Library

Lockheed Missiles and Space Company, Inc.
ATTN: Tech. Info. Ctr., D.Coll.
ATTN: C. Felippa
ATTN: J. DeRuntz
3 cy ATTN: T. Geers

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

Nathan M. Newmark
Consulting Engineering Services
ATTN: N. Newmark

University of Maryland
Dept. of Civil Engineering
ATTN: B. Berger

Merritt CASES, Inc.
ATTN: Library

Pacifica Technology
ATTN: J. Kent

Physics International Company
ATTN: Doc. Con. for Technical Library

R&D Associates
ATTN: Technical Information Center

Science Applications, Inc.
ATTN: Technical Library

SRI International
ATTN: B. Gasten
ATTN: G. Abrahamson

Polytechnic Institute of New York
ATTN: J. Klosner

Systems, Science & Software, Inc.
ATTN: Library

Terra Tek, Incorporated
ATTN: Library

Tetra Tech, Incorporated
ATTN: Library
ATTN: L. Hwang

TRW Defense & Space Sys. Group
ATTN: Technical Information Center

Weidlinger Assoc., Consulting Engineers
ATTN: D. Ranlet
2 cy ATTN: M. Baron

Weidlinger Assoc., Consulting Engineers
ATTN: J. Isenberg